



DATA SHEET

MMDT3904

- ◇Epoxy meets UL 94 V-0 flammability rating
- ◇Lead Free Finish/RoHS Compliant
- ◇For Switching and AF Amplifier Applications
- ◇Rugged and reliable

Device Marking Code	
MMDT3904	K6N

Equivalent Circuit



MAXIMUM RATINGS (Ta = 25 °C)







Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	60	V
V_{CEO}	Collector-Emitter Voltage	40	V
V_{EBO}	Emitter-Base Voltage	5	V
P_C	Collector Power Dissipation	200	mW
I_C	Collector Current	200	mA
T_J	Junction Temperature	150	°C
T_{STG}	Storage Temperature	-55 to 150	°C

ELECTRICAL CHARACTERISTICS (Ta = 25 °C)

Symbol	Parameter	Test conditions	Min	Typ	Max	Unit
$V_{(BR)CBO}$	Collector-base breakdown voltage	$I_C=10\mu A, I_E=0$	60			V
$V_{(BR)CEO}$	Collector-emitter breakdown voltage	$I_C=1mA, I_B=0$	40			V
$V_{(BR)EBO}$	Emitter-base breakdown voltage	$I_E=10\mu A, I_C=0$	5			V
I_{CBO}	Collector cut-off current	$V_{CB}=30V, I_E=0$			50	nA
I_{EBO}	Emitter-Base Cutoff Current	$V_{EB}=5V, I_C=0$			50	nA
I_{CEX}	Collector cut-off current	$V_{CE}=30V, V_{BE(off)}=3V$			50	nA
h_{FE}	DC current gain*	$V_{CE}=1V, I_C=0.1mA$	40			
		$V_{CE}=1V, I_C=1mA$	70			
		$V_{CE}=1V, I_C=10mA$	100		300	
		$V_{CE}=1V, I_C=50mA$	60			
		$V_{CE}=1V, I_C=100mA$	30			
$V_{CE(sat)}$	Collector-emitter saturation voltage	$I_C=10mA, I_B=1mA$			0.2	V
		$I_C=50mA, I_B=5mA$			0.3	V

$V_{BE(sat)}$	Base-emitter saturation voltage	$I_C=10mA, I_B=1mA$	0.65		0.85	V
		$I_C=50mA, I_B=5mA$			0.95	
f_T	Transition frequency	$V_{CE}=20V, I_C=10mA$ $f=100MHz$	300			MHZ
Cob	Collector output capacitance	$V_{CB}=5V, I_E=0$ $f=1MHz$			4	pF
NF	Noise figure	$V_{CE}=5V, I_C=0.1mA$ $f=1kHz, R_S=1K\Omega$			5	dB
t_d	Delay time	$V_{CC}=3V, V_{BE(off)}=-0.5V$ $I_C=10mA, I_{B1}=-I_{B2}=1mA$			35	nS
t_r	Rise time				35	nS
t_s	Storage time	$V_{CC}=3V, I_C=10mA$ $I_{B1}=-I_{B2}=1mA$			200	nS
t_f	Fall time				50	nS

TYPICAL CHARACTERISTICS




ORDERING INFORMATION

Device	Package	Shipping	Tape wide	Emboss pitch	Tape specification	Notes
MMDT3904	SOT363-6L	Tape & Reel 3000pcs /7" Reel	8mm	4mm	Conductive	


PACKAGE DIMENSIONS

Package outline : SOT363-6L

TOP VIEW




SIDE VIEW




SYMBOL	DIMENSIONS IN MILLIMETER	
	MIN	MAX
A	0.900	1.000
A1	0.000	0.100
A2	0.900	1.000
b	0.150	0.350
c	0.100	0.150
D	2.000	2.200
E	1.150	1.350
E1	2.150	2.400
e	0.650 TYP.	
e1	1.200	1.400
L	0.525 REF.	
L1	0.260	0.460
θ	0°	8°

FRONT VIEW



SOLDERING PATTERN



Notice:

- Lead plating: Pb free solder
- Lead thickness includes solder plating
- Lead frame: CAC-5
- Other Tolerance: ±0.05
- Dimensions are exclusive of Burrs, Mold Flash and Tie Bar extrusions
- Unit: mm

NOTICE

AM'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS COMPONENTS IN ANY LIFE SUPPORT DEVICES OR SYSTEMS.

AM reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. AM does not assume any liability arising out of the application or use of any product described herein.