

Part Number: 768290104

Product Description: Mega-Fit Slim Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 4 Circuits, 1.52µm Tin (Sn) Plating, Glow-

Wire Capable, Black Series Number: 76829

**Status:** Active

**Product Category: PCB Headers and** 

Receptacles



#### **Documents & Resources**

### **Drawings**

<u>Drawing 768290104\_sd.pdf</u> Packaging Design Drawing 768291100-000.pdf

## 3D Models and Design Files

3D Model 768290104\_stp.zip 3D Model PDF 768290104.pdf

## **Specifications**

Application Specification AS-76823-100-001.pdf
Application Specification 768232000-AS-000.pdf
Product Specification 1720631000-PS-000.pdf
Product Specification PS-76823-100-001.pdf
Test Summary TS-76823-100-001.pdf
Test Summary 1720631000-TS-000.pdf

# **Product Environment Compliance**

# Compliance

GADSL/IMDS	Compliant with Exemption 44; 33
G/(D3E/IIVID3	Compliant with Exemption 44, 55
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

**Multiple Part Product Compliance Statements** 

- Eu RoHS
- REACH SVHC
- Low-Halogen

# Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

## **Part Details**

### General

Status	Active
Category	PCB Headers and Receptacles
Series	76829
Description	Mega-Fit Slim Vertical Header, Through Hole, 5.70mm Pitch, Dual Row, 4 Circuits, 1.52µm Tin (Sn) Plating, Glow-Wire Capable, Black
Application	Power, Wire-to-Board
Component Type	PCB Header
Product Family	Mega-Fit Power Connectors
Product Name	Mega-Fit
UPC	889056895552

# Agency

UL	E29179
----	--------

#### **Electrical**

Current - Maximum per Contact	23.5A
Voltage - Maximum	600V AC (RMS)/DC

# **Physical**

Breakaway	No
Circuits (Loaded)	4
Circuits (maximum)	4

Color - Resin	Black
Durability (mating cycles max)	25
First Mate / Last Break	No
Flammability	94V-0
Glow-Wire Capable	Yes
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Mated Height	16.78mm
Material - Metal	High Conductivity Copper
Material - Plating Mating	Matte Tin
Material - Plating Termination	Matte Tin
Material - Resin	Liquid Crystal Polymer
Net Weight	2.394/g
Number of Rows	2
Orientation	Vertical
Packaging Type	Tray
PC Tail Length	3.73mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.58mm
Pitch - Mating Interface	5.70mm
Pitch - Termination Interface	5.70mm
Plating min - Mating	1.524µm
Plating min - Termination	1.524µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Shrouded	Yes
Temperature Range - Operating	-40° to +105°C
Termination Interface Style	Through Hole
Unmated Height	14.80mm

# Mates With / Use With

# Mates with Part(s)

Description	Part Number
2 00 0 [0 0. 0	1 5.1 5 1 1 5.1 1 5 5 1

Mega-Fit Dual Row Receptacle Housings	170001
Mega-Fit Dual Row Receptacle Housings	<u>171692</u>
Mega-Fit-to-Mega-Fit Off-the-Shelf (OTS) Cable Assemblies	<u>45136</u>

This document was generated on Aug 25, 2023