

NHESD5Z5.0CA

Transient Voltage Suppressors for ESD Protection



V_{RWM} :	5.0	Volts
-------------	-----	-------

P_{PP} :	85	Watts
------------	----	-------


SOD-523	Marking and Polarity
---------	----------------------

FEATURES

- Bi-Direction Transient Voltage Suppressor
- Low capacitance and low leakage
- ESD Rating of Class 3 per Human Body Model
- IEC61000-4-2 level 4 ESD protection
- IEC61000-4-4 Level 4 EFT protection
- We declare that the material of product compliance with RoHS requirements.

DEVICE MARKING


Device MODEL	Marking
NHESD5Z5.0CA	5C



ABSOLUTE RATINGS(Ta = 25°C)

Parameter	Symbol	Limits	Unit
IEC 61000-4-2 (ESD)	Contact Discharge	±30	KV
	Air Discharge	±30	
Peak Pulse Power (tp = 8/20µs)	P_{PP}	85	W
Maximum Junction Temperature	T_J	150	°C
Operating Temperature Range	T_{OP}	-45 ~ +150	°C
Lead Solder Temperature - Maximum(10 Second Duration)	T_L	255±5	°C
Storage temperature	T_{STG}	-55 ~ +150	°C

ELECTRICAL CHARACTERISTICS (Ta= 25°C)



Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Maximum Reverse Leakage Current @ V_{RWM}
I_T	Test Current
I_F	Forward Current
V_F	Forward Voltage @ I_F
P_{pk}	Peak Power Dissipation
C	Capacitance @ $V_R = 0$ and $f = 1.0$ MHz

NHESD5Z5.0CA

Transient Voltage Suppressors for ESD Protection





ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

DEVICE	V _{RWM}	I _R @±V _{RWM}	V _{BR} @I _T		I _T	V _C @I _{PP} =5A	V _C @Max.I _{PP}	I _{PP}	P _{PK}	C _D
	Max.	Max.	Min.	Max.	mA	Typ.	Max.	Max.	Max.	Typ.
	V	uA	V			V	V	A	W	pF
NHESD5Z5.0CA	5.0	1.0	5.6	8.2	1.0	8.5	11	9	85	13

Note:VBR is measured with a pluse test current IT at an ambient temperature of 25°C .

ELECTRICAL CHARACTERISTICS CURVES




NHESD5Z5.0CA

Transient Voltage Suppressors for ESD Protection



OUTLINE DRAWINGS


SOD-523



OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	1.100	-	1.300	0.043	-	0.051
B	0.750	-	0.850	0.030	-	0.033
C	0.510	-	0.770	0.020	-	0.030
D	1.500	-	1.700	0.059	-	0.067
E	0.250	-	0.350	0.010	-	0.014
F	0.030	-	0.150	0.001	-	0.006
G	-	0.250	-	-	0.0098	-

RECOMMENDED LAYOUT DRAWINGS

SOD-523



RECOMMENDED MOUNTING PAD DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	--	2.020	--	--	0.080	--
B	--	0.700	--	--	0.028	--
C	--	0.820	--	--	0.032	--
D	--	0.600	--	--	0.024	--

PACKING INFORMATION

SOD-523

Package Method	Reel Size (mm)	Quantity (pcs/reel)	Inner Box Size LxWxH(mm)	Quantity (pcs/Inner Box)	Carton Size LxWxH(mm)	Quantity (pcs/carton)
Tape Reel	Φ180	3000	210x210x203	45000	455x455x240	180000

NHESD5Z5.0CA


Transient Voltage Suppressors for ESD Protection



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat -Temperature Min(T _S min) -Temperature Max(T _S max) -Time(t _s min to t _s max)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
Time maintained above: -Temperature (T _L) - Time (t _L)	183°C 60-150 seconds	217°C 60-150 seconds
Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(t _p)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

NHESD5Z5.0CA

Transient Voltage Suppressors for ESD Protection



Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from niuhang Electronics co., LTD
- Niuhan Electronics co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhan Electronics co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhan Electronics co., LTD. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Niuhan Electronics co., LTD. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Niuhan Electronics co., LTD. for any damages resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to product the customer quality, change the internal structure and the production process Niuhan can not notify