

FullAXS | FullAXS LC

TE Internal #: 1828935-1

Fiber Optic Patch Cable Assemblies, OFNR, .295 in [7.5 mm]

Diameter, 2 Fibers, Beige, Beige, Black Cable, Standard Boot Type

(Left), FullAXS LC

View on TE.com >



Fiber Optics > Fiber Optic Cable Assemblies > Fiber Optic Patch Cable Assemblies



Fiber Optic Cable Type: OFNR

Cable Assembly Fiber Diameter: 62.5/125 µm

Outside Cable Diameter: 7.5 mm [.295 in]

Number of Fibers: 2

Connector Color (End A): Beige

Features

Product Type Features

Fiber Optic Cable Type	OFNR
Fiber Optic Mode	Multimode
Connector Type (End A)	LC Duplex Plug
Connector Type (End B)	LC Duplex Plug
Cable Assembly Type	LC Duplex
Fiber Type	OM1

Configuration Features

Number of Connectors (End A)	2
Number of Connectors (End B)	2
Number of Fibers	2
Cable Buffering	Tight Buffer

Signal Characteristics

Insertion Loss A (Max)	.5 dB
Insertion Loss B (Max)	.5 dB



Return Loss	30 dB
Body Features	
Cable Flammability Rating	OFNR (Riser) Jacket
Connector Color (End A)	Beige
Connector Color (End B)	Beige
Cable Color	Black
Boot Type (Left)	Standard
Boot Type (Right)	Standard
Boot Color (Left)	Black
Boot Color (Right)	Black
Polarity	Flipped
Contact Features	
Ferrule Material	Zirconia
Dimensions	
Cable Assembly Fiber Diameter	62.5/125 μm
Outside Cable Diameter	7.5 mm[.295 in]
Other	
Cable Assembly Length	1 m[.305 ft]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | FullAXS LC



Docking Connectors(1)



Fiber Connector Covers & Caps(1)



Fiber Optic Patch Cable Assemblies(8)



LC Connectors(4)



ODVA LC Connectors(3)




PCB Headers & Receptacles(1)

Customers Also Bought





TE Part #1735104-3 SAS BACKPLANE RECEPT, VERTICAL



TE Part #1-1623803-0 SQZ7 4K7 5% (METAL FILM)



TE Part #1103431-1
MALE INSERT, CRIMP, 12-POS. TYPE III+





TE Part #1828936-2 CA FO 2FIB B/O SM,LC ODVA









Documents

Product Drawings

CA FO, 2FIB B/O 62.5/125 LC ODVA

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1828935-1_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1828935-1_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1828935-1_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Fiber Optic Patch Cable Assemblies, OFNR, .295 in [7.5 mm] Diameter, 2 Fibers, Beige, Beige, Black Cable, Standard Boot Type (Left), FullAXS LC



Fiber Optic Products_0412

English