



Product: <u>82503</u> ☑

RS232, #24-3pr, FEP, O/A Foil, LS-PVC Jkt, CMP

Product Description

Computer EIA RS-232 Cable, 3-Pair, 24 AWG stranded (7x32) tinned copper conductors, FEP insulation, overall Beldfoil® shield (100% coverage), 24 AWG stranded tinned copper drain wire, Flamarrest® jacket, plenum rated

Technical Specifications

Product Overview

| Suitable Applica | tions: | indoor plenum applications; RS-232 applications; computer communications; low voltage analog signals (4-20ma, 0-10v,); low voltage digital control (24v,); line level audio; panel wiring |
|------------------|--------|---|
|------------------|--------|---|

Construction Details

Conductor

| Element | Number of Element | Size | Stranding | Material |
|---------|-------------------|--------|-----------|--------------------|
| Pair(s) | 3 | 24 AWG | 7x32 | TC - Tinned Copper |

Insulation

| Element | Material | Nom. Thickness | Nom. Insulation Diameter | Color Code |
|---------|--------------------------------------|--------------------|--------------------------|---|
| Pair(s) | FEP - Fluorinated Ethylene Propylene | 0.006 in (0.15 mm) | 0.036 in (0.91 mm) | Black & Red, Black & White, Black & Green |

Outer Shield

| Shield Type | Material | Coverage | Drainwire Type |
|-------------|-------------------------|----------|------------------|
| Tape | Bi-Laminate (Alum+Poly) | 100% | 24 AWG (7x32) TC |

Outer Jacket

| Material | Nom. Thickness | Nom. Diameter |
|-----------------------------------|--------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.015 in (0.38 mm) | 0.171 in (4.34 mm) |
| Overall Cable Diameter (Nominal): | 0.171 in (4 | .34 mm) |

Electrical Characteristics

Electricals

| Elei | ment | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Max. Current |
|------|------|--------------------|-------------------------------|---|--------------------------------|
| Pair | r(s) | 24.1 Ohm/1000ft | 25 pF/ft (82 pF/m) | 45 pF/ft (150 pF/m) | 1.5 Amps per Conductor at 25°C |

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|-----------------------|--------------|
| 60°C | 0°C to +60°C |

Bend Radius

Stationary Min. Installation Min.

| 1.7 in (43 mm) | 1.7 in (43 mm) | |
|-------------------|----------------|----------------|
| Max. Pull Tension | n: | 39 lbs (18 kg) |
| Bulk Cable Weig | jht: | 18 lbs/1000ft |

Standards and Compliance

| Environmental Suitability: | Indoor - Plenum, Indoor | |
|----------------------------------|--|--|
| Flammability / Reaction to Fire: | NFPA 262, UL 910 (Plenum), FT6, IEC 60332-1-2 | |
| CPR Compliance: | CPR Euroclass: Eca | |
| NEC / UL Compliance: | rticle 800, CMP | |
| CEC / C(UL) Compliance: | CMP | |
| European Directive Compliance: | EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) | |
| UK Regulation Compliance: | UKCA Mark | |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) | |

History

| Update and Revision: | Revision Number: 0.458 Revision Date: 01-20-2023 |
|----------------------|--|

Part Numbers

Variants

| Item # | Color | UPC |
|----------------|---------|--------------|
| 82503 8771000 | Natural | 612825197195 |
| 82503 877U1000 | Natural | 612825197188 |

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.