


# SAC-5P- 2,0-900/FSB SCO - Bus system cable



1517916

<https://www.phoenixcontact.com/us/products/1517916>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bus system cable, INTERBUS (16 Mbps), 5-position halogen-free, shielded, free cable end, on Socket straight M12, coding: B SPEEDCON, cable length: 2 m

## Commercial data

Item number	1517916
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF04
Product key	BF1CKB
Catalog page	Page 198 (C-6-2019)
GTIN	4017918968038
Weight per piece (including packing)	168.3 g
Weight per piece (excluding packing)	164.5 g
Customs tariff number	85444290
Country of origin	PL

1517916

<https://www.phoenixcontact.com/us/products/1517916>

## Technical data

### Product properties

Product type	Data cable preassembled
Sensor type	INTERBUS
Number of positions	5
Application	Standard
No. of cable outlets	1
Shielded	yes
Coding	B

### Insulation characteristics

Overvoltage category	II
Degree of pollution	3

### Interfaces

Bus system	INTERBUS
Signal type/category	INTERBUS, 16 Mbps

### Signaling

Status display	No
Status display present	No

### Electrical properties

Contact resistance	$\leq 5 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage $U_N$	48 V AC
	60 V DC
Nominal current $I_N$	4 A
Transmission medium	Copper

### Material specifications

Flammability rating according to UL 94	V0
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	PA 6.6
Material for screw connection	Zinc die-cast, nickel-plated

### Connection data

#### Pin assignment

Contact   Color (signal designation)   Contact (optional)	1 (Socket)   YE (DQ)
	2 (Socket)   GN (DQ)

# SAC-5P- 2,0-900/FSB SCO - Bus system cable



1517916

<https://www.phoenixcontact.com/us/products/1517916>

	3 (Socket)   GY (DI)
	4 (Socket)   PK (DI)
	5 (Socket)   BN (GND)

## Connector

### Connection 1

Type	free cable end
------	----------------


### Connection 2

Type	Socket straight M12 SPEEDCON
Number of positions	5
Coding type	B (inverse)
Number of positions	5
Locking type	SPEEDCON

## Cable/line

Cable length	2 m
--------------	-----

### INTERBUS [900]

Dimensional drawing	
Cable weight	70 kg/km
Number of positions	6
Shielded	yes
Cable type	INTERBUS [900]
Conductor structure	3 x 2 x 0.22 mm <sup>2</sup>
Signal speed	0.66 c
Conductor structure signal line	32x 0.10 mm
AWG signal line	24
Conductor cross section	3x 2x 0.22 mm <sup>2</sup>
External cable diameter	8 mm
Outer sheath, material	PUR
External sheath, color	may green RAL 6017
Conductor material	Bare Cu litz wires
Material wire insulation	PE
Single wire, color	green-yellow, white-brown, gray-pink
Twisted pairs	2 cores to the pair
Overall twist	3 pairs to the core

# SAC-5P- 2,0-900/FSB SCO - Bus system cable



1517916

<https://www.phoenixcontact.com/us/products/1517916>

Insulation resistance	≥ 5 GΩ*km
Coupling resistance	< 250.00 mΩ/m (at 30 MHz)
Loop resistance	≤ 159.80 Ω/km
Wave impedance	120 Ω ±20 % (at 64 kHz)
	100 Ω ±15 % (with 1 MHz)
Cable capacity	≤ 60 nF/km (At 800 Hz)
Nominal voltage, cable	250 V (Peak value, not for high-power applications)
Test voltage Core/Core	1500 V <sub>rms</sub>
Test voltage Core/Shield	1000 V <sub>rms</sub>
Minimum bending radius, fixed installation	7.5 x D
Minimum bending radius, flexible installation	15 x D
Max. bending cycles	5000000
Near end crosstalk attenuation (NEXT)	≥ 61 dB (at 772 kHz)
	≥ 59 dB (with 1 MHz)
	≥ 55 dB (at 2 MHz)
	≥ 50 dB (at 4 MHz)
	≥ 46 dB (at 8 MHz)
	≥ 44 dB (at 10 MHz)
	≥ 41 dB (at 16 MHz)
	≥ 40 dB (at 20 MHz)
Shield attenuation	≤ 15 dB/km (at 256 kHz)
	≤ 24 dB/km (at 772 kHz)
	≤ 27 dB/km (with 1 MHz)
	≤ 52 dB/km (at 4 MHz)
	≤ 84 dB/km (at 10 MHz)
	≤ 112 dB/km (at 16 MHz)
	≤ 119 dB/km (at 20 MHz)
Flame resistance	according to VDE 0472, Part 4, test type B
	according to IEC 60332-1
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-30 °C ... 70 °C (Cable, flexible installation)

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)

# SAC-5P- 2,0-900/FSB SCO - Bus system cable



1517916

<https://www.phoenixcontact.com/us/products/1517916>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1517916>



**EAC-RoHS**

Approval ID: RU D-DE.HB35.B.00387

# SAC-5P- 2,0-900/FSB SCO - Bus system cable



1517916

<https://www.phoenixcontact.com/us/products/1517916>

## Classifications

### ECLASS

ECLASS-11.0	27060307
ECLASS-12.0	27060307
ECLASS-13.0	27060307

### ETIM

ETIM 8.0	EC001855
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# SAC-5P- 2,0-900/FSB SCO - Bus system cable



1517916

<https://www.phoenixcontact.com/us/products/1517916>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)