



NOTES:

1. MATERIAL: SEE TABLE
2. FINISHES: SEE TABLE
3. WRAP LABEL IS MARKED WITH P/N, DATE CODE VOLTAGE & AMPERAGE
4. MATES WITH: QUICK CHANGE 4 POLE RECEPTACLE
5. ELECTRICAL DATA:
 10AWG UL TYPE: TC-ER STRANDED CABLE (HI-FLEX)
 MAX VOLTAGE: 600V
 MAX CURRENT: 32A
 PROTECTION IP67 (WHEN MATED)
 TEMPERATURE RANGE: -20°C TO 90°C
6. PACKAGING:
 CABLE ASSEMBLIES ARE BAGGED SEPARATELY IN POLY BAGS WITH BAR CODE LABEL ATTACHED TO OUTSIDE OF BAG.
7. ASSEMBLY IS RoHS COMPLIANT



PART NUMBER LEGEND

CC4030K25MXXXG



11	2	WARNING LABEL	VINYL	ORANGE/BLACK
10	1	WRAP LABEL	VINYL	BLACK/YELLOW
9	1	OVERMOLD (MALE, STRAIGHT)	PVC	BLACK
8	1	COUPLING (MALE)	ALUMINUM	CLEAR ANNODIZE
7	3	CONTACT PIN	Cu ALLOY	GOLD PLATED
6	1	INSERT (MALE)	PVC	BLACK
5	1	OVERMOLD (FEMALE, STRAIGHT)	PVC	BLACK
4	1	COUPLING	ALUMINUM	CLEAR ANNODIZE
3	3	CONTACT SOCKET	Cu ALLOY	GOLD PLATED
2	1	INSERT	PVC	BLACK
1	1	CABLE, 10/4 TC-ER (SEE NOTE 5)	TPE JACKET	BLACK
ITEM	QTY.	DESCRIPTION	MATERIAL	DESCRIPTION

RELEASED EC NO: IPG2016-1647 DRWINRSTONE 2016/06/06 CHKDK:K COX 2016/08/15 APPR:BWODMAN 2016/08/18	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>3 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>2 PLACES</td> <td>± 0.13</td> <td>± .01</td> </tr> <tr> <td>1 PLACE</td> <td>± 0.3</td> <td>± .020</td> </tr> </tbody> </table> ANGULAR ± 1 °		mm	INCH	4 PLACES	± ---	± ---	3 PLACES	± ---	± ---	2 PLACES	± 0.13	± .01	1 PLACE	± 0.3	± .020	DIMENSION STYLE IN/MM DRAWN BY DATE RSTONE 2016/06/06 CHECKED BY DATE K COX 2016/08/15 APPROVED BY DATE BWOODMAN 2016/08/18 MATERIAL NO.	SCALE 1:1 DESIGN UNITS INCH THIRD ANGLE PROJECTION	TITLE QC FEMALE/MALE STR/STR SINGLE KEY10/4 HI-FLEX TPE BLACK MOLEX INCORPORATED DOCUMENT NO. SD-130064-020 SHEET NO. 1 OF 1
		mm	INCH																	
4 PLACES	± ---	± ---																		
3 PLACES	± ---	± ---																		
2 PLACES	± 0.13	± .01																		
1 PLACE	± 0.3	± .020																		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SIZE C	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																		