

ABS2 THRU ABS10  
BRIDGE RECTIFIERS



<b>VOLTAGE:</b> 200-1000 Volts	<b>CURRENT:</b> 1.0 Amperes	<b>ABS</b>	<b>Marking &amp; Schematic diagram</b>
<b>FEATURES</b> <ul style="list-style-type: none"> <li>Glass passivated die construction</li> <li>low forward voltage drop</li> <li>High surge current capability</li> <li>Plastic material-UL flammability 94V-0</li> </ul>			
<b>MECHANICAL DATA</b> <ul style="list-style-type: none"> <li><b>Case:</b> ABS</li> <li><b>Terminals:</b> Plated Leads Solderable per MIL-STD-202, Method 208</li> <li><b>Polarity:</b> As Marked on Case</li> <li><b>Mounting Position:</b> Any</li> <li><b>Lead Free:</b> For RoHS / Lead Free Version</li> <li><b>Weight:</b> App. 0.1 grams (0.0035 ounce)</li> </ul>		<b>Remark:</b> <ol style="list-style-type: none"> <li>NH=niuhang trademark</li> <li>FF=Product line code,According to actual changes YWW=Data code,According to actual changes</li> <li>ABSx=Modle;X=2,4,6,8,10</li> <li>"- "+"=Polarity mark</li> </ol>	
<b>TYPICAL APPLICATIONS</b> <ul style="list-style-type: none"> <li>For use in switch power supply ,high frequency inverters , PD power supply applications</li> </ul>			

Single phase,half wave,60Hz,resistive or inductive load.For capacitive load,derate current by 20%

**Maximum Ratings (Ratings at 25°C ambient temperature unless otherwise specified )**

Parameter	Symbol	ABS2	ABS4	ABS6	ABS8	ABS10	Unit
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	200	400	600	800	1000	V
Maximum RMS Voltag	$V_{RMS}$	140	280	420	560	700	V
Maximum DC Blocking Voltage	$V_{DC}$	200	400	600	800	1000	V
Maximum Average Forward Rectified Current @ TC=100°C (see fig.1)	$I_{F(AV)}$	1					A
Peak Forward Surge Current 8.3ms Single Half Sine-wave Superimposed On Rate Load (JEDEC Method)	$I_{FSM}$	35					A
Current Squared Time Per Diode(t<8.3ms)	$I^2t$	5.08					A <sup>2</sup> sec

**Electrical Charactercsts (Ratings at 25°C ambient temperature unless otherwise specified )**

Parameter	Test Conditions	Symbol	ABS2			Unit
			Min.	Typ.	Max.	
Maximum Forward Voltage Per Diode (Note 1)	Ta=25°C IF= 1.0 A	$V_{FM}$	--	0.93	1.1	V
Maximum DC Reverse Current at Rated DC Blocking Voltage (Note 1)	Ta=25°C VR= $V_{RRM}$	$I_{RRM}$	--	1	5	uA
	Ta=125°C VR= 80%* $V_{RRM}$		--	50	300	
Typical Junction Capacitance Per Diode	4V,1MHz	$C_J$	--	150	--	pF

**Thermal Characteristics (Ratings at 25°C ambient temperature unless otherwise specified )**

Parameter	Symbol	ABS2		Unit
Operating Junction Temperature Range	$T_J$	-55	to 150	°C
Storage Temperature Range	$T_{STD}$	-55	to 150	
Typical thermal resistance (Note 2)	$R_{\theta JA}$	62.5		°C/W
	$R_{\theta JL}$	25.0		

- Notes:
- Pulse test: 300 μs pulse width,1% duty cycle
  - Mounted on glass epoxy PC board with 4×1.5"×1.5" (3.81×3.81 cm) copper pad.

**ABS2 THRU ABS10**  
BRIDGE RECTIFIERS



**RATING AND CHARACTERISTIC CURVES**




Fig.1-FORWARD CURRENT DERATING CURVE




Fig.2- TYPICAL INSTANTANEOUS FORWARD




Fig.3- TYPICAL REVERSE CHARACTERISTICS




Fig.4- TYPICAL JUNCTION CAPACITANCE





Fig.5-MAX. NON-REPETITIVE SURGE CURRENT

**ABS2 THRU ABS10**  
BRIDGE RECTIFIERS




**OUTLINE DRAWINGS**



**ABS**

OUTLINE DIMENSIONS						
Dim.	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.300	-	4.500	0.169	-	0.177
B	6.000	-	6.500	0.236	-	0.252
C	3.800	-	4.400	0.150	-	0.173
D	4.900	-	5.400	0.193	-	0.213
E	0.550	-	0.850	0.022	-	0.033
F	1.220	-	1.450	0.048	-	0.056
G	-	-	1.500	-	-	0.059
H	0.300	-	0.800	0.012	-	0.031
J	0.150	-	0.250	0.006	-	0.010
K	0.030	-	0.150	0.001	-	0.006

**RECOMMENDED LAYOUT DRAWINGS**



**ABS**

RECOMMENDED LAYOUT DIMENSIONS						
Dim.	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	-	6.200	-	-	0.244	-
B	-	4.000	-	-	0.157	-
C	-	2.000	-	-	0.079	-
C	-	1.000	-	-	0.039	-

**PACKING INFORMATION**

**ABS**

Package Method	Reel Size (mm)	Quantity (pcs/reel)	Inner Box Size LxWxH(mm)	Quantity (pcs/Inner Box)	Outer Carton Size LxWxH(mm)	Quantity (pcs/carton)
Tape Reel	Φ330	5000	340×340×40	10000	360×360×260	60000


ABS2 THRU ABS10  
BRIDGE RECTIFIERS



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (Tsmmax to Tp)	3°C/second max.	3°C/second max.
Preheat -Temperature Min(TS min) -Temperature Max(TS max) -Time(ts min to ts max)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
Time maintained above: -Temperature (TL) - Time (tL)	183°C 60-150 seconds	217°C 60-150 seconds
Peak Temperature(TP)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

**ABS2 THRU ABS10**  
BRIDGE RECTIFIERS



**Disclaimer**

- Reproducing and modifying information of the document is prohibited without permission from Niuhang Electronics Co., LTD
- Niuhang Electronics Co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhang Electronics Co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhang Electronics Co., LTD. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Niuhang Electronics Co., LTD. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Niuhang Electronics Co., LTD. for any damages resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to product the customer quality, change the internal structure and the production process Niuhang can not notify