


DIMENSIONS (mm)						
POSITIONS	A	B	C	D	E(REF)	F
9	30.81	24.99	16.92	8.36	15.45	11.35
15	39.19	33.32	25.25	8.36	24.50	11.37
25	53.04	47.04	38.96	8.36	37.83	11.37
37	69.32	63.50	55.42	8.36	54.45	11.40
50	67.00	61.10	52.80	11.26	51.65	11.40

MATERIAL:

- SHELL: STEEL, NICKEL PLATED
- INSULATOR: UL 94V-O RATED, PBT-BLACK
- PROCESS TEMP: 230°C
- CONTACTS: BRASS - GOLD PLATED
- HARDWARE: NICKEL PLATED BRASS

ELECTRICAL:

- CURRENT RATING: 5 AMPS
- CONTACT RESISTANCE: 10 mOhms Max.
- INSULATION RESISTANCE: 5,000 MOhms min.
- WORKING VOLTAGE: 250VAC RMS
- OPERATING TEMPERATURE: -55°C TO 100°C



172-YYY-18YLYY1

- SERIES
- POSITIONS
- 009
- 015
- 025
- 037
- 050
- GENDER
- 1 = MALE
- TERMINATION
- 8 = HIGH PROFILE VERTICAL
- SHELL PLATING
- 3 = NICKEL (GROUND INDENTS)
- RoHS COMPLIANT
- HARDWARE OPTIONS
- 00 = NO HARDWARE
- 01 = 2.50mm CLINCH NUT (BOARD SIDE)
- 02 = 5.80mm CLINCH NUT (BOARD SIDE)
- 03 = 5.80mm CLINCH NUT (MATING SIDE)
- PLATING OPTIONS
- 1 = GOLD FLASH

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.






DRAWN: W. ROBBINS
DATE: 08/23/1998

UNITS = mm

DO NOT SCALE FROM DRAWING

NorComp

SCALE: NTS	SHEET 1 OF 2	REV 22
DWG NO. 172-YYY-18YLYY1		



HARDWARE MOUNTING HOLES
MAY NOT BE REQUIRED DEPENDING
ON MOUNTING METHOD TO PCB

* TYP.
SUGGESTED SIZE
MAY NOT BE SUITABLE FOR ALL APPLICATIONS

RoHS COMPLIANT

UNITS = inch

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:
W. ROBBINS
DATE:
08/23/1998

NorComp

SCALE: NTS	SHEET 2	OF 2	REV 22
DWG NO. 172-YYY-18YLYY1			