<b>⊥</b> Ω			0			
Z'	ØS					
CHARACTERISTICS	Keying Shown as example		LAYO	UT SHOWN AS EXAMPLE		
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	Connector dimensionDimNominaØS29.4 MaZ'31.5 MaVV THREADM18x1-	ax ax	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +200°C		A	PN 18-10-2016 First Release	FR Not Listed   PN: 8D513M98AN   10-2016		
-Salt Spray : 2000 hours Mass : 17.2 g ± 10%		ISS Designe	DATE Latest modification	- by	CUSTOMER DRAWING	MOD N°
		-	TITLE Composite Plug 8D series		BD series	
ASIC SERIES: 8D 5 - 13 M SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact		ORIENTATION : N PIN(500 Matings)		General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the prop SOURIAU it must not be reproduc	ed or
SHELL SIZE : 13		DINI/FOO Matimaa)			communicated without pe	rmission

_	т	െ	п п	m		0
		Contact Layout				
4		$x_{i} \begin{pmatrix} \bullet & \bullet \\ \bullet & $				
	Conti positic A B B C C D C C C C C C C C C C C C C C C	on ID     (mm)     (mm)       4     +.000 (0.00)     +.195 (4.95)       5     +.125 (3.18)     +.150 (3.81)       5     +.133 (4.90)     +.030 (0.76)       6    104 (4.17)    105 (2.67)       7    164 (4.17)    105 (2.67)       6    193 (4.90)     +.030 (0.76)       6    125 (3.18)     +.150 (3.81)       6    125 (3.18)     +.150 (3.81)       6    125 (3.18)    150 (3.81)				
ω	Shell Arrangement No. c 13 -98	Number Size Service Contact Supersedes ontacts International Contact I Contact I I All MS20051-98				
						SOURIAU shall not be liable for an due to a use of the Products wi the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D513N
_					A 18-10-20 ISS DATE Designed By:	116 First Release Latest modification - by Date:
					TITLE	Compo
					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D513M
L	Н	G	F	E	D	C

