SMT COMMON MODE INDUCTORS

Toroid - Ruggedized 0.5A to 3.6A




- Ruggedized header with POGO pins for secure board mounting
- Rated voltage 250V_{AC}
- Low RFI toroid
- Moisture Sensitivity Level: 1

Electrical Specifications @ 25 °C – Operating Temperature – 55 °C to +130 °C										
Part ⁸ Number	Inductance @ Irated (mH +/- 30%)	Irated (A)	DCR (MAX) (mΩ)	SRF (MHz)	Impedance Curve (See below)	Size Code	Weight (Grams)	Quantity in Tube		
PL8800	1.0	3.60	50	4	1.	P0G0 50	7.1	30		
PL8801	1.5	1.50	60	2	2	P0G0 40	2.5	30		
PL8802	3.0	2.50	80	2.2	3	P0G0 50	7.1	30		
PL8803	10.0	1.00	450	0.5	4	POGO 40	3.0	30		

Note: 1. Option Tape & Reel packaging can be ordered by adding a "T" suffix to the part numer (i.e. PL8800, becomes PL8800T.) Pulse complies to industry standard tape and reel specification EIA481.

Mechanicals Electrical Schematic






SMT COMMON MODE INDUCTORS

Toroid - Ruggedized 0.5A to 3.6A



Tin/Lead Recommended Reflow Profile (Based on J-STD-020D)



	T _{SMAX} (°C)		T _P (°C MAX)	ts (s)	t _L (s)	t _P (s MAX)	Ramp-up rate (T _L to T _P)	Ramp-down rate (T _P to T _L)	Time 25°C to peak temperature (s MAX)
100	150	183	235	60-120 60-150 20 3°C/s MAX 6°C/s MAX		6°C/s MAX	360		

Notes:

- 1. All temperatures measured on the package leads.
- 2. Maximum times of reflow cycle: 2.

For More Information

iNRCORE,LLC 311 Sinclair Road Bristol, PA 19007-6812 U.S.A Tel: + 1.215.781.6400 Fax: +1.215.7816430

Global Sales Representatives and Locations:

http://www.inrcore.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2020. iNRCORE, LLC. All rights reserved.



www.inrcore.com