SSL1D101BD

Harmony, Solid state slim relay, 0.1 A, DC switching, input 16...30 V DC, output 1...48 V DC



Main

Range of Product	Harmony Solid State Relays
Product or Component Type	Solid state relay up to 10 A
Device short name	SSL
Phase	1 phase
Output switching mode	DC switching

Complementary

- Comprehensive	
Mounting Support	Socket
Line Rated Current	0.1 A
Output voltage	148 V DC
[Uc] control circuit voltage	1630 V DC
Capacitance unbalance	1.5 pF input/output
Minimum switching voltage	16 V DC turn-on
Maximum switching voltage	9 V DC turn-off
Input current limits	5 mA
Input impedance	3500 Ohm
Solid state output type	DC switching Transistor output
Load current	0.0010.1 A
Tansient Overvoltage	60 V DC
Maximum operating frequency	500 Hz
Surge current	0.3 A 10 ms
Maximum voltage drop	<1 V on-state
Maximum leakage current	0.001 mA off-state
Response time	0.02 ms (turn-on) 0.13 ms (turn-off)
Overvoltage category	III
Width	0.20 in (5 mm)
Height	1.10 in (28 mm)
Depth	0.59 in (15 mm)
Net Weight	0.01 lb(US) (0.0041 kg)

Environment

Flame retardance	V0 conforming to UL 94
Dielectric strength	3750 V for input/output
Pollution degree	2
Product Certifications	CSA UL
Marking	CE
Ambient Air Temperature for Operation	-4176 °F (-2080 °C)
Ambient Air Temperature for Storage	-4185 °F (-2085 °C)

Ordering and shipping details

Category	22375-INTERFACE MODULE(ABA,R,S)
Discount Schedule	CP2
GTIN	3606480579684
Nbr. of units in pkg.	1
Package weight(Lbs)	0.18 oz (5.0 g)
Returnability	No
Country of origin	MX

Packing Units


PCE
0.28 in (0.7 cm)
0.98 in (2.5 cm)
14.57 in (37 cm)
S01
1080
12.53 lb(US) (5.684 kg)
5.91 in (15 cm)
5.91 in (15 cm)
15.75 in (40 cm)
BB1
12
2.12 oz (60.0 g)
0.28 in (0.7 cm)
0.98 in (2.5 cm)
14.57 in (37 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	[☑] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information

SSL1D101BD


Dimensions



Product data sheet Performance Curves

SSL1D101BD

Derating Curves



A: Load Current (Amperes)
B: Ambient Temperature (°C)