CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Sounector dimension -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	ſ	т	۵	ш П	т			0	B			7
CHARACTERISTICS Shell Material ::::::::::::::::::::::::::::::::::::	4											4
CHARACTERSTIC Standard: Based on MIL-DTL:38999 Series III Stell Material ::: Shell ::: Sh	ω							LAYOUT SHO	OWN AS EXAMPLE			3
Standard : Based on ML-DTL-38099 Series III Image: Control Instantian Shell Material : Aluminium Shell Material : Aluminium Shell Platag : Object of any non-conformity of amage. Shell Platag : Object of any non-conformity of amage. Shell Platag : Object of the Portice of the Partice or by a third party. Schell Platag : Object of the Portice of the Partice or by a third party. Schell Platag : Object of the Portice of the Partice or by a third party. Schell Platag : Object of the Portice of the Partice or by a third party. Schell Platag : Object of the Portice of the Partice or by a third party. Schell Platag : Object of the Portice of the Partice or by a third party. Schell Platag : Object of the Portice of the Partice or by a third party. : Object of the Portice of the Partice of the Partice or by a third party. : Object of the Partice of the Partice or by a third party. : Object of the Partice of th				Keying Sł	hown as example							
-Sendard: Eased on MIL-DT-3899 Series III -Shell Material : Aluminium -Insulator : Thermoplastic -Contact S : Copper Alloy -Sole I Material : Sole I Material -Sole I Material : Sole I Material -Sole I Material : Contact S -Contact S : Copper Alloy -Sole I Material : Sole I Material -Sole I Material : Contact Plaing : Contact Plaing <td: contact="" output<="" sole="" td=""> : Contact Plaing : Delivered with Souriau contacts and Accessories : Phile Book -Temperature Range : Sole Contact Plaing : Sole I Material : Sole I Material Mass : I 6.89 g ± 10% Mass<!--</td--><td></td><td>CHARACTERISTICS</td><td></td><td></td><td>Connector dimension</td><td>_</td><td></td><td></td><td></td><td></td><td></td><td></td></td:>		CHARACTERISTICS			Connector dimension	_						
Shell Material : Adufinium - Shell Material : Adufinium - Shell Material : Adufinium - Shell Material : Cantacts - Contacts : Copper Alley - Contact Signer : Sold over copper Alley 0.8µm minimum - Ouract Plating :: Sold over copper Alley 0.8µm minimum - Ouract Plating :: Sold over copper Alley 0.8µm minimum - Ouract Plating :: Sold over copper Alley 0.8µm minimum - Ouract Plating :: Sold over copper Alley 0.8µm minimum - Ouract Plating :: Sold over copper Alley 0.8µm minimum - Ouract Plating :: Sold over copper Alley 0.8µm minimum - Ouract Plating :: Sold over copper Alley 0.8µm minimum - Ouract Plating :: Sold over copper Alley 0.8µm minimum - Sold over copper Alley 0.8µm minimum :: Sold over copper Alley 0.8µm minimum - Sold over copper Alley 0.8µm minimum :: Sold over copper Alley 0.8µm minimum - Sold over copper Alley 0.8µm minimum :: Sold over copper Alley 0.8µm minimum - Ouract Plating : Sold over copper Alley 0.8µm minimum - Sold over copper Alley 0.8µm minimum :: Sold over copper Alley 0.8µm minimum - Sold Sold over copper Alley 0.8µm minimum :		Standard : Based on N	1IL-DTL-38999 Series III		Dim Nominal							
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : 65°C to +175°C -Salt Spray : 500 hours -Mass : 16.89 g ± 10% BASIC SERIES: 8D SHELL TYPE : Plive with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 ORIENTATION : N CONTACT TYPE : Souriau NHELL SIZE : 11 CONTACT TYPE : Source are being contact SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : Source are being contact Source are being contact SOURIAU WWW.SOURIAU.COM Trimwain not be reproduced or commission rommission rommating SOURIAU DRG N° SUBS11W22BN-C 1/2		-Shell Plating -Insulator -Contacts	: Olive drab Cadmium : Thermoplastic : Copper Alloy		Z 31 Max		due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)					
-Delivered with Souriau contacts and Accessories -Temperature Range :: -65°C to +175°C -Sait Spray :: : : : : : : : : : : : : : : : : :		•		minimum					FR	Not Listed		2
-Salt Spray :: 500 hours -Mass :: 16.89 g ± 10% -Mass :: 16.89 g ± 10% BASIC SERIES: 8D 5 11 W 22 B N SHELL TYPE :: Plug with RFI Shielding CONTACT TYPE :: Standard Crimp Contact SHELL SIZE :: 11 PLATING :: W = Olive drab Cadmium CONTACT TYPE :: SOCKET(500 Matings) CONTACT LAYOUT :: 11:22 A3 SOURIAU DRG N° SHEET A3 SOURIAU DRG N° SHEET A3 SOURIAU DRG N° SHEET A3 SOURIAU DRG N° SHEET							PN: 8D511W22BN					
-Salt Spray : 500 hours -Mass : 16.89 g ± 10% BASIC SERIES: 8D 5 - 11 W 22 B N SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) CON												-
BASIC SERIES: 8D 5 11 W 22 B N SHELL TYPE : Plug with RFI Shielding SCALE General linear NPRDS / PROJECT CONTACT TYPE : Standard Crimp Contact 859 SHELL SIZE : 11 ORIENTATION : N SHELL SIZE : 11 PLATING : W = Olive drab Cadmium FORMAT SOURIAU WWW.SOURIAU DRG N° SHEET A3 8D511W22BN-C 1/2		-Salt Spray	: 500 hours				A 18-10-20	TP HILL KEIEBSE				
TITLE Aluminium Plug 8D series BASIC SERIES: 80 5 11 W 22 B N SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SCALE NA SCALE NA SCALE NA SCALE NA SHELL TYPE : Plug with RFI Shielding This document is the property of SOURIAU CONTACT TYPE : Standard Crimp Contact SCONTACT TYPE : SOCKET(500 Matings) SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) PORMAT SOURIAU DRG N° SHEET A3 8D5111W22BN-C 1/2	_	-Mass	: 16.89 g ± 10%					-		CUSTOMER DRAWING	MOD N°	╞
BASIC SERIES. SD SD S II W ZZ B N III N N III N N III N III N ZZ B N III N N IIII N N IIII N N IIII N N IIIIIIIII N N IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII										_		
CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SOURIAU This document is the property of SOURIAU.COM SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) SOURIAU SOURIAU DRG N° it must not be reproduced or communicated without permission PLATING : W = Olive drab Cadmium CONTACT TYPE : 11-22 FORMAT SOURIAU DRG N° SHEET A3 8D511W22BN-C 1/2	_			11 W 22 B	N			-{	rances:			-
SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) communicated without permission PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 11-22 FORMAT SOURIAU DRG N° SHEET A3 8D511W22BN-C 1/2					OR	IENTATION : N	SOURIA	J WWW.SOUF	SOURIAU.COM it must not be reproduced			
A3 8D511W22BN-C 1/2		SHELL SIZE : 11			CONTACT TYPE : SOCKET	r(500 Matings)						
		PLATING : W =	Olive drab Cadmium		CONTACT L	AYOUT : 11-22						
	l								1		1/2	

	т	۵	н г	m	D	0
		Contact Layout				
		22*				
4		°0 0°				
		c0 0,				
		4#22D				
	Ctc A B	11-22 X Y 1.905 1.905 1.905 -1.905				
ယ	C D	-1.905 -1.905 -1.905 1.905	_			
	F				[
						SOURIAU shall not be liable for a due to a use of the Products w the Specifications issued by either (professional recommend
N						Coun
						PN: 8D511
					A 18-10-201	L6 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumi
_					SCALE NA	General linear Tolerances:
					SOURIAL	J WWW.SOURIAU.
					FORMAT	SOURIA

G

Н

F

Е

A3

D

С

