


200 WATTS

MULTI OUTPUT AC-DC

FEATURES:

- Compact 3.0" x 5.0" x 1.3" Size
- 3 Year Warranty
- Universal 85-264V Input
- Dual, Triple or Quad Outputs
- 90% Peak Efficiency
- 86% Average Efficiency
- <300mW No Load Input Power
- RoHS Compliant
- IEC 60601-1 3rd ed. Medical Cert.
- IEC 60950-1 2nd ed. ITE Certification
- IEC 62368-1 2nd ed. Certification
- IEC 60601-1-2 4th ed. EMC
- Class B Emissions per EN55011/32
- -20 to +70°C Operating Temperature
- Optional Power Fail Warning
- Optional Chassis/Cover



CHASSIS/COVER

OPEN FRAME

SAFETY SPECIFICATIONS



Underwriters Laboratories
File E137708/E140259

UL 62368-1:2014, 2nd Edition
CAN/CSA-C22.2 No. 62368-1-14
AAMI/ANSI ES60601-1:2005/(R) 2012
CAN/CSA-C22.2 No. 60601-1:2014



CB Reports/Certificates (including all National and Group Deviations)

IEC 62368-1:2014, 2nd Edition
IEC 60601-1:2005/A1:2012



TUV SUD America

EN 62368-1:2014, 2nd Edition
EN 60601-1:2006/A1:2013



Low Voltage Directive
RoHS Directive (Recast)

(2014/35/EU of February 2014)
(2015/863/EU of March 2015)



Electrical Equipment (Safety) Regulations 2016 SI No. 1101
Restriction of the Use of Certain Hazardous Substances in EEE Regulations
2012 SI No. 3032 + 2019 SI No.492

MODEL LISTING

MODEL	OUTPUT 1	OUTPUT 2	OUTPUT 3	OUTPUT 4
GRN-200-4001	+3.3V/30A	+5V/8A	+12V/2A	-12V/2A
GRN-200-4002	+5V/30A	+3.3V/8A	+12V/2A	-12V/2A
GRN-200-4003	+5V/30A	+24V/3A	+12V/2A	-12V/2A
GRN-200-4004	+5V/30A	+24V/3A	+15V/2A	-15V/2A
GRN-200-4005	+24V/6A	+5V/8A	+12V/2A	-12V/2A
GRN-200-3001	+5V/30A	+12V/6A		-12V/2A
GRN-200-3002	+5V/30A	+15V/5A		-15V/2A
GRN-200-3003	+5V/30A		+24V/1.5A	-24V/1.5A
GRN-200-2001	+5V/30A	+24V/3A		
GRN-200-2002	+5V/30A	+12V/6A		
GRN-200-2003	+12V/12A	-12V/6A		
GRN-200-2004	+15V/10A	-15V/5A		

ORDERING INFORMATION

Consult factory for alternate output configurations.

Please specify the following optional features when ordering:

CH - Chassis
CO - Cover
BF - Type BF

PF - Power Fail Warning
IO - Isolated Outputs

All specifications are maximum at 25°C, 200W unless otherwise stated, may vary by model and are subject to change without notice.

GRN-200

OUTPUT SPECIFICATIONS

Output Power at 50°C ₍₁₎ (See Derating Chart)	135W 200W	Convection Cooled, Open Frame 300LFM Forced Air, Open Frame ⁽¹⁴⁾
Voltage Centering ₍₁₅₎	Output 1: Output 2: Outputs 2-4:	± 0.5% (all outputs at 50% load) ± 6.0% (4005, all outputs at 50% load) ± 5.0% (all outputs at 50% load)
Voltage Adjust Range	Output 1:	95-105%
Load Regulation	Output 1: Output 2:	± 0.5% (0-100% load change) ± 6% (4001,4002,4005 20-100% load change)
	Outputs 2-4:	± 5.0% (10-100% load change)
Source Regulation	Outputs 1-4:	0.5%
Cross Regulation	Outputs 2-4:	5.0%
Ripple & Noise ₍₆₎	Outputs 1-4:	1.0% or 100mV p-p, 20MHz BW
Turn on Overshoot		None
Transient Response		Output recovers to within 1% of initial set point due to a 50-100-50% step load change, 500µs maximum, 4% dev.
Overvoltage Protection		Latching, between 110% and 150% of rated output voltage.
Overpower Protection		110-150% rated P _{OUT} , cycle on/off, auto recovery
Hold Up Time		16ms minimum, full power
Start Up Time		<1 sec., 115/230V Input
Output Rise Time		25ms typical
Minimum Load ₍₅₎		No minimum load required

INPUT SPECIFICATIONS

Protection Class	I
Source Voltage	85 – 264 Volts AC (see derating chart)
Frequency Range	47 – 63 Hz
Input Protection	Dual internal 5A time delay fuses, 1500A breaking capacity
Peak Inrush Current	40A max
Peak Efficiency	Up to 90%
Average Efficiency	86% (Avg. of 25%, 50%, 75%, 100% rated load)
No Load Input Power	<300mW, 115/230 V _{IN} , no load <500mW, 115/230 V _{IN} , no load (PF Option)

ENVIRONMENTAL SPECIFICATIONS

Ambient Operating Temp. Range	-20°C to +70°C, Derating (see derating Chart)
Ambient Storage Temp. Range	-40°C to +85°C
Operating Relative Humidity Range	20-90% non-condensing
Altitude	5,000m ASL – Operating / 12,192m ASL – Non-Operating
Temperature Coefficient	0.02%/°C
Vibration (MIL-STD-810G)	2.5G swept sine, 10-2000Hz, 1octave/min, 3 axis, 1 hour each
Shock (MIL-STD-810G)	20G, 11ms, 3 axis

GENERAL SPECIFICATIONS

Means of Protection	
Primary to Secondary	2MOPP (Means of Patient Protection)
Primary to Ground	1MOPP (Means of Patient Protection)
Secondary to Ground	Operational Insulation (1MOPP w/ Option BF)
Dielectric Strength _(7, 8)	
Reinforced Insulation	5656 VDC (4000VAC)
Basic Insulation	2121 VDC (1500VAC)
Operational Insulation	707 VDC (500VAC)/2121VDC(1500VAC) w/ Option BF
Leakage Current	
Earth Leakage	<300µA NC, <1000µA SFC
Touch Current	<100µA NC, <500µA SFC
Patient Leakage Current	<100µA NC, <500µA SFC w/Option BF
Power Fail Signal	Logic low with input power failure 9ms prior to loss of Output 1 ₍₁₃₎
Switching Frequency	PWM:65 KHz/PFC:Variable
Remote Sense ₍₉₎	250mV compensation of output cable losses (output 1)
Mean-Time Between Failures	>200,000 HOURS, MIL-HDBK-217F, 25° C, GB
Weight	1.0 lb. Open frame / 1.16 lb. Chassis and cover

EMC SPECIFICATIONS (IEC 60601-1-2:2014, 4TH ed./IEC 61000-6-2:2005)


Electrostatic Discharge	EN 61000-4-2	±8KV contact / ±15KV air discharge	A
Radiated Electromagnetic Field	EN 61000-4-3	80MHz-2.7GHz, 10V/m, 80% AM	A
Electrical Fast Transients/Bursts	EN 61000-4-4	±2 KV, 5KHz/100KHz	A
Surge Immunity	EN 61000-4-5	±2 KV line to earth / ±1 KV line to line	A
Conducted Immunity	EN 61000-4-6	0.15 to 80MHz, 10V, 80% AM	A
Magnetic Field Immunity	EN 61000-4-8	30A/m, 60 Hz	A
Voltage Dips	EN 61000-4-11	0% U _T , 0.5 cycles, 0-315°	100/240V A/A
		0% U _T , 1 cycles, 0°	100/240V A/A
		40% U _T , 10/12 cycles, 0°	100/240V B/A
		70% U _T , 25/30 cycles, 0°	100/240V B/A
Voltage Interruptions	EN 61000-4-11	0% U _T , 300 cycles, 0°	100/240V B/B
Radiated Emissions	EN 55011/32	Class B	
Conducted Emissions	EN 55011/32	Class B	
Harmonic Current Emissions	EN 61000-3-2	Class A	
Voltage Fluctuations/Flicker	EN 61000-3-3	Compliant	



INTEGRATED
POWER DESIGNS

300 Stewart Road ■ Wilkes-Barre, PA 18706 ■ Phone: (570) 824-4666 ■ Fax: (570) 824-4843 ■ Email: sales@ipdpower.com ■ Web: www.ipdpower.com


GRN-200 SERIES MECHANICAL SPECIFICATIONS



DERATING REQUIREMENTS

- Derate Output 1 current rating 33% when convection cooled.
- Derate Outputs 2-4 current rating 25% when convection cooled.
- Derate Total Output Power linearly from 100% load at 50°C to 50% load at 70°C.
- Derate Total Output Power linearly from 100% load at 90V_{IN} to 90% load at 85V_{IN}.
- Derate Total Output Power 10% when convection cooled using Chassis or Chassis/Cover.
- Derate Total Output Power 10% when forced-air cooled using Chassis or Chassis/Cover.

CONNECTOR SPECIFICATIONS



Ground: 0.187 quick disconnect terminal.

P1: 0.156 friction lock header mates with Molex 09-50-3031 or equivalent crimp terminal housing with Molex 08-50-0189 or equivalent crimp terminal.

P3: 5566 Mini-Fit Jr. header mates with 5557 Mini-Fit Jr. or equivalent crimp housing with 5556 Mini-Fit or equivalent crimp terminal.

P2: 6-32 screw down terminal mates with #6 ring tongue terminal. (10 in-lb Max)

P4: 0.100 friction lock header mates with Molex 22-55-2061 or equivalent crimp terminal housing with Molex 71851 or equivalent crimp terminal.

APPLICATIONS INFORMATION

- Each output can deliver its rated current but Total Output Power must not exceed 200W, as determined by the cooling method.
- Generally, adequate cooling is provided when semiconductor case temperatures do not exceed 70°C rise and transformer temperature does not exceed 60°C rise at any specified ambient temperature.
- Sufficient area must be provided around power supply to allow natural movement of air to develop in convection-cooled applications.
- This product is intended for use as a professionally-installed component within information technology, industrial, and medical equipment and is not intended for stand-alone operation.
- Minimum load is not required for reliable operation; however, a 10% load may be required on Output 1 when loading Outputs 2, 3 or 4.
- Peak-to-Peak Output Ripple and Noise is measured directly at the output terminals of the power supply, without the use of the probe ground lead or retractable tip (tip-and-barrel method), 20MHz bandwidth.
- This product was type-tested and safety-certified using the dielectric strength test voltages listed in Table 6 of IEC 60601-1:2005. In consideration of Clause 8.8.3, care must be taken to ensure that the voltage applied to a reinforced insulation does not overstress different types and levels of insulation. Primary and secondary-to-ground capacitors may need to be disconnected prior to performing a dielectric strength test on the power supply or the end product. It is highly recommended that the DC test voltages listed in DVB.1, Annex DVB of UL 60601-1 1st Edition are not exceeded during a production-line dielectric strength test of the assembled end product. Please consult factory for further information.
- This power supply has been safety-approved and final-tested using a DC dielectric strength test. Please consult factory before performing an AC dielectric strength test.
- Remote-Sense terminals may be used to compensate for cable losses up to 400mV, depending on model. The use of a twisted pair, decoupling capacitors and an appropriately-rated low-impedance capacitor connected across the load will increase noise immunity.
- Maximum screw penetration into bottom chassis mounting holes is 0.100 inches. Maximum screw penetration into side chassis mounting holes is 0.188 inches.
- To comply with emissions specifications, all four mounting hole pads must be electrically connected to a common metal chassis. Chassis/Cover option is recommended. Refer to Operating Instructions for additional information.
- Common RF shielding precautions may need to be taken to assure emissions compliance. Refer to Operating Instructions for additional information.
- Power Fail (AC-Good) feature provides a logic-low warning signal from an open collector transistor output 9-15ms prior to loss of output from AC failure.
- 300LFM minimum of airflow must be maintained one inch above all points of top-side components or cover when forced-air cooling is required.
- A 3% increase above nominal voltage of Output 1 is required to meet ±5% centering of Output 2 on 4002 only.

MAX P_{OUT} vs. AMBIENT TEMPERATURE/INPUT VOLTAGE

