



Figure similar

Duplex starter with alternator Size 1 Three phase full voltage Solid-state overload relay OLR amp range 10-40A 110VAC 50Hz / 120VAC 60Hz Coil Combination type Two 30A disconnect switches Encl NEMA type 4 painted steel Water/dust tight weather proof

|   |  |
|---|--|
| product brand name  | Class 84   |
| design of the product   | Duplex controller with two non-fusible disconnect switches with alternator |
| special product feature   | ESP200 overload relay  |
| <b>General technical data</b>   |  |
| weight [lb]   | 70 lb  |
| Height x Width x Depth [in]   | 34 × 25 × 8 in   |
| touch protection against electrical shock                               | NA for enclosed products   |
| installation altitude [ft] at height above sea level maximum            | 6560 ft  |
| ambient temperature [°F]  |  |
| • during storage  | -22 ... +149 °F  |
| • during operation  | -4 ... +104 °F   |
| ambient temperature   |  |
| • during storage  | -30 ... +65 °C   |
| • during operation  | -20 ... +40 °C   |
| country of origin   | USA  |
| <b>Horsepower ratings</b>   |  |
| yielded mechanical performance [hp] for 3-phase AC motor                |  |
| • at 200/208 V rated value  | 7.5 hp   |
| • at 220/230 V rated value  | 7.5 hp   |
| • at 460/480 V rated value  | 0 hp   |
| • at 575/600 V rated value  | 0 hp   |
| <b>Contactor</b>  |  |
| size of contactor   | NEMA controller size 1   |
| number of NO contacts for main contacts                                 | 3  |
| operating voltage for main current circuit at AC at 60 Hz maximum       | 600 V  |
| operational current at AC at 600 V rated value                          | 27 A   |
| mechanical service life (switching cycles) of the main contacts typical | 10000000   |
| <b>Auxiliary contact</b>  |  |
| number of NC contacts at contactor for auxiliary contacts               | 0  |
| number of NO contacts at contactor for auxiliary contacts               | 1  |
| number of total auxiliary contacts maximum                              | 8  |
| contact rating of auxiliary contacts of contactor according to UL       | 10A@600VAC (A600), 5A@600VDC (P600)  |
| <b>Coil</b>   |  |
| type of voltage of the control supply voltage                           | AC   |

|  |   |
|--|---|
| control supply voltage   |   |
| <ul style="list-style-type: none"> <li>• at DC rated value</li> <li>• at AC at 50 Hz rated value</li> <li>• at AC at 60 Hz rated value</li> </ul>  | 0 ... 0 V<br>110 ... 110 V<br>120 ... 120 V |
| holding power at AC minimum  | 8.6 W                                       |
| apparent pick-up power of magnet coil at AC  | 218 VA                                      |
| apparent holding power of magnet coil at AC  | 25 VA                                       |
| operating range factor control supply voltage rated value of magnet coil   | 0.85 ... 1.1                                |
| percental drop-out voltage of magnet coil related to the input voltage   | 50 %  |
| ON-delay time  | 19 ... 29 ms                                |
| OFF-delay time   | 10 ... 24 ms                                |
| <b>Overload relay</b>  |   |
| product function   |   |
| <ul style="list-style-type: none"> <li>• overload protection</li> <li>• phase failure detection</li> <li>• asymmetry detection</li> <li>• ground fault detection</li> <li>• test function</li> <li>• external reset</li> </ul> | Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes      |
| reset function   | Manual, automatic and remote                |
| trip class   | CLASS 5 / 10 / 20 (factory set) / 30        |
| adjustable current response value current of the current-dependent overload release  | 10 ... 40 A                                 |
| tripping time at phase-loss maximum  | 3 s   |
| relative repeat accuracy   | 1 %   |
| number of NC contacts of auxiliary contacts of overload relay  | 1   |
| number of NO contacts of auxiliary contacts of overload relay  | 1   |
| operational current of auxiliary contacts of overload relay  |   |
| <ul style="list-style-type: none"> <li>• at AC at 600 V</li> <li>• at DC at 250 V</li> </ul>   | 5 A<br>1 A                                  |
| contact rating of auxiliary contacts of overload relay according to UL   | 5A@600VAC (B600), 1A@250VDC (R300)          |
| insulation voltage (Ui)  |   |
| <ul style="list-style-type: none"> <li>• with single-phase operation at AC rated value</li> <li>• with multi-phase operation at AC rated value</li> </ul>  | 600 V<br>300 V                              |
| <b>Disconnect Switch</b>   |   |
| response value of switch disconnecter  | 30A / 600V                                  |
| design of fuse holder  | non-fusible                                 |
| operating class of the fuse link   | non-fusible                                 |
| <b>Enclosure</b>   |   |
| degree of protection NEMA rating of the enclosure  | NEMA Type 4                                 |
| design of the housing  | dustproof, waterproof & weatherproof        |
| <b>Mounting/wiring</b>   |   |
| mounting position  | Vertical                                    |
| fastening method   | Surface mounting and installation           |
| type of electrical connection for supply voltage line-side   | Box lug                                     |
| tightening torque [lbf-in] for supply  | 35 ... 35 lbf-in                            |
| type of connectable conductor cross-sections at line-side at AWG cables single or multi-stranded   | 1x (14 ... 2 AWG)                           |
| temperature of the conductor for supply maximum permissible  | 75 °C                                       |
| material of the conductor for supply   | AL or CU                                    |
| type of electrical connection for load-side outgoing feeder  | Screw-type terminals                        |
| tightening torque [lbf-in] for load-side outgoing feeder   | 35 ... 35 lbf-in                            |
| type of connectable conductor cross-sections at AWG cables for load-side outgoing feeder single or multi-stranded  | 1x (14 ... 2 AWG)                           |
| temperature of the conductor for load-side outgoing feeder   | 75 °C                                       |

|  |   |
|--|---|
| maximum permissible  |   |
| material of the conductor for load-side outgoing feeder  | AL or CU  |
| type of electrical connection of magnet coil   | Screw-type terminals                                |
| tightening torque [lbf-in] at magnet coil  | 5 ... 12 lbf-in                                     |
| type of connectable conductor cross-sections of magnet coil at AWG cables single or multi-stranded                           | 2x (16 ... 12 AWG)                                  |
| temperature of the conductor at magnet coil maximum permissible  | 75 °C   |
| material of the conductor at magnet coil   | CU  |
| type of electrical connection at contactor for auxiliary contacts  | Screw-type terminals                                |
| tightening torque [lbf-in] at contactor for auxiliary contacts   | 10 ... 15 lbf-in                                    |
| type of connectable conductor cross-sections at contactor at AWG cables for auxiliary contacts single or multi-stranded      | 1x (12 AWG), 2x (16 ... 14 AWG), 2x (18 ... 16 AWG) |
| temperature of the conductor at contactor for auxiliary contacts maximum permissible   | 75 °C   |
| material of the conductor at contactor for auxiliary contacts  | CU  |
| type of electrical connection at overload relay for auxiliary contacts   | Screw-type terminals                                |
| tightening torque [lbf-in] at overload relay for auxiliary contacts  | 7 ... 10 lbf-in                                     |
| type of connectable conductor cross-sections at overload relay at AWG cables for auxiliary contacts single or multi-stranded | 2x (20 ... 14 AWG)                                  |
| temperature of the conductor at overload relay for auxiliary contacts maximum permissible                                    | 75 °C   |
| material of the conductor at overload relay for auxiliary contacts   | CU  |

#### Short-circuit current rating

|   |   |
|---|---|
| design of the fuse link for short-circuit protection of the main circuit required | 10kA@600V (Class H or K); 100kA@600V (Class R or J) |
| certificate of suitability  | NEMA ICS 2; UL 508; CSA 22.2, No.14                 |

#### Further information

**Industrial Controls - Product Overview (Catalogs, Brochures,...)**

[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:84DUE92EDF>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/US/en/ps/US2:84DUE92EDF>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:84DUE92EDF&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:84DUE92EDF&lang=en)

**Certificates/approvals**

<https://support.industry.siemens.com/cs/US/en/ps/US2:84DUE92EDF/certificate>

last modified:

1/25/2022 