



NTE2690 Silicon NPN Transistor TV Horizontal Deflection Output w/Damper Diode TO-3MPL Type Package

Features:

- High Voltage, High Speed
- Low Collector Saturation Voltage
- On-Chip Damper Diode

Applications:

- Horizontal Deflection Stage in Standard and High Resolution Displays for TVs and Monitors
- Switching Power Supplies for TVs and Monitors

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Collector–Base Voltage (Open Emitter), V_{CBO}	1700V
Collector–Emitter Voltage (Open Base), V_{CEO}	700V
Emitter–Base Voltage (Open Collector), V_{EBO}	10V
Collector Current, I_C		
Continuous	8A
Peak ($t_p < 5\text{ms}$)	15A
Base Current, I_B		
Continuous	5A
Peak ($t_p < 5\text{ms}$)	8A
Collector Dissipation ($T_C = +25^\circ\text{C}$), P_c	60W
Operating Junction Temperature, T_J	+150°C
Storage Temperature Range, T_{stg}	-65° to +150°C
Thermal Resistance, Junction-to-Case, R_{thJC}	2.08°C/W

Electrical Characteristics: ($T_J = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Collector–Emitter Sustain Voltage	$V_{CEO(sus)}$	$I_C = 100\text{mA}$, $I_B = 0$		700	–	–	V
Collector–Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 5\text{A}$, $I_B = 1.25\text{A}$		–	–	1.5	V
Base–Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 5\text{A}$, $I_B = 1.25\text{A}$		–	–	1.3	V
Collector Cutoff Current	I_{CES}	$V_{CE} = 1700\text{V}$, $V_{BE} = 0$	$T_J = +125^\circ\text{C}$	–	–	1.0	mA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 5\text{V}$, $I_C = 0$		–	–	200	mA
DC Current Gain	h_{FE1}	$V_{CE} = 5\text{V}$, $I_C = 1\text{A}$		8	–	–	
	h_{FE2}	$V_{CE} = 5\text{V}$, $I_C = 5\text{A}$		6	–	–	
Diode Forward Voltage	V_F	$I_F = 5\text{A}$		–	–	2.0	V

