	т т		0	₿ >	
ØS~					
			LAYOUT SHOWN AS EXAM	APLE	
CHARACTERISTICS	Keying Shown as example				
-Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal				
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	ØS25 MaxZ31 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List	
-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles			FR	Not Listed	
-Delivered without Souriau contacts			PN: 8D511F22SAL		
-Temperature Range65°C to +200°C		A 15-10-2016	Eirst Palaasa		
-Salt Spray : 48 hours					
Mass : 15.89 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°
	TITLE Aluminium Plug 8D		m Plug 8D series		
BASIC SERIES: 8D 5 - 11 F	22 S A L	SCALE	General linear	NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding	Delivered W/O Cor	ntacts NA	Tolerances:	859	
CONTACT TYPE : Standard Crimp Contact	ORIENTATIO		This document is the property SOUDIALL NAVA/N/ SOUDIALLCONA SOURIAU		
SHELL SIZE : 11	ZE : 11 CONTACT TYPE : SOCKET(500 Matings)		SUDITIAD VV VV SUDITIAD.CUIVI it must not be reproduct communicated without per		
		FORMAT			CULC FT
PLATING : F = Nickel	CONTACT LAYOUT : :	A3	SOURIAU D 8D511F22		SHEET

	T	۵ ۵	п П	m	D	0	
4		Contact Layout 22*					
 ت	Ctc A B C D	X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905					
						SOURIAU shall not be liable fo due to a use of the Product the Specifications issued by eith (professional recomme	ts w ier (
N						PN: 8D51	
_	-				A 15-10-201 ISS DATE Designed By:	6 First Release Latest modification - by Date:	
_ _					SCALE NA	Alur General line Tolerances ±	ear s:
					FORMAT	J WWW.SOURIAU	

G

Н

F

Е

A3

D

С

