



Thick Film Chip Resistors, Military / Established Reliability MIL-PRF-55342 Qualified, Type RM



FEATURES

HALOGEN FREE

- Fully conforms to the requirements of MIL-PRF-55342
Established reliability - verified failure rate; M, P, R, U, S, V, and T levels
Construction is sulfur impervious against a high sulfur environment (ASTM B 809-95 test method)
100 % group A screening per MIL-PRF-55342
Termination style B - tin / lead wraparound over nickel barrier
Operating temperature range is -65 °C to +150 °C
For MIL-PRF-32159 zero ohm jumpers, see Vishay Dale's RCWPM Jumper (Military M32159) datasheet (www.vishay.com/doc?31028)
Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

Table with 2 columns: Property and Value. Includes Resistive element (Ruthenium oxide), Encapsulation (Epoxy), Substrate (96 % alumina), Termination (Solder-coated nickel barrier), Solder finish (Tin / lead solder alloy).

Table with 10 columns: VISHAY DALE MODEL, MIL-PRF-55342 STYLE, MIL SPEC. SHEET, TERM., CASE SIZE, POWER RATING P70 °C W, MAX. WORKING VOLTAGE (1) V, RESISTANCE RANGE Ω, TOLERANCE ± %, TEMPERATURE COEFFICIENT (2) ± ppm/°C. Lists various resistor models and their specifications.



**STANDARD ELECTRICAL SPECIFICATIONS**

| VISHAY DALE MODEL         | MIL-PRF-55342 STYLE | MIL SPEC. SHEET | TERM. | CASE SIZE | POWER RATING $P_{70^{\circ}\text{C}}$ W | MAX. WORKING VOLTAGE $V^{(1)}$ | RESISTANCE RANGE $\Omega$ | TOLERANCE $\pm \%$ | TEMPERATURE COEFFICIENT $^{(2)}$ $\pm \text{ppm}/^{\circ}\text{C}$ |
|---------------------------|---------------------|-----------------|-------|-----------|---|--------------------------------|---------------------------|--------------------|--|
| RCWPM-0603, RCWPM-0603-98 | RM0603              | 12              | B     | 0603      | 0.10                                    | 50                             | 1 to 5.1                  | 2, 5, 10           | 200, 300   |
|                           |                     |                 |       |           |   |                                | 5.6 to 22M                | 1, 2, 5, 10        | 100, 200, 300  |
|                           |                     |                 |       |           |   |                                | 5.62 to 10M               | 0.5                | 100, 200, 300  |
| RCWPM-0302, RCWPM-0302-98 | RM0302              | 13              | B     | 0302      | 0.04                                    | 15                             | 1 to 9.1                  | 2, 5, 10           | 200, 300   |
|                           |                     |                 |       |           |   |                                | 10 to 22M                 | 1, 2, 5, 10        | 100, 200, 300  |
|                           |                     |                 |       |           |   |                                | 10 to 10M                 | 0.5                | 100, 200, 300  |

**Notes**

- DSCC has created a series of drawings to support the need for 0201-sized product. Vishay Dale is listed as a resource on this drawing as follows:

| DSCC DRAWING NUMBER | VISHAY DALE MODEL | TERM. | POWER RATING $P_{70^{\circ}\text{C}}$ W | RES. RANGE $\Omega$    | RES. TOL. $\pm \%$ | TEMP. COEF. $\pm \text{ppm}/^{\circ}\text{C}$ | MAX. WORKING VOLTAGE $V^{(1)}$ |
|---------------------|-------------------|-------|---|------------------------|--------------------|---|--------------------------------|
| 07009               | RCWP-0201         | B     | 0.05                                    | 10 to 46.4<br>47 to 1M | 1, 5               | 200<br>100                                    | 30                             |

This drawing can be viewed at: [www.landandmaritime.dla.mil/Programs/MilSpec/ListDwgs.aspx?DocTYPE=DSCCdwg](http://www.landandmaritime.dla.mil/Programs/MilSpec/ListDwgs.aspx?DocTYPE=DSCCdwg)

- (1) Continuous working voltage shall be  $\sqrt{P \times R}$  or maximum working voltage, whichever is less
- (2) Characteristics: K =  $\pm 100 \text{ ppm}/^{\circ}\text{C}$ ; L =  $\pm 200 \text{ ppm}/^{\circ}\text{C}$ ; M =  $\pm 300 \text{ ppm}/^{\circ}\text{C}$
- (3) MIL case size 0705 and EIA case size 0805 are dimensionally the same

**GLOBAL PART NUMBER INFORMATION**

New Global Part Numbering: M55342M02B10E0RWB (preferred part number format)

|   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |  |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|--|
| M | 5 | 5 | 3 | 4 | 2 | M | 0 | 2 | B | 1 | 0 | E | 0 | R | W | B |  |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|--|

| MIL STYLE  | CHARACTERISTICS  | SPEC. SHEET                                    | TERMINATION STYLE                                | VALUE AND TOLERANCE                   | FAILURE RATE  | PACKAGING $^{(1)}$   | SPECIAL  |
|--|--|--|--|---------------------------------------|---|--|--|
| <b>D55342</b> applies to Style 07 (RM1206) only.<br><br><b>M55342</b> applies to all other styles. | <b>K</b> = 100 ppm<br><b>L</b> = 200 ppm<br><b>M</b> = 300 ppm | (see Standard Electrical Specifications table) | <b>B</b> = pre-tinned nickel barrier, wraparound | (see Tolerance and Multipliers table) | <b>C</b> = non-ER<br><b>M</b> = 1.0 %/1000 h<br><b>P</b> = 0.1 %/1000 h<br><b>R</b> = 0.01 %/1000 h<br><b>U</b> = 0.01 %/1000 h $^{(2)}$<br><b>S</b> = 0.001 %/1000 h<br><b>V</b> = 0.001 %/1000 h $^{(2)}$<br><b>T</b> = space level | <b>TP</b> = tin / lead, T/R (full)<br><b>TN</b> = tin / lead, T/R (full), w/ESD<br><b>UL</b> = tin / lead, T/R single lot date code<br><b>S3</b> = tin / lead, T/R (1000 pieces)<br><b>SV</b> = tin / lead, T/R (1000 pieces), w/ESD<br><b>WB</b> = tin / lead, waffle tray<br><b>WA</b> = tin / lead, waffle tray, w/ESD<br><b>WL</b> = tin / lead, waffle tray, single lot date code<br><b>S2</b> = tin / lead, T/R (500 pieces)<br><b>SU</b> = tin / lead, T/R (500 pieces), w/ESD<br><b>S6</b> = tin / lead, T/R (300 pieces)<br><b>ST</b> = tin / lead, T/R (300 pieces), w/ESD | Blank = standard (dash number) (up to 1 digits)<br><b>D</b> = 0.5 % tolerance $^{(3)}$<br><b>S</b> = space level w/option 1 part marking (-97) $^{(4)}$<br><b>T</b> = space level (-98)<br><b>2</b> = option 1 part marking (-20) $^{(4)}$<br><b>3</b> = options 2 and 3 part marking (-30) $^{(4)}$ |

Historical Part Numbering: M55342M02B10E0R (will continue to be accepted)

|           |                 |             |                   |                     |              |                |
|-----------|-----------------|-------------|-------------------|---------------------|--------------|----------------|
| M55342    | M               | 02          | B                 | 10E0                | R            | WB             |
| MIL STYLE | CHARACTERISTICS | SPEC. SHEET | TERMINATION STYLE | VALUE AND TOLERANCE | FAILURE RATE | PACKAGING CODE |

**Notes**



- For additional information on packaging, refer to the Surface Mount Resistor Packaging document ([www.vishay.com/doc?31543](http://www.vishay.com/doc?31543))
- (1) Products with space level failure rates are only offered in packaging codes with ESD overpack and labeling. For all other failure rates, the ESD pack codes are an optional type of packaging
- (2) Failure rates U and V require group A and B inspection ran on each production lot
- (3) Add a "D" after the packaging code at the end of the global part number to specify Vishay Dale Thick Film product with a tolerance of 0.5 %
- (4) MIL spec option 1, 2, and 3 part marking is not offered for the slash sheet 01, 02, 11, and 13 sizes

**RESISTANCE TOLERANCE AND MULTIPLIERS**

| TOLERANCE |       |       |       |        | MULTIPLIER | VALUE RANGE (Ω) |
|-----------|-------|-------|-------|--------|------------|-----------------|
| ± 0.5 %   | ± 1 % | ± 2 % | ± 5 % | ± 10 % |            |                 |
| W         | D     | G     | J     | M      | 1          | 1 to 9xx        |
| Y         | E     | H     | K     | N      | 1000       | 1K to 9xxK      |
| Z         | F     | T     | L     | P      | 1 000 000  | 1M to 22M       |

Examples:


|                        |                      |                      |
|------------------------|----------------------|----------------------|
| 38W8 = 38.8 Ω ± 0.5 %  | 11D3 = 11.3 Ω ± 1 %  | 15J0 = 15 Ω ± 5 %    |
| 10Y0 = 10 kΩ ± 0.5 %   | 10E0 = 10 kΩ ± 1 %   | 10K0 = 10 kΩ ± 5 %   |
| 988W = 988 Ω ± 0.5 %   | 332D = 332 Ω ± 1 %   | 560K = 560 kΩ ± 5 %  |
| 2Z13 = 2.13 MΩ ± 0.5 % | 2F21 = 2.21 MΩ ± 1 % | 8L20 = 8.2 MΩ ± 5 %  |
|                        | 51G0 = 51 Ω ± 2 %    | 10M0 = 10 Ω ± 10 %   |
|                        | 10H0 = 10 kΩ ± 2 %   | 10N0 = 10 kΩ ± 10 %  |
|                        | 33H0 = 33 kΩ ± 2 %   | 2P70 = 2.7 MΩ ± 10 % |
|                        | 22T0 = 22 MΩ ± 2 %   | 8P20 = 8.2 MΩ ± 10 % |

**DIMENSIONS** in inches (millimeters)


| VISHAY DALE MODEL | MIL-PRF-55342 STYLE | MIL SPEC. SHEET | A (LENGTH)                     | B (WIDTH)                      | C (HEIGHT)                     | D (TOP TERM)                   | E (BOTTOM TERM)                               |
|-------------------|---------------------|-----------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|---|
| RCWPM-0502        | RM0502              | 01              | 0.055 ± 0.005<br>(1.40 ± 0.13) | 0.023 ± 0.003<br>(0.58 ± 0.08) | 0.015 ± 0.003<br>(0.38 ± 0.08) | 0.010 ± 0.005<br>(0.25 ± 0.13) | 0.015 ± 0.005<br>(0.38 ± 0.13)                |
| RCWPM-550         | RM0505              | 02              | 0.055 ± 0.005<br>(1.40 ± 0.13) | 0.050 ± 0.005<br>(1.27 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.010 ± 0.005<br>(0.25 ± 0.13) | 0.015 ± 0.005<br>(0.38 ± 0.13)                |
| RCWPM-5100        | RM1005              | 03              | 0.105 ± 0.005<br>(2.67 ± 0.13) | 0.050 ± 0.005<br>(1.27 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.015 ± 0.005<br>(0.38 ± 0.13) | 0.015 ± 0.005<br>(0.38 ± 0.13)                |
| RCWPM-5150        | RM1505              | 04              | 0.155 ± 0.005<br>(3.94 ± 0.13) | 0.050 ± 0.005<br>(1.27 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.015 ± 0.005<br>(0.38 ± 0.13) | 0.015 ± 0.005<br>(0.38 ± 0.13)                |
| RCWPM-7225        | RM2208              | 05              | 0.230 ± 0.005<br>(5.84 ± 0.13) | 0.075 ± 0.005<br>(1.91 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13)                |
| RCWPM-575         | RM0705              | 06              | 0.080 ± 0.005<br>(2.03 ± 0.13) | 0.050 ± 0.005<br>(1.27 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.016 ± 0.008<br>(0.41 ± 0.20) | 0.015 ± 0.005<br>(0.38 ± 0.13)                |
| RCWPM-1206        | RM1206              | 07              | 0.125 ± 0.005<br>(3.18 ± 0.13) | 0.063 ± 0.005<br>(1.60 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.015 ± 0.005<br>(0.38 ± 0.13) | 0.015 ± 0.005<br>(0.38 ± 0.13)                |
| RCWPM-2010        | RM2010              | 08              | 0.197 ± 0.006<br>(5.00 ± 0.15) | 0.098 ± 0.005<br>(2.49 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13)                |
| RCWPM-2512        | RM2512              | 09              | 0.250 ± 0.005<br>(6.35 ± 0.13) | 0.124 ± 0.005<br>(3.15 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13)                |
| RCWPM-1100        | RM1010              | 10              | 0.105 ± 0.005<br>(2.67 ± 0.13) | 0.100 ± 0.005<br>(2.54 ± 0.13) | 0.020 ± 0.005<br>(0.51 ± 0.13) | 0.015 ± 0.005<br>(0.38 ± 0.13) | 0.015 ± 0.005<br>(0.38 ± 0.13)                |
| RCWPM-0402        | RM0402              | 11              | 0.039 ± 0.003<br>(0.99 ± 0.08) | 0.020 ± 0.003<br>(0.51 ± 0.08) | 0.013 ± 0.003<br>(0.33 ± 0.08) | 0.010 ± 0.005<br>(0.25 ± 0.13) | 0.010 ± 0.005<br>(0.25 ± 0.13)                |
| RCWPM-0603        | RM0603              | 12              | 0.063 ± 0.005<br>(1.60 ± 0.13) | 0.032 ± 0.005<br>(0.81 ± 0.13) | 0.018 ± 0.005<br>(0.46 ± 0.13) | 0.012 ± 0.005<br>(0.30 ± 0.13) | 0.015 ± 0.005<br>(0.38 ± 0.13)                |
| RCWPM-0302        | RM0302              | 13              | 0.034 ± 0.004<br>(0.86 ± 0.10) | 0.021 ± 0.003<br>(0.53 ± 0.08) | 0.013 ± 0.003<br>(0.33 ± 0.08) | 0.007 ± 0.005<br>(0.18 ± 0.13) | 0.008 ± 0.005<br>(0.20 ± 0.13)                |
| RCWP-0201         |                     |                 | 0.024 ± 0.002<br>(0.61 ± 0.05) | 0.012 ± 0.002<br>(0.30 ± 0.05) | 0.009 ± 0.002<br>(0.23 ± 0.05) | 0.006 ± 0.003<br>(0.15 ± 0.08) | 0.006 ± 0.002 - 0.004<br>(0.15 ± 0.05 - 0.10) |



**DERATING CURVE**



**CAGE CODE: 91637 and 2799A (formerly SH903)**



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.