APPLICAE	BLE STAND	DARD										
OPERATING		E DANCE	-55 °C TO 85 °	C (1)		RAGE	DE DANG	`E	-10 °C TO 60 °	C (2)		
RATING	TEMPERATURE RANGE		100 V AC			RATING	ATURE RANGE ING HUMIDITY		40 % TO 80 %			
10,41110							JMIDITY		12 13 1 2 2 1			
	CURRENT		0.5 A RAN							(2)		
			SPECIFICATION			S						
ITEM			TEST METHOD			REQUIREMENTS				QT	AT	
CONSTRU		1										
	XAMINATION		LY AND BY MEASURING IN	ISTRUM	1ENT.	ACCO	RDING 1	O DR	RAWING.	×	×	
MARKING			MED VISUALLY.							×	×	
	CHARACT							40	- O MAY	T	_	
CONTACT RESISTANCE CONTACT RESISTANCE		100 mA (DC OR 1000 Hz). 20 mV MAX, 1 mA(DC OR 1000Hz)				40 mΩ MAX. 50 mΩ MAX.				×	+-	
MILLIVOLT LEVEL METHOD		25 HIV WAYS, 1 HALDO ON 1000A2)				50 HIS2 MAX.						
INSULATION RESISTANCE		250 V DC				100 MΩ MIN.					_	
VOLTAGE PROOF		300 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				×	 	
	CAL CHAR											
MECHANICAL OPERATION		100 TIMES INSERTIONS AND EXTRACTIONS.				① CONTACT RESISTANCE: 50 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	_	
VIBRATION		FREQUENCY 10 TO 55 Hz, AMPLITUDE: 1.5 mm,				NO ELECTRICAL DISCONTINUITY OF 1 μs. NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	-	
SHOCK		2 h IN 3 DIRECTIONS. 490 m/s ² , DURATION OF PULSE 11 ms FOR 3 TIMES IN 3 DIRECTIONS.								×	-	
ENVIRON	MENTAL C		TERISTICS	10110.								
DAMP HEAT			DAT 40±2°C, 90 ~ 95	5 %, 96	h.	① CO	NTACT	RESIS	STANCE: 50 mΩ MAX.	×	_	
(STEADY STATE) RAPID CHANGE OF		TEMPERATURE-55→+15~+35→ +85→+15~+35°C				② INSULATION RESISTANCE:100 MΩ MIN.				×	_	
TEMPERATURE		TIME $30 \rightarrow MAX 5 \rightarrow 30 \rightarrow MAX 5 min$ 5 CYCLES.				③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.					_	
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				① CONTACT RESISTANCE: 50 mΩ MAX.② NO HEAVY CORROSION.				×	-	
		EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA 38)								×	-	
RESISTANCE TO		1) REFLOW SOLDERING : 250 °C MAX,				NO DEFORMATION OF CASE OF					-	
SOLDERING HEAT		: 220 °C MIN,				EXCESSIVE LOOSENESS OF THE						
		FOR 60 s 2) SOLDERING IRONS : 360 °C,				TERMINALS.					+_	
		2) 00101		5 s						×		
		SOLDERED AT SOLDER TEMPERATURE,				A NEW UNIFORM COATING OF SOLDER					-	
		240°C, FOR IMMERSION DURATION. 3 s.				SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.						
				T								
COUN	T DE	SCRIPTION	ON OF REVISIONS		DESIG	;NED			CHECKED		DATE	
<u> </u>	TEMPERATUR	RE RISE INC	 CLUDED WHEN ENERGIZED.			APPROVED			HS.OKAWA OS		11.15	
⁽²⁾ THIS STORAGE INDICATE			TES A LONG-TERM STORAGE STATE ODUCT BEFORE THE BOARD MOUNTED.			CHECKED			HS.OZAWA	.OZAWA 05.11.		
									TK.YANAGISAWA			
l Inless of	herwise sna	cified re	efer to MIL-STD-1344.			DRAWN			TK.YANAGISAWA			
		-	urance Test X:Applicable Test			PRAWING NO.				C4-084975-21		
		PECIFICATION SHEET			PART NO.		FX6-100P-0. 8SV1 (91)					
HS.			E ELECTRIC CO., LTD.			CODE NO.		L576	.576-0028-0-91			
EORM HDOOLL	1		<u> </u>			-			-			