

P-Channel Enhancement Mode Power MOSFET

<p>Description</p> <p>The G075P02D5 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge. It can be used in a wide variety of applications.</p> <p>General Features</p> <ul style="list-style-type: none"> ● V_{DS} -20V ● I_D (at $V_{GS} = -10V$) -45A ● $R_{DS(ON)}$ (at $V_{GS} = -4.5V$) < 7.5mΩ ● $R_{DS(ON)}$ (at $V_{GS} = -2.5V$) < 10mΩ ● 100% Avalanche Tested ● RoHS Compliant <p>Application</p> <ul style="list-style-type: none"> ● Power switch ● DC/DC converters 	<p>Schematic diagram</p> <p>pin assignment</p> <p>DFN5X6-8L</p>
---	---

Ordering Information			
Device	Package	Marking	Packaging
G075P02D5	DFN5X6-8L	G075P02	5000pcs/Reel

Absolute Maximum Ratings $T_C = 25^\circ\text{C}$, unless otherwise noted			
Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	-20	V
Continuous Drain Current	I_D	-45	A
Pulsed Drain Current (note1)	I_{DM}	-180	A
Gate-Source Voltage	V_{GS}	± 12	V
Power Dissipation	P_D	63	W
Single pulse avalanche energy (note2)	E_{AS}	49	mJ
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 To 150	$^\circ\text{C}$

Thermal Resistance			
Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Ambient	R_{thJA}	60	$^\circ\text{C}/\text{W}$
Maximum Junction-to-Case	R_{thJC}	2	$^\circ\text{C}/\text{W}$

Specifications $T_J = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
Static Parameters						
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}} = 0\text{V}, I_D = -250\mu\text{A}$	-20	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}} = -20\text{V}, V_{\text{GS}} = 0\text{V}$	--	--	-1	μA
Gate-Source Leakage	I_{GSS}	$V_{\text{GS}} = \pm 12\text{V}$	--	--	± 100	nA
Gate-Source Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = -250\mu\text{A}$	-0.5	-0.65	-1.0	V
Drain-Source On-Resistance	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = -4.5\text{V}, I_D = -15\text{A}$	--	6.3	7.5	$\text{m}\Omega$
		$V_{\text{GS}} = -2.5\text{V}, I_D = -15\text{A}$	--	8.1	10	
Forward Transconductance	g_{FS}	$V_{\text{DS}} = -5\text{V}, I_D = -15\text{A}$	--	72	--	S
Dynamic Parameters						
Input Capacitance	C_{iss}	$V_{\text{GS}} = 0\text{V}, V_{\text{DS}} = -10\text{V}, f = 1.0\text{MHz}$	--	4775	--	pF
Output Capacitance	C_{oss}		--	647	--	
Reverse Transfer Capacitance	C_{rss}		--	597	--	
Total Gate Charge	Q_g	$V_{\text{DD}} = -10\text{V}, I_D = -15\text{A}, V_{\text{GS}} = -10\text{V}$	--	44	--	nC
Gate-Source Charge	Q_{gs}		--	9	--	
Gate-Drain Charge	Q_{gd}		--	11	--	
Turn-on Delay Time	$t_{\text{d}(\text{on})}$	$V_{\text{DD}} = -10\text{V}, I_D = -15\text{A}, R_G = 3\Omega$	--	18	--	ns
Turn-on Rise Time	t_r		--	32	--	
Turn-off Delay Time	$t_{\text{d}(\text{off})}$		--	136	--	
Turn-off Fall Time	t_f		--	59	--	
Drain-Source Body Diode Characteristics						
Continuous Body Diode Current	I_S	$T_C = 25^\circ\text{C}$	--	--	-45	A
Body Diode Voltage	V_{SD}	$T_J = 25^\circ\text{C}, I_{\text{SD}} = -15\text{A}, V_{\text{GS}} = 0\text{V}$	--	--	-1.2	V
Reverse Recovery Charge	Q_{rr}	$I_F = -15\text{A}, V_{\text{GS}} = 0\text{V}$ $dI/dt = -500\text{A/us}$	--	100	--	nC
Reverse Recovery Time	T_{rr}		--	33	--	ns

Notes


1. Repetitive Rating: Pulse width limited by maximum junction temperature

2. EAS condition : $T_J=25^\circ\text{C}$, $V_{\text{DD}}=-20\text{V}$, $V_{\text{GS}}=-10\text{V}$, $L=0.5\text{mH}$, $R_G=25\Omega$


The table shows the minimum avalanche energy, which is 132mJ when the device is tested until failure

3. Identical low side and high side switch with identical R_G


Gate Charge Test Circuit



Switch Time Test Circuit



EAS Test Circuit



Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Drain Source On Resistance




Figure 4. Gate Charge




Figure 5. Capacitance





Figure 6. Source-Drain Diode Forward



Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 7. Drain-Source On-Resistance




Figure 10. Safe Operation Area






Figure 9. Normalized Maximum Transient Thermal Impedance



DFN5X6-8L Package Information



SYMBOL	COMMON			
	MM		INCH	
	MIN.	MAX.	MIN.	MAX.
A	1.03	1.17	0.0406	0.0461
b	0.34	0.48	0.0134	0.0189
c	0.824	0.970	0.0324	0.0382
D	4.80	5.40	0.1890	0.2126
D1	4.11	4.31	0.1618	0.1697
D2	4.80	5.00	0.1890	0.1969
E	5.95	6.15	0.2343	0.2421
E1	5.65	5.85	0.2224	0.2303
E2	1.40	—	0.0551	—
e	1.27	BSC	0.05	BSC
L	0.05	0.25	0.0020	0.0098
L1	0.38	0.50	0.0150	0.0197
L2	0.38	0.71	0.0150	0.0280
H	3.30	3.50	0.1299	0.1378
I	—	0.18	—	0.0070