

承 認 書

SPECIFICATION FOR APPROVAL

*客戶名稱 :
Customer name

*產品名稱 : 电源插座
Product Description

*產品型號 : DC-005BE-2.0-PU
Product part number

*客戶料號 :
Customer's material number

*數量 :
Quantity

*日期 :
Date (R)

| | | | |
|----------|-----|--|--|
| 供應商負責人簽名 | | 皓宇電子 HOUYA ELECTRONICS 客戶負責人確認簽回 | |
| 製作人 | 莫丽琴 | 承認人 | |
| 審核 | 郭远维 | 審核 | |
| 批准 | 王瑞宝 | 批准 | |

皓宇(香港)有限公司
HAOYU (HONG KONG) LIMITED
东莞市弘皓电子有限公司
DONGGUAN HOUYA ELECTRONICS CO. LTD

東莞市石碣鎮四村第一工業區
Sicun 1st Industrial park, Sicun,
Shijie Town, Dongguan

電話 : 13829152824
Tel No

傳真 : (86) 769-82310510
Fax No

郵箱 : hooya89@hooya.hk
E - mail

核 准
Approved






皓宇(香港)有限公司
HAOYU (HONG KONG) LIMITED

索引(INDEX)

| | |
|-------------------------------------|-----|
| 1)承认书首页(HOME PAGE)----- | 1 |
| 2) 索引 (INDEX) ----- | 2 |
| 3)规格书(SPECIFICATION)----- | 3-5 |
| 4)工程图(DRAWING) ----- | |
| 5)环保报告(ROHS)----- | |
| 6) 低毒测试报告(NOXIOUS TEST REPORT)----- | |



皓宇电子
HOOYA ELECTRONICS

| | | |
|---|---------|-------------|
| 皓宇(香港)有限公司 HAOYU (HONG KONG) LIMITED | 文件編號 | HY-WI-32 |
| | 發行日期 | 2008-07-23 |
| SPECIFICATION 承認書 | 第 B-2 版 | 第 1 頁 共 3 頁 |

| | | | |
|---|--|---|--|
| SERIES 產品系列 | DC POWER JACK (DIP) 直插式 DC 電源插座 | TYPE 產品型號 | DC-005BE (環保) |
| DRAWN 設計 | LI JIAN | APVD 審批 | 李劍 |
| 1 · RATING (額定值): DC24V 5A | CONSTRUCTION DIMENSION 結構尺寸 | Apply to the appended drawing. 符合附加圖紙 | |
| 2 · OPERATING TEMPERATURE RANGE 操作溫度範圍 | -20°C~70°C | PRESERVATIVE TEMPERATURE RANGE 儲存溫度範圍 | 15°C~35°C |
| ITEM 項目 | TEST CONDITIONS 測試條件 | SPECIFICATIONS 規格 | |
| 3 · ELECTRICAL PERFORMANCE (電氣性能規格): | | | |
| 3A | CONTACT RESISTANCE 接觸電阻 | MEASURED BY THE CONTACT RESISTANCE APPARATUS OR mΩ METER AT 0.1A DC5V .THE RESULT IS THE AVERAGE OF5 SUCCESSIVE MEASUREMENTS. 在電壓為 5V，直流電流為 0.1A 時，用接觸電阻測量儀或毫歐表測量。結果取測量 5 次後的平均值。 | 50mΩ max 50 毫歐以下 |
| 3B | INSULATION RESISTANCE 絕緣阻抗 | A VOLTAGE OF 250V DC SHALL BE APPLIED FOR 1 MIN. AFTER WHICH MEASUREMENT SHALL BE MADE. BETWEEN TERMINALS BETWEEN INDIVIDUAL TERMINALS AND FRAME 輸入 250V DC 電壓 1 分鐘,按以下接觸方法測試 (1) 接觸端子之間 (2) 插座本體與端子之間 | 100MΩ min 100 兆歐以上. |
| 3C | DIELECTRIC STRENGTH 耐電壓 | A VOLTAGE OF250V AC SHALL BE APPLIED FOR 1 MIN. AFTER WHICH MEASUREMENT SHALL BE MADE. BETWEEN TERMINALS BETWEEN INDIVIDUAL TERMINALS AND FRAME 輸入 250V AC 電壓 1 分鐘,按以下接觸方法測試 (3) 接觸端子之間 (4) 插座本體與端子之間 | WITHOUT DAMAGE TO PARTS ARCING OR BREAKDOWN ETC 沒有損傷 變形絕緣破壞等異常. |
| 4.MECHANICAL PERFORMANCE(機械性能規格) | | | |
| 4A | INSERTION AND WITHDRAW FORCE 插拔力 | Being measure at across spring piece and across matching plug for ergometer 用測力計在插頭與彈片之間進行測量。(空插三次後測試) | Insertion and extraction force 3-30N 插拔力 3-30 牛頓 |
| 4B | TERMINAL STRENGTH 端子強度 | A STATIC LOAD OF 10 N(1000gf) SHALL BE APPLIED TO THE TIP OF THE TERMINALS FOR 60 SEC. IN ANY DIRECTION 在任意一個方向的前端上加力度 10N(1000gf)60 秒鐘 | ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED.WITHOUT DAMAGE OR EXCESSIVE LOOSEN-ESS OF ACTUATOR 在端子中沒有裂開\鬆動等異常滿足於電器性能. |
| 4C | STANDARD ATMOSPHEIC CONDITIONS 使用標準狀態 | UNLESS OTHERWISE SPECIFIED. THE STANDRD RANGE OF ATMOSPHERIC CONDITIONS FOR MAKING MEASUREMENTS AND TESTS ARE AS FOLLOWS: AMDIENT TEMPERATURE: 15°C TO 35°C RELATIVE HUMIDITY :25%TO 85%RH AIR PRESSURE :80Kpa TO 106Kpa | 在沒有指定的情況下測試溫度濕度、氣壓如下： (1) 溫度為 15°C~35°C (2) 濕度為 25%~ 85%RH (3) 氣壓 80Kpa ~106Kpa |

| | | |
|---|---------|-------------|
| 皓宇(香港)有限公司 HAOYU (HONG KONG) LIMITED | 文件編號 | HY-WI-32 |
| | 發行日期 | 2008-07-23 |
| SPECIFICATION 承認書 | 第 B-2 版 | 第 2 頁 共 3 頁 |

| 5 · DURABILITY (耐久性) | | | |
|----------------------|--|--|--|
| 5A | SOLDERABILITY TEST 可焊性試驗 | <p>THE TOP OF THE TERMINALS SHALL BEDIPPED 2mm IN THE SOLDER BATH OF 220 ± 5 °C FOR 3 ± 0.5 SECONDS. THE PLASTIC BODY IS 1.6mm ABOVE THE TIN LIQUID.</p> <p>端子頂部被浸入焊錫池中 2mm 深，溫度為 220±5°C，時間為 3± 0.5 秒。手工焊接溫度為 350±5°C，時間為 2±0.5 秒。膠身距離錫液 1.6mm。</p> <p>注：本產品只適合用手焊、波峰焊。</p> | <p>(1) SOLDER WETTING TIME SHALL BE 3 SEC OR LESS 焊接時間應少於 3 秒</p> <p>(2) THE AREA OF SOLDERABILITY SHOULD BE OVER 90% 焊接面積要有 90%以上</p> |
| 5B | RESISTANCE TO SOLDERING HEAT TEST 耐焊性試驗 | <p>THE TOP OF THE TERMINALS SHALL BEDIPPED 2mm . THE PLASTIC BODY IS 1.6mm ABOVE THE TIN LIQUID. 端子頂部被浸入焊錫池中 2mm 深，膠身距離錫液 1.6mm。</p> <p>Wave-soldering is to be performed within 3seconds at 260 +/-5 °C 波峰焊接溫度 260 +/-5°C 時間 3 秒。</p> <p>Hand weilding to be performed within 3 seconds at 380°C or below. 手工焊接溫度為 380°C 或以內，時間為 3±0.5 秒。</p> <p>注：本產品只適合用手焊、波峰焊。</p> | <p>WITHOUT DEFORMATION OF CASE OR EXCESSIVE LOOSENESS OF TERMINALS ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED.</p> <p>本體無變形，能滿足於機械、電氣性能。</p> |
| 5C | LIFE TEST. 壽命試驗 | <p>WITHOUT LOAD (IT IS TESTED BY MACHINE , ACTING FORCE MUST BE PARALLED TO THE WAY OF PUSHING) :</p> <p>AN ACTUATOR SHALL BE SUBJECT TO 5000 CYCLES AT A SPEED OF 30 CYCLES FOR 1 MIN</p> <p>無負荷 (只限於機器測試，作用力平行於插拔方向) : 操作者以每分鐘 30 次的頻率作 5000 回之無負荷測試。</p> | <p>(1) CONTACT RESISTANCE SHALL BE 70mΩmax</p> <p>(2) MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED.</p> <p>(1) 接觸電阻不能超於 70mΩ</p> <p>(2) 其他滿足於機械電器性能。</p> |
| 5D | HEAT TEST. 耐熱試驗 | <p>85±2°C FOR 48 HOURS AFTER TEST KEEP IN NORMAL CONDITION FOR 30 MINUTES.</p> <p>在 85±2°C 環境中放 48 小時，再放在正常環境中 30 分鐘後進行測試。</p> | <p>THERE SHALL BE NO DAMAGE ON APPEARANCE .</p> <p>MECHANICAL AND ELECTRICAL CHARACTERISTICS SHALL BE SATISFIED</p> <p>外觀無異常，滿足於機械，電器性能。</p> |
| 5E | HUMIDITY TEST. 耐濕試驗 | <p>40 ± 2 °C 90-96%RH FOR 48 HOURS, TEST AFTER KEEPING IN NORMAL CONDITION FOR 30 MIN.</p> <p>在 40±2°C 90—96%RH 環境中放 48 小時，再放在正常環境中，30 分鐘後進行測試。</p> | |
| 5F | COLD TEST. 耐冷試驗 | <p>AT -40 ± 2 °C FOR 48 HRS. AFTER TEST KEEP IN NORMAL CONDITION FOR 30 MIN.</p> <p>在 -40±2°C 環境中放 48 小時，再置於正常環境中 30 分鐘後進行測試。</p> | |
| 5G | SALT SPRAY TEST 噴霧試驗 | <p>AT 5% NACL LIQUOR FOR 24HOURS, AFTER WASHING, KEEP IN NORMAL CONDITION FOR 30 MIN.</p> <p>5%的 Nacl 溶液中噴霧 24 小時，用水清洗並在室溫下放置 30 分鐘</p> | |

| | | |
|---|---------|-------------|
| 皓宇(香港)有限公司 HAOYU (HONG KONG) LIMITED | 文件編號 | HY-WI-32 |
| | 發行日期 | 2008-07-23 |
| SPECIFICATION 承認書 | 第 B-2 版 | 第 3 頁 共 3 頁 |

6· 注意事項 (APPLICATION NOTES:)

1、在耐焊接過程中,不得把松香等絕緣、有腐蝕性物質浸入產品內。

(RO SIN AND OTHER INSULATING AND CAUSTIC MATERIAL CAN NOT BE DIPPED INTO THE ROCKET DURING SOLDERING.)

2、產品焊接後不能用氣槍吹或用溶劑沖洗。

(PRODUCTS CAN NOT BE BLOWN WITH AIR GUN OR CLEANED WITH A SOLVENT AFTER SOLDERING.)

3、產品焊接前各零件不能被溶化。

(ALL PARTS OF THE PRODUCTS CAN NOT BE DISSOLVED BEFORE SOLDERING.)

4、避免儲藏於高溫、潮濕及腐蝕的場所。

(AVOID STORING THE PRODUCTS IN A PLACE AT HIGH TEMPERATURE, HIGH HUMIDITY AND IN CORROSIVE GASES.)

5、貯存期限:自發貨之日起,貯存期不超過 180 天.若超出貯存期限,產生不良品,本公司概不負責。



(SHELF LIFE IS LESS THAN 180 DAYS SINCE THE GOODS WARE SENT OUT FROM OUR FACTORY. OUR COMPANY DOESN'T ACCEPT RESPONSIBILITY FOR REJECTS IF THE SHELF LIFE OF GOODS EXCEEDS 180 DAYS.)

6、本產品如有不良事件,望廠家及時回饋,以便及時記錄、查核、改善、跟蹤。

(PLEASE FEEL FREE TO REPORT TO US IF YOU DISCOVER THE INFERIOR GOODS, SO THAT WE CAN TAKE NOTE, CHECK, TRACK AND IMPROVE THEM. THANKS.)




HAOYU



| | |
|-------|--------|
| MATAL | X |
| SUS | 0.2mm |
| PBS | 0.25mm |

| | | |
|-------|------|------|
| PIN | φ2.0 | φ2.5 |
| APPD. | | |



SCHEMATIC

| | | | | TOLERANCE UNLESS SPECIFIED | | | | | | | |
|-----|-----------------------|----------|-----|----------------------------|---|---------|------------|----------------|-----------|----|----------|
| 6 | DC-005 PING | BRASS | 1 | Ni PLATED | UP TO 5mm: ±0.1 | ANGULAR | 1 | | | | |
| 5 | 3#SPRING | SUS/PBS | 1 | Ag PLATED | ABOVE 5mm: ±0.2 | ±1° | NO | DATE | REVISIONS | BY | APPD |
| 4 | DC-005 4#FLAT PIECE | BRASS | 1 | Ag PLATED | TITLE:DC JACK | | UNIT : MM | ROHS COMPLIANT | DWN | | |
| 3 | DC-005A 2#CURVE PIECE | BRASS | 1 | Ag PLATED | MODEL: DC-005BE-2.0-PU | | SCALE: 4:1 | COMPLIANT | CHK'D | | |
| 2 | DC-005B COVER | PBT | 1 | BLACK | HAOYU(HONGKONG)LIMITED 皓宇(香港)有限公司 | | | | APPD | | |
| 1 | DC-005B CASE | PBT | 1 | BLACK | | | | | | | PRO.AGL: |
| NO. | PART NAME | MATERIAL | QTY | FINISHING | | | | | | | |