


T491D157K016ZT

Obsolete

B45196H, Tantalum, MnO2 Tantalum, 150 uF, 10%, 16 VDC, SMD, Molded, 7343, Height Max = 3.1 mm



Dimensions		
Footprint	7343	
L	7.3mm +/-0.3mm	
W	4.3mm +/-0.3mm	
Н	2.8mm +/-0.3mm	
S	1.3mm +/-0.3mm	
F	2.4mm +/-0.1mm	
K	1.8mm TYP	

Packaging Specifications	
Packaging	T&R, 178mm
Packaging Quantity	750

General Information		
Series	B45196H	
Dielectric	MnO2 Tantalum	
Style	SMD Chip	
Description	SMD, Molded	
RoHS	Yes	
Termination	Tin	
AEC-Q200	No	
Notes	Obsolete. Old Part Number [Obsolete] Was B45196H3157K409.	

Specifications	
Capacitance	150 uF
Capacitance Tolerance	10%
Voltage DC	16 VDC (85C), 10.72 VDC (125C)
Temperature Range	-55/+125°C
Rated Temperature	85°C
Dissipation Factor	10%
Failure Rate	N/A
Leakage Current	24 uA

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.