

SRPE-06E1A0

Non-Isolated DC-DC Converter

The Bel SRPE-06E1A0 is part of the non-isolated DC/DC converter power module series. The modules use a SIP package. These converters are available in a range of output voltages from 0.6 VDC to 5.5 VDC over a wide range of input voltage ($V_{in} = 5.5 - 13.2$ VDC). The efficiency is typically 91% at 3.3 Vout ($V_{in} = 12$ VDC) at full load.



Key Features & Benefits

- 5.5 – 13.2 VDC Input
- 0.6 – 5.5 VDC / 6 A Output
- Non-Isolated
- Under-Voltage Lockout
- High Efficiency
- Wide Trim
- Fixed Frequency
- OCP/SCP
- Low Cost
- Remote On/Off
- Wide Input
- Class II, Category 2, Non-Isolated DC-DC Converter
(refer to IPC-9592B)



Applications

- Networking
- Computers and Peripherals
- Telecommunications

1. MODEL SELECTION

MODEL NUMBER	OUTPUT VOLTAGE	INPUT VOLTAGE	MAX. OUTPUT CURRENT	MAX. OUTPUT POWER	TYPICAL EFFICIENCY
SRPE-06E1A0G	0.6 - 5.5 V	5.5 - 13.2 V	6 A	33 W	91%
SRPE-06E1A0R					

PART NUMBER EXPLANATION

S	R	PE	-	06	E	1A	0	x
Mounting Type	RoHS Status	Series Name		Output Current	Input Range	Output Voltage	Active Logic	Package
Surface Mount	RoHS	SMD SIP		6 A	5.5 - 13.2 V	0.6 - 5.5 V	Active High	G – Tray Package R – Tape and Reel Package

2. ABSOLUTE MAXIMUM RATINGS

PARAMETER	DESCRIPTION	MIN	TYP	MAX	UNITS
Input Supply Voltage		-0.3	-	15	V
Remote On/Off		-0.3	-	15	V
Ambient Temperature		0	-	50	°C
Storage Temperature		-55	-	125	°C
Altitude		-	-	2000	m

NOTE: All specifications are typical at 25 °C unless otherwise stated.

3. INPUT SPECIFICATIONS

PARAMETER	DESCRIPTION	MIN	TYP	MAX	UNIT
Input Voltage		5.5	-	13.2	V
Input Current (full load)	This power module is not internally fused. An input line fuse must always be used	-	-	4.9	A
Input Current (no load)		-	50	150	mA
Remote Off Input Current		-	1	5	mA
Input Reflected Ripple Current (rms)	With simulated source impedance of 1000 nH, 5 Hz to 20 MHz. Use a 1000 µF/25 V AL-Cap with ESR = 0.03 ohm max and 2*100 µF/25 V Tan cap with ESR = 0.013 ohm max, at 100 kHz @ 25°C.	-	7	20	mA
Input Reflected Ripple Current (pk-pk)		-	22	40	mA
I ² t Inrush Current Transient		-	-	1	A ² s
Turn-on Voltage Threshold		4.15	4.2	4.45	V
Turn-off Voltage Threshold		3.7	4	4.2	V

NOTE: All specifications are typical at 25 °C unless otherwise stated.

4. OUTPUT SPECIFICATIONS

PARAMETER	DESCRIPTION	MIN	TYP	MAX	UNIT	
Output Voltage Set Point	Vo, set ≥ 0.9 VDC Vo, set < 0.9 VDC	Setpoint test condition: Vin = 12 V, Iout = half load, Ta = 25°C	-2 -3	- -	2 3	%Vo,set
Load Regulation	Vo ≥ 3.3 VDC Vo < 3.3 VDC	Vin = 12 V, Io = 0 – 6 A, Ta = 25°C	-2 -40	- -	2 40	%Vo,set mV
Line Regulation	Vo ≥ 3.3 VDC Vo < 3.3 VDC	Vin = 8 – 13.2 V, Io = 3 A, Ta = 25°C Vin = 5.5 – 13.2 V, Io = 3 A, Ta = 25°C	-1.5 -15	- -	1.5 15	%Vo,set mV
Regulation Over Temperature			-	0.8	-	%Vo,set
Output Ripple and Noise (pk-pk)	0-20 MHz BW, with 360 µF ceramic capacitor at output.		-	60	200	mV
Output Ripple and Noise (rms)			-	15	80	mV
Output Current Range			0	-	6	A
Output DC Current Limit			7	-	10	A
Output Short-Circuit Current (Vo ≤ 20 mV) (Hiccup Mode)			-	-	4	Adc
Rise Time			-	2	2.5	ms
Turn On Time			-	2.9	5	ms
Overshoot at Turn on			-	0	4.5	%
Output Capacitance		200	-	2000	µF	
TRANSIENT RESPONSE						
△V 50% ~ 100%	Overshoot		-	40	80	mV
Max Load	Settling Time	di/dt = 0.25 A/µs, Vin = 12 VDC, Ta = 25°C, with 360 µF ceramic capacitor at output.	-	80	200	µs
△V 100% ~ 50%	Overshoot		-	40	80	mV
Max Load	Settling Time		-	80	200	µs

NOTE: All specifications are typical at nominal input, full load at 25°C unless otherwise stated.

5. GENERAL SPECIFICATIONS

PARAMETER	DESCRIPTION	MIN	TYP	MAX	UNIT
Switching Frequency		-	650	-	kHz
Efficiency	Vo = 5.5 V Vo = 3.3 V Vo = 0.6 V	92.2 9. 69	94.2 91.6 71	- - -	%
Output Voltage Trim Range (Wide Trim)	This voltage is achieved by trimming up output slowly.	0.6	-	5.5	V
FIT	Calculated Telcordia SR-332, Issue 2 (Vin = 12 V, Vo = 5.5 V, Io = 6 A, Ta = 40°C, no forced air, 90% confidence Level, FIT=10 ⁹ /MTBF)	-	17	-	-
Weight		-	2.5	-	g
Dimensions (L × W × H)			0.41 × 0.315 × 0.65 10.41 × 8.00 × 16.51		inch mm

NOTE: All specifications are typical at nominal input, full load at 25°C unless otherwise stated.

6. REMOTE ON/OFF

PARAMETER	DESCRIPTION	MIN	TYP	MAX	UNIT
Signal Low (Unit Off)	Active High	-0.3	-	0.8	V
Signal High (Unit On)	The remote on/off pin open, Unit off.	2.4	-	18	V

Recommended remote on/off circuit for active high




Figure 1. Control with open collector/drain circuit




Figure 2. Control with photocoupler circuit




Figure 3. Control with logic circuit







Figure 4. Permanently on

7. EFFICIENCY DATA

Figure 5. $V_{out} = 0.6 \text{ V}$ Figure 6. $V_{out} = 3.3 \text{ V}$ 

Figure 7. $V_{out} = 5.5 \text{ V}$

8. TRIM

Trim up circuit (using an external resistor)




Figure 8. Trim up circuit

SRPE-06E1A0 Trim up Resistor Calculate:

$$R_{trim} = \frac{1.2}{V_o - 0.6} k\Omega$$




Figure 9. Trim curve

V_o is the desired output voltage.

R_{trim} is the required resistance between TRIM and GND.

9. THERMAL DERATING CURVES

$V_{in} = 12\text{ V}$, with maximum junction temperature of semiconductors derated to $115\text{ }^{\circ}\text{C}$.




Figure 10. Airflow direction and hot spot




Figure 11. $V_{out} = 0.6\text{ V}$




Figure 12. $V_{out} = 1.8\text{ V}$




Figure 13. $V_{out} = 3.3\text{ V}$




Figure 14. $V_{out} = 5.5\text{ V}$



10. RIPPLE AND NOISE WAVEFORM




Figure 15. Ripple and noise at full load, 12 V input, 0.6 V output and $T_a = 25^\circ C$




Figure 16. Ripple and noise at full load, 12 V input, 3.3 V output and $T_a = 25^\circ C$




Figure 17. Ripple and noise at full load, 12 V input, 5.5 V output and $T_a = 25^\circ C$

NOTE: Test condition of the output ripple and noise: 0 – 20 MHz BW, with 360 μ F ceramic cap at output.

11. TRANSIENT RESPONSE WAVEFORMS




Figure 18. 100%-50% Load Transients at $V_{in} = 12\text{ V}$,
 $V_{out} = 0.6\text{ V}$ @ $T_a = 25^\circ\text{C}$




Figure 19. 50%-100% Load Transients at $V_{in} = 12\text{ V}$,
 $V_{out} = 0.6\text{ V}$ @ $T_a = 25^\circ\text{C}$




Figure 20. 100%-50% Load Transients at $V_{in} = 12\text{ V}$,
 $V_{out} = 3.3\text{ V}$ @ $T_a = 25^\circ\text{C}$




Figure 21. 50%-100% Load Transients at $V_{in} = 12\text{ V}$,
 $V_{out} = 3.3\text{ V}$ @ $T_a = 25^\circ\text{C}$




Figure 22. 100%-50% Load Transients at $V_{in} = 12\text{ V}$, $V_{out} = 5.5\text{ V}$ @ $T_a = 25^\circ\text{C}$




Figure 23. 50%-100% Load Transients at $V_{in} = 12\text{ V}$, $V_{out} = 5.5\text{ V}$ @ $T_a = 25^\circ\text{C}$

NOTE: Test condition of the transient response: $di/dt = 0.25\text{ A}/\mu\text{s}$, with 360 μF ceramic cap at output.

12. INPUT UNDER-VOLTAGE LOCKOUT




Figure 24. Input under-voltage lockout

$V_1 = 4\text{ V}$
 $V_2 = 4.15\text{ V}$

13. SOLDERING INFORMATION

The SRPE-06E1A0 modules are designed to be compatible with a reflow soldering process. The suggested Pb-free solder paste is Sn/Ag/Cu(SAC). The recommended reflow profile using Sn/Ag/Cu solder is shown in the following. Recommended reflow peak temperature is 245°C while the part can withstand peak temperature of 260°C maximum for 10seconds. This profile should be used only as a guideline. Many other factors influence the success of SMT reflow soldering. Since your production environment may differ, please thoroughly review these guidelines with your process engineers.




Figure 25. Solder information

14. MSL RATING

The SRPE-06E1A0 modules have a MSL rating of 3.

15. STORAGE AND HANDLING

The SRPE-06E1A0 modules are designed to be compatible with J-STD-033 Rev: A (Handling, Packing, Shipping and Use of Moisture /Reflow Sensitive surface Mount devices). Moisture barrier bags (MBB) with desiccant are applied. The recommended storage environment and handling procedure is detailed in J-STD-033.

16. PRE-BAKING

This component has been designed, handled, and packaged ready for Pb-free reflow soldering. If the assembly shop follows J-STD-033 guidelines, no pre-bake of this component is required before being reflowed to a PCB. However, if the J-STD-033 guidelines are not followed by the assembler, Bel recommends that the modules should be pre-baked @ 120~125°C for a minimum of 4 hours (preferably 24 hours) before reflow soldering.

17. MECHANICAL DIMENSIONS

OUTLINE






Figure 26. Outline

NOTE: 1) All Pins: Material - Copper Alloy;

Finish – 3 micro inches minimum Gold over 50 micro inches minimum Nickel plate.

2) Un-dimensioned components are shown for visual reference only.

3) All dimensions in inch [mm]; Tolerances: x.xx +/- 0.02 inch [0.51 mm]; x.xxx +/- 0.010 inch [0.25 mm].

PIN DEFINITIONS

PIN	FUNCTION
1	Enable
2	Vin
3	GND
4	Vout
5	Trim

Figure 27. Pins


RECOMMENDED PAD LAYOUT

Figure 28. Recommended pad layout



bel

POWER
SOLUTIONS &
PROTECTION

a bel group

Asia-Pacific
+86 755 298 85888

Europe, Middle East
+353 61 225 977

North America
+1 408 785 5200

18. REVISION HISTORY

DATE	REVISION	CHANGES DETAIL	APPROVAL
2013-08-20	A	First Release 1.Mechanical drawing; 2. Output ripple and noise; 3.Output DC Current Limit; 4.Transient Response; 5.add ROHS logo;	XF.Jiang
2014-01-23	B	6.Output Voltage Set Point; 7.Load Regulation; 8.Line Regulation; 9.Output DC Current Limit; 10.Efficiency; 11.Turn on/off Voltage Threshold; 12.Update on/off description, add a note for UVLO.	XF.Jiang
2014-04-08	C	Update MD.	XF.Jiang
2014-06-24	D	Update MD.	XF.Jiang
2014-07-03	E	Update part number explanation, RoHS compliance, Add MD Note.	XF.Jiang
2014-11-05	F	Update MD.	XF.Jiang
2014-11-18	G	Update General Specifications, TD, MD.	XF.Jiang
2015-11-12	H	Update Input Specs, Output Specs, General, Efficiency Data, NR, TR, MD.	XF.Jiang
2015-12-22	I	Update Output Specs.	XF.Jiang
2016-05-12	J	Update Thermal Derating Curves.	XF.Jiang
2020-06-09	AK	Update mechanical outline	XF.Jiang
2021-06-28	AL	Add object ID.	XF.Jiang

For more information on these products consult: tech.support@psbel.com

NUCLEAR AND MEDICAL APPLICATIONS - Products are not designed or intended for use as critical components in life support systems, equipment used in hazardous environments, or nuclear control systems.

TECHNICAL REVISIONS - The appearance of products, including safety agency certifications pictured on labels, may change depending on the date manufactured. Specifications are subject to change without notice.