

# Features

# Regulated Converter

- Up to 1000 Watt fan-less power / 1200W boost
- Designed and manufactured in Europe
- Efficiency exceeding 90% from 15% load
- Wide Operating temperature range -40...+80°C
- Certified to Industrial, and medical standards
- Analogue control & monitor function
- Custom Variants



## RACM1200-V

**1200 Watt**  
**9" x 3.8"**  
**Enclosed**  
**Single Output**



### Description

The RACM1200-V series is setting a new benchmark for compactness in the class of AC power supplies for reliable fan-less operation supporting long term system availability. A special baseplate cooled design supports heat transfer to allow up to 1000W continuous output power. Up to 1200 Watt output power is available for up to 10 seconds and in boost mode operation or for extended time with sufficient system airflow through the unit. A wide output voltage adjustment range and a combination of constant current limitation and hiccup mode settings makes the product multipurpose. The various analogue control and monitoring functions are accessible via connector. Optional firmware settings available on project base. The RACM1200-V Series can be limited to inherently fail-safe settings on request, using smart, controlled, fault-limiting functions. Only the /PMB Variant supports default settings ex factory to be adjusted, and warning signals to be adopted. An adjustable 12V system fan output and a 1.5kVAC isolated auxiliary stand by output of 5VSB/1A are available to power the application's housekeeping functions. Peak efficiency reaches up to 95% and in standby mode, the unit is compliant to ecodesign requirements. The product holds worldwide safety files to medical, industrial and ITE standards along with electromagnetic compatibility compliance with class A immunity and class B emissions. Spring stainless steel mounting brackets are available separately for a perfect fixation when mounting over the top of the base plate is preferred. All these features make the product one of the easiest to integrate modular power solutions in the industry.



### Selection Guide

Part Number	Input Voltage Range [VAC]	Output Voltage Factory Set [VDC]	Output Voltage Range [VDC]	Max. Output Current [A]	Efficiency typ. <sup>(1)</sup> [%]
RACM1200-24SAV/ENC	80-264	24	24-28	50	95
RACM1200-36SAV/ENC	80-264	36	30-36	40	95
RACM1200-48SAV/ENC	80-264	48	48-56	25	95

#### Notes:

Note1: Efficiency is tested at nominal input and 40-60% load at +25°C ambient temperature

### Accessible Part

Part Number	Description	Datasheet Link
RAC-MB1	mounting bracket	<a href="#">RAC-MB1.pdf</a>

### Model Numbering



#### Notes:

Note2: with suffix "/PMB" PMBus option is built-in (available with 24V and 48V Versions)

For master commands please refer to link:

[www.recom-power.com/RACM1200-SAV\\_PMBus\\_mastercommands.pdf](http://www.recom-power.com/RACM1200-SAV_PMBus_mastercommands.pdf)

IEC/EN62368-1 certified  
 UL62368-1 certified  
 CAN/CSA-C22.2 No. 62368-1 certified  
 IEC/EN60601-1 certified  
 ANSI/AAMI ES60601-1 certified  
 IEC/EN61558-1/2 compliant <sup>(9)</sup>  
 IEC61010-1/-2-201 compliant <sup>(10)</sup>  
 IEC/EN60601-1-2 compliant  
 EN55032/35 compliant  
 EN55024 compliant  
 CB Report



**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)


**BASIC CHARACTERISTICS**

Parameter	Condition	Min.	Typ.	Max.
Nominal Input Voltage	60/50Hz	100VAC		240VAC
Operating Range	47-63Hz	80VAC		264VAC
Input Current	according to CB report		11.5A	14A
Inrush Current	cold start at +25°C, 230VAC			25A
No load Power Consumption	main output REMOTE ON		2W	
Standby Power	main output REMOTE OFF			1W
Minimum Load		0%		
Power Factor			refer to "Power Factor"	
Start-up Time	5VSB Aux.			500ms
	FAN		750ms	1.5s
	main, 800W, 85-264VAC (-25°C to +70°C)		750ms	1.5s
Hold-up Time	800W	20ms		
Output Ripple and Noise <sup>(3)</sup>	20MHz BW, valid for MAIN, 5VSB, FAN			1% of nom. Vout


**Notes:**

Note3: Measurements are made with a 0.1µF MLCC & 10µF E-cap in parallel across output. (low ESR)


**Efficiency vs. Load**



**Power Factor**





**Power Dissipation**



**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

REGULATIONS			
Parameter	Condition		Value
Set Point Accuracy	MAIN		±1.0% max.
	5VSB / FAN		±5.0% max.
Total Regulation	line, load and temperature drift	MAIN & FAN	±2.0% max.
		5VSB Aux.	±5.0% max.


ADDITIONAL FEATURES					
Parameter	Condition		Min.	Typ.	Max.
5VSB Stand By Output Voltage	always on				5VDC
5VSB Stand By Output Current					
Output Voltage Adjustability	tactile button push up/down	24Vout type (100mV steps)	24VDC		28VDC
		36Vout type (150mV steps)	30VDC		36VDC
		48Vout type (200mV steps)	48VDC		56VDC
Remote ON/OFF	maximum allowed voltage referenced to SIGNAL RTN				5VDC
FAN Output Voltage adjustment via FAN ADJ Pin #6 @ TTL levels	CTRL= 2.5VDC CTRL= 2.2VDC...0VDC or open		5VDC	OFF	12VDC
FAN Output Current	ON/OFF with main channel				1A
<b>"Remote Sense"</b>	differential mode, cable loss compensation				500mV
LED Signals (Single RGB LED)	Green continuously Blue intermittent (30% on) Green intermittent (50% on) Green / Red alternatively (50%:50%) Red intermittent (50% on) Red / Blue alternatively (50%:50%) Red continuously		PSU-Good: PSU in standard operation mode STBY: Standby mode; Main Output OFF via REMOTE signal DC-LOW: Signal: {75%<V <sub>OUT</sub> <95%} drives nonlinear loads OTW: Over temperature warning; Output normal operation OTP: Over temperature, Output OFF, self-recovering after cooling OLP: Over load protection: Output OFF, auto-recovery DC-Fail: Output latch-OFF, permanent fault until AC-reset		



\* applicable with standard version  
\*\* applicable with „PMB“ version

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

## SIGNALS



### Notes:

Note4: The outputs are open-drain and require an external pull-up resistor to keep the output in a defined logic state

**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

**Signal Description\***

\*default signal functions of standard firmware setting

**Remote ON/OFF (applicable with standard version)**

Pin position - #17 (CON3 connector). Pin type – input pin, referenced to 'SIGNAL RTN' ground. Maximum allowed voltage level: 5VDC. Leave this signal 'open' (not connected) for always-ON operation. Connect to 'SIGNAL RTN' for 'always-OFF' operation.

NOTE: Typically, use external mechanical switch between pins #17 and #18 of CON3 connector to control the unit's on/off functionality.

**/SCL (applicable with "/PMB" version)**

For master commands please refer to link: [www.recom-power.com/RACM1200-SAV\\_PMBus\\_mastercommands.pdf](http://www.recom-power.com/RACM1200-SAV_PMBus_mastercommands.pdf)

**Remote Sense Activation (applicable with standard version)**

Pin position - #15 (CON3 connector). Pin type – input pin, referenced to 'SIGNAL RTN' ground. Maximum allowed voltage level: 5VDC. Leave this signal 'open' (not connected) for internal output sensing functionality. Connect to 'SIGNAL RTN' for activating the remote main-output voltage sensing. When this functionality is set active, the pins 'Remote Sense +' (pin #10) and 'Remote Sense RTN' (pin #9) must be connected to the load points where customer wants to remotely monitor the main output amplitude. When this functionality shall be left inactive (default state), the remote sensing lines 'Remote Sense+' and 'Remote Sense RTN' must stay unconnected.

NOTE: Typically, activating this feature comes together with an external wired sense line connections to the load point, which is expected to be done at process of installing the unit within a system.

**/SDA (applicable with "/PMB" version)**

For master commands please refer to link: [www.recom-power.com/RACM1200-SAV\\_PMBus\\_mastercommands.pdf](http://www.recom-power.com/RACM1200-SAV_PMBus_mastercommands.pdf)

**AC\_OK**

Pin position - #13 (CON3 connector). Pin type – open-collector output pin, referenced to 'SIGNAL RTN' ground. Minimal pull-up resistor: 5kOhm. Maximal pull-up rail voltage: 5VDC. Maximal output current (+25°C): 1mAmp. Active status: low. Output voltage at active-low state (+25°C): max. 0.4V. Recommended usage: pull-up resistor of 10kOhm to +5VSB voltage rail. The 'AC\_OK' signal is set active-low state, when input AC line is more than typ.80VACrms. The 'AC\_OK' signal is set inactive-high state, when input AC line is less than typ.70VACrms.

**PSU\_GOOD**

Pin position - #14 (CON3 connector). Pin type – open-collector output pin, referenced to 'SIGNAL RTN' ground. Minimal pull-up resistor: 5kOhm. Maximal pull-up rail voltage: 5VDC. Maximal output current (+25°C): 1mAmp. Active status: low. Output voltage at active-low state (+25°C): max. 0.4V. Recommended usage: use pull-up resistor of 10kOhm to +5VSB voltage. The 'PSU\_OK' signal is set active-low state, when 3 conditions are met: outputs are present, temperature is within limits (less than warning temperature) and no internal failure is activated (e.g. OTP, OCP, OLP, etc.) The 'PSU\_OK' signal is set inactive-high state, when at least one of the above 3 conditions is not met.

PROTECTIONS		
Parameter	Type	Value
Internal Input Fuse	L and N (dual fusing)	2x T12A/250VAC
Over Voltage Category (OVC)	IEC62368-1; IEC61010-1 <sup>(10)</sup>	OVCII
	IEC62477-1; up to 2000m	OVCIII
Over Temperature Protection (OTP)	detected on internal sensors	auto recovery after cooling down to +70°C (±5°C)
Over Temperature Warning		refer to <b>"LED Signals"</b> and <b>"PSU_GOOD"</b> description
Class of Equipment	with PE	Class I
Isolation Voltage <sup>(6)</sup>	I/P to O/P (unit)	4kVAC
	I/P and O/P to chassis	1.5kVAC
	O/P to 5VSB & signals; 5VSB & signals to chassis (when factory bridge #7 to #16 is removed)	1.5kVAC
Insulation Grade	I/P to O/P	reinforced
Earth Leakage Current		NC: 300µA max.; SFC: 1mA
Patient Leakage		NC: 100µA max.; SFC: 500µA
Means of Protection		2MOPP
Medical Device Classification		built-in, suitable for Type BF rated medical applications
<b>Notes:</b>		
Note5: For repeat Hi-Pot testing, reduce the time and/or the test voltage		

**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

**PROTECTIONS MAIN OUTPUT**

Parameter	Type	Value	
Short Circuit Protection (SCP)		auto recovery, hiccup mode	
Over Voltage Protection (OVP) <sup>(6)</sup>	main output and fan output protection activated	24Vout	29.5VDC typ.
		36Vout	38.8VDC typ.
		48Vout	59VDC typ.
Over Load Protection (OLP)	refer to <b>“Over Load Protection”</b>	max. power / max. current limiting / hiccup mode	

**Notes:**

Note6: Unit is not protected for reversal polarity on the output and can be damaged during this event


**Over Load Protection**

The unit operates in constant-voltage mode until the max. output power is reached. In case of overload, the unit then decreases the output voltage according the constant power curve until the current reaches the maximum output current. Permanent operation in overload may damage the unit. Refer to **“Suggested Power Rating for main Output”**

For even higher load demands, the unit delivers the max. Iout current and further reduces the output voltage (constant-current curve). When the output is less than 80% of the minimal output voltage, the unit shuts-off and triggers short circuit protection mode of Main and Fan Output (unlimited hiccup mode, 4 sec period).

\*\* In case of use in extended constant current limitation, after 4s the unit enters into up to 4 cycles hiccup mode followed by latch off.

For continuous operation with reduced power (limited to max.700 Watt) see [PMBus master-commands](#) STATUS\_IOUT bitmap for constant current with limited max. output power.



**PROTECTIONS FAN**

Parameter	Type	Value
Short Circuit Protection (SCP)		auto recovery
Over Voltage Protection (OVP)	main output and fan output protection activated	auto recovery, hiccup mode
Over Current Protection (OCP)		auto recovery, power limitation

**PROTECTIONS 5VSB**

Parameter	Type	Value
Short Circuit Protection (SCP)	all outputs protection will be activated	auto recovery, hiccup mode
Over Voltage Protection (OVP)		auto recovery, hiccup mode
Over Current Protection (OCP)		auto recovery, hiccup mode

**ENVIRONMENTAL**

Parameter	Condition		Value
Operating Temperature Range	refer to <b>“Main Output Nominal Power Rating vs. Ambient Temperature”</b>	T <sub>AMB</sub> and T <sub>BASE</sub> temperature max. start-up temperature	-40°C to +80°C +70°C typ.
Operating Altitude <sup>(7)</sup>	IEC/EN62368-1		5000m
	ANSI/AAMI/EN60601-1 (pending)		4000m
Operating Humidity	non-condensing		95% RH max.
IP Rating			IP20
Pollution Degree			PD2
Shock	random	5-500Hz, 2Grms, 15 min for each axis	according to IEC60068-2-64
	sinusoidal	5-500Hz, 20m/s <sup>2</sup> 15 min for each axis	according to IEC60068-2-6
Vibration (Bump)	Half Sine 100m/s <sup>2</sup> , 11ms duration, 100 pulse per direction		according to IEC60068-2-29
Design Lifetime	+40°C (refer to <b>“thermal reference point”</b> )		88 x 10 <sup>3</sup> hours



**Notes:**

Note7: Recognized by safety agency for safe operation up to 5000m. High altitude operation above 2000m may impact the performance and lifetime. Please contact RECOM tech support for advice.

continued on next page

Specifications (measured @  $T_a = 25^\circ\text{C}$ , nom.  $V_{in}$ , full load and after warm-up unless otherwise stated)


Suggested Power Rating for main Output



The units were evaluated to safety files for nominal input voltages 100-240VAC; including a tolerance band of  $\pm 10\%$ , with a specified maximum  $T_{BASE}$  of  $80^\circ\text{C}$  for full load rating with  $50^\circ\text{C}$   $T_{AMB}$  and up to  $80^\circ\text{C}$   $T_{AMB}$  at reduced output power.  $T_{BASE}$  at reference point (see "thermal reference point") shall not exceed  $70^\circ\text{C}$ ,  $80^\circ\text{C}$  or  $90^\circ\text{C}$  depending on the condition as per derating graph.

Peak power was evaluated at 60s duty cycle period for safety files. Without externally provided forced airflow, continuous output power needs to be limited to 1000W at high input voltage range and  $T_{AMB} < 40^\circ\text{C}$  with a  $T_{BASE} < 70^\circ\text{C}$ . With forced airflow of 2.5m/s 1200W continuous boost power at high input voltage range ( $> 172\text{V}$ ) is available.

Main Output Nominal Power Rating vs. Ambient Temperature



Notes:

Note8: Below  $T_{AMB} - 25^\circ\text{C}$  some specifications may not be met

Note9: Output Power at  $T_{AMB} = -40^\circ\text{C}$  cold start  $\leq 250\text{W}$ .

Note10: At  $T_{AMB} + 80^\circ\text{C}$  and 30% load, the maximum allowed baseplate temperature  $T_{BASE} \leq 90^\circ\text{C}$  measured on thermal reference point. Refer to "thermal reference point"



**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

**PEAK LOAD CAPABILITY**


PEAK POWER IS NOT AVAILABLE DURING START UP PHASE!

Exceeding power ratings, may reduce the lifetime and lead to OLP power limitation or OTP temperature shut off. Inherently safe unit set up for more strict automatic power limitation is available on request per firmware setting option. Peak Power duty cycle plus recovery period shall not exceed 90% of the average nominal power for repetitive load conditions.

**Peak Load Calculation**

$$P_{nom} * 0.9 * (t_{rec} + t_{peak}) \geq P_{peak} * t_{peak} + P_{rec} * t_{rec}; [t_{rec} + t_{peak} \geq 60s]$$

$P_{nom}$	... nominal power output (as per derating graph)	[W]
$P_r$	... applied recovery power	[W]
$P_p$	... applied peak power	[W]
$t_r$	... recovery time	[s]
$t_p$	... peak time	[s]
	$V_{IN} < 172VAC = 4s$	[s]
	$V_{IN} \geq 172VAC-264VAC = 10s$	[s]



**SAFETY AND CERTIFICATIONS**

Certificate Type (Safety)	Report Number	Standard
Audio/video, information and communication technology equipment- Safety requirements (CB)	T223-0052/22	IEC62368-1:2014 2nd Edition
Audio/video, information and communication technology equipment - Safety requirements		EN62368-1:2014 + A11:2017
Audio/video, information and communication technology equipment- Safety requirements (CB)	E224736-A6006-UL	UL62368-1:2014
Audio/video, information and communication technology equipment - Safety requirements		CAN/CSA-C22.2 No. 62368-1:2014
Medical Electric Equipment, General Requirements for Safety and Essential Performance	E314885-D1007-1-A0-C0-UL	ANSI/AAMI ES60601-1:2005 CAN/CSA-C22.2 No. 60601:14
Medical Electric Equipment, General Requirements for Safety and Essential Performance (CB)	T223-0756/21	IEC60601-1:2005, 3rd Edition + AM1:2012
Medical Electric Equipment, General Requirements for Safety and Essential Performance		EN60601-1:2006 + A1:2013
Safety of transformers, reactors, power supply units and combinations thereof - Part 1: General requirements and tests	compliant <sup>(11)</sup>	IEC61558-1:2005, 2nd Edition + A1:2009 EN61558-1:2005 + A1:2009
Electrical Equipment For Measurement, Control, and Laboratory Use; Part 1: General Requirements	compliant <sup>(12)</sup>	IEC61010-1/-2-201
RoHS2		RoHS 2011/65/EU + AM2015/863

**Notes:**

Note11: Insulation inside transformer meets requirements for insulation and overload per IEC61558-1 (tested in T223-0765/20)

Note12: Creepage and clearance according to IEC61010-1/-2-201 (tested in T223-0766/20)

continued on next page



**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

<b>EMC Compliance (Medical)</b>		
Medical electrical equipment - Part 1-2: General requirements for basic safety and essential performance - Collateral standard: Electromagnetic compatibility - Requirements and tests		IEC60601-1-2:2014, Class B EN60601-1-2:2015, Class B
Industrial, scientific and medical equipment - Radio frequency disturbance characteristics - Limits and methods of measurement		EN55011, Class B
Industrial, scientific and medical equipment - Radio-frequency disturbance characteristics - Limits and methods of measurement <sup>(12)</sup>		CISPR 11, Group 1, Class B
ESD Electrostatic discharge immunity test	Contact: ±8kV	IEC61000-4-2:2008 EN61000-4-2:2009
Radiated, radio-frequency, electromagnetic field immunity test	10V/m (80-1000MHz, 1.0-2.7GHz) 27V/m (385MHz) 28V/m (450, 810, 870, 930, 1720, 1845, 1970, 2450MHz) 9V/m (710, 745, 780, 5240, 5500, 5785MHz)	IEC61000-4-3:2006+A2:2010 EN61000-4-3:2006+A2:2010
Fast Transient and Burst Immunity	AC Power Port: ±4kV	IEC/EN61000-4-4:2012
Surge Immunity	AC Power Port: L-N ±4kV L-PE, N-PE: ±3kV	IEC/EN61000-4-5:2014
Immunity to conducted disturbances, induced by radio-frequency fields	3Vrms (0.15-80MHz) 6Vrms (ISM, amateur radio bands)	IEC61000-4-6:2013 EN61000-4-6:2014
Power Magnetic Field Immunity	30A/m, 50Hz	IEC61000-4-8:2009 EN61000-4-8:2010
Voltage Dips and Interruptions	Voltage Dip 100% (0.5P) Voltage Dip 100% (1.0P) Voltage Dip 30% Voltage Interruption 100%	IEC/EN61000-4-11:2004
Limits of Harmonic Current Emissions	Class A	EN61000-3-2
Limits of Voltage Fluctuations & Flicker	Clause 5	EN61000-3-3
<b>EMC Compliance (Industrial)</b>		
Electromagnetic compatibility of multimedia equipment - Emission requirements <sup>(13)</sup>		EN55032:2015, Class B
Electromagnetic compatibility of multimedia equipment - Immunity requirements		EN55035:2017
Information technology equipment - Immunity characteristics - Limits and methods of measurement		EN55024:2010 + A1:2015
Limitations on the amount of electromagnetic interference allowed from digital and electronic devices		FCC 47 CFR Part 15 Subpart B, ANSI C63.4:2014, Class B
<b>Notes:</b>		
Note13: The emission performance was tested with snap-on ferrite Wurth 742 712 21. The 48V versions with 2-turns of AC-line cable; the 24V version with 2-turns of N (neutral) line only. The output cables were used twisted pair lines, with the typical configuration of grounded return lines.		
Note14: Performance criteria A indicates operation within ±10% tolerance band of nominal settings		


<b>DIMENSION AND PHYSICAL CHARACTERISTICS</b>		
Parameter	Type	Value
Material	case/baseplate PCB	aluminum FR4 (UL94 V-0)
Dimension (LxWxH)		228.0 x 96.2 x 40.0mm
Weight		1000g. typ.

continued on next page


**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

**Dimension Drawing (mm)**

Front View (Input)



Back View (Output/Signal)



**Connector information**

**AC Input CON1**

#	Function	Terminal
1	AC/L	Phoenix
2	PE	TDPT 4-SP-6.35
3	AC/N	

**DC Output Connector CON2**

#	Function	Terminal
1,1	-Vout	Phoenix
2,2	+Vout	TDPT 2.5-SP-5.w08


**General tolerances according to ISO 2768-m (table for reference only)**

Dimension range	Tolerances
0.5 - 6 mm	±0.1 mm
6 - 30 mm	±0.2 mm
30 - 120 mm	±0.3 mm
120 - 400 mm	±0.5 mm

**Connector information CON3**

**Cvilux CI0120P1HD0.NH Type Pin Header**

#	Function	#	Function
2	Reserved for factory config.	1	reserved for factory config.
4	Reserved for factory config.	3	NC
6	FAN ADJ	5	FAN+
8	NC	7	FAN RTN *
10	Remote Sense+	9	Remote Sense RTN
12	NC	11	NC
14	PSU_GOOD	13	AC_OK
16	Signal RTN *	15	Remote Sense Activation** / SDA***
18	Signal RTN	17	Remote ON/OFF** / SCL***
20	5VSB RTN	19	5VSB+



\* factory bridge from Pin7 (FAN RTN) to Pin16 (Signal RTN)

\*\* applicable with standard version

\*\*\* applicable with "/PMB" version

**Mating connector CON3**

Housing= Cvilux CI0120SD000


Contact= Cvilux CI01TD21PE0

Connection wire cross sections: during building in the product, installer needs to take care to use wires with appropriate cross-section for the rated voltage/currents


**INSTALLATION AND APPLICATION**

**Mounting suggestions**


horizontal



side



upside down






If the PSU is horizontal, upside down or side mounted, no derating is required.

With forced air cooling, mounting orientation has no impact on output power. Device should be fan cooled from AC side.

If thermal conduction cooling is suggested, use of heat sink compound is recommended for improved heat transfer via baseplate.

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

Dimension Drawing (mm)



Dimensions marked with \* are for pre-fixing features


General tolerances according to ISO 2768-m (table for reference only)

Dimension range	Tolerances
0.5 - 6 mm	±0.1 mm
6 - 30 mm	±0.2 mm
30 - 120 mm	±0.3 mm
120 - 400 mm	±0.5 mm

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

**INSTALLATION AND APPLICATION**

Mounting with RECOM RAC-MB-1 accessory kit<sup>(15)</sup>:



**Notes:**

Note15: Although sufficient heat transfer via base plate can be achieved with just 3 screws per side, the use of 2x4 screws is recommended.

**PACKAGING INFORMATION**

Parameter	Type	Value
Packaging Dimension (LxWxH)	cardboard box	303.0 x 164.0 x 45.0mm
Packaging Quantity		1pcs
Storage Temperature Range		-40°C to +85°C
Storage Humidity	non-condensing	90% RH max.

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.