



- SPECIFICATIONS**
1. Current Rating: 3A AC, DC
  2. Voltage Rating: 250V AC, DC
  3. Temperature Range: -25°C~ +85°C
  4. Contact Resistance: 20mΩ Max
  5. Insulation Resistance: 1000mΩ Min
  6. Withstanding Voltage: 1000V AC/minute
  7. Material: Wafer Nylon66 UL94-VO (2)  
Pin Brass Tin-plated

Circuit	Part NO.	Dimensions mm	
		A	B
2	XD-XH-2A-PF	2.50	7.50
3	XD-XH-3A-PF	5.00	10.00
4	XD-XH-4A-PF	7.50	12.50
5	XD-XH-5A-PF	10.00	15.00
6	XD-XH-6A-PF	12.50	17.50
7	XD-XH-7A-PF	15.00	20.00
8	XD-XH-8A-PF	17.50	22.50
9	XD-XH-9A-PF	20.00	25.00
10	XD-XH-10A-PF	22.50	27.50
11	XD-XH-11A-PF	25.00	30.00
12	XD-XH-12A-PF	27.50	32.50
13	XD-XH-13A-PF	30.00	35.00
14	XD-XH-14A-PF	32.50	37.50
15	XD-XH-15A-PF	35.00	40.00
16	XD-XH-16A-PF	37.50	42.50

**Ordering Information**

XD - XH - N \*\*\* - \* - \*\*

Pin	Type	Colour	Contact Plating
	针型	颜色	镀层
	A=直针	和红色	0.1µr Gold
	AH=斜针	绿色	0.2µr Gold
	AL=冲针	蓝色	0.3µr Gold
	AM=冲针	黄色	0.5µr Gold
		白色	1.0µr Gold
		棕色	2.0µr Gold
		黑色	3.0µr Gold
		灰色	4.0µr Gold
		紫色	5.0µr Gold
		银色	6.0µr Gold
		铜色	7.0µr Gold
		镍色	8.0µr Gold
		铬色	9.0µr Gold
		锌色	10.0µr Gold
		锡色	11.0µr Gold
		铅色	12.0µr Gold
		铋色	13.0µr Gold
		锑色	14.0µr Gold
		碲色	15.0µr Gold
		硒色	16.0µr Gold
		砷色	17.0µr Gold
		锆色	18.0µr Gold
		铈色	19.0µr Gold
		镧色	20.0µr Gold

GENERAL TOLERANCE			制图 DRAWING	10	<b>深圳讯答科技有限公司</b> ShenzhenXunDaTechnology Co.,Ltd	产品名称 TITLE	XH (2.50) 单排 直针 增强	版本 REV.	A
DIM TOL			审核 CHECK			产品料号 PART NO.	XD-XH-NA-PF	单位 UNITS	mm
X.X ±0.30			批准 APPROVAL		材料 MATERIAL		页次 SHEET	1/1	
X.XX ±0.20			比例 SCALE						
X.XXX ±0.10			投影 Projection						
Angle ±3.0°									
1	初版发行								
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE							