


Construction

- Dielectric: Metallized Polypropylene
- Wound Technology
- Plastic box case (UL 94 V-0)
- Epoxy resin sealing


Terminals

- Parallel wire leads, tinned
- Lead length (C):
- Lead executions:

 6^{-1} mm

Number of Wires	Lead Ø mm	P(mm)		
		27.5	37.5	52.5
2-pin	0.8	D	---	---
	1.0	E	E	---
	1.2	F	F	---
4-pin	1.2	---	G	G

■ Standard lead diameter (Preferred).

Marking

- Manufacturer's logo
- Rated capacitance (coded)
- Tolerance
- Rated dc voltage
- Type number

Electrical Characteristics

Reference standard	IEC 61071/ IEC 60068 / IEC60384-16						
Capacitance tolerance	J ($\pm 5\%$), K ($\pm 10\%$)						
Climatic category	40/100/56						
Voltage derating at high temperature	$85 \leq T \leq 100 \text{ }^\circ\text{C}$. $U_{op} = (165 - T) / 80 \times U_N$						
D.F. $\tan \delta$ (in 10^{-3}) at $20 \text{ }^\circ\text{C}$ at 1 kHz	≤ 1						
Insulation Resistance ($R_{IS}C$, at 100Vdc, $20 \text{ }^\circ\text{C}$ and $RH \leq 65\%$)	30 000 s						
Test Voltage between terminations (acc. to IEC61071)	$1.5 \times U_N$, 10 s / $1.65 \times U_N$, 2 s.						
Pulse Rise Time (dV/dt)	Refer to table						
Maximum peak current (I_{PK} , Amps)	$C(\mu\text{F}) \times dV/dt$ (V/ μs)						
Peak non-repetitive current	$1.5 \times I_{PK}$						
Continuous operation voltage @ $70 \text{ }^\circ\text{C}$ (U_{OP})	<table border="1"><tr><td>U_{OP}(V)</td><td>450</td><td>630</td><td>800</td><td>900</td><td>1050</td></tr></table>	U_{OP} (V)	450	630	800	900	1050
U_{OP} (V)	450	630	800	900	1050		
Nominal operation voltage @ $85 \text{ }^\circ\text{C}$ (U_N)	<table border="1"><tr><td>U_N (V)</td><td>300</td><td>450</td><td>630</td><td>750</td><td>875</td></tr></table>	U_N (V)	300	450	630	750	875
U_N (V)	300	450	630	750	875		
Maximum peak voltage (U_{PK})	<table border="1"><tr><td>U_{PK} (V)</td><td>450</td><td>675</td><td>950</td><td>1125</td><td>1300</td></tr></table>	U_{PK} (V)	450	675	950	1125	1300
U_{PK} (V)	450	675	950	1125	1300		



C _R μF	U _N (V _{dc})	U _{RMS} (V _{ac})	U _{PK} (V _{dc})	dV/dt (V/μs)	Dimensions (Max.) b x h x l (mm)	P (mm)	P1 4-pin (mm)	Ordering Code	ESR (mΩ) @ 100 KHz				I _{RMS} (A) @ 100 KHz, 70°C				PU (pcs)
									2-pin		4-pin		2-pin		4-pin		
									Ø 0.8	Ø 1.0	Ø 1.2	Ø 1.2	Ø 0.8	Ø 1.0	Ø 1.2	Ø 1.2	
2.2	300	160	450	40	11.0x19.0x31.5	27.5	---	B32674□3225+	12.0	11.5	11.0	---	7	7	8	---	320
3.3	300	160	450	40	12.5x21.5x31.5	27.5	---	B32674□3335+	9.0	8.4	7.8	---	7	8	10	---	280
3.3	300	160	450	22	12.0x22.0x42.0	37.5	---	B32676□3335+	---	13.1	12.2	---	---	7	9	---	135
4.7	300	160	450	40	14.0x24.5x31.5	27.5	---	B32674□3475+	7.0	6.5	6.0	---	7	10	12	---	260
4.7	300	160	450	22	12.0x22.0x42.0	37.5	---	B32676□3475+	---	12.2	11.5	---	---	8	10	---	135
5.6	300	160	450	40	15.0x24.5x31.5	27.5	---	B32674□3565+	6.6	6.2	5.8	---	7	8	12	---	240
5.6	300	160	450	22	14.0x25.0x42.0	37.5	---	B32676□3565+	---	11.6	10.8	---	---	9	10	---	115
6.5	300	160	450	22	14.0x25.0x42.0	37.5	---	B32676□3655+	---	10.8	10	---	---	9	10	---	115
6.8	300	160	450	40	18.0x27.5x31.5	27.5	---	B32674□3685+	6.4	5.9	5.5	---	7	9	12	---	200
6.8	300	160	450	22	16.0x28.5x42.0	37.5	---	B32676□3685+	---	10.4	9.4	---	---	9	11	---	100
8.0	300	160	450	40	16.0x32.0x31.5	27.5	---	B32674□3805+	6.0	5.5	5.0	---	7	9	12	---	220
8.2	300	160	450	40	18.0x33.0x31.5	27.5	---	B32674□3825+	6.0	5.2	4.8	---	7	9	12	---	200
10	300	160	450	40	21.0x31.0x31.5	27.5	---	B32674□3106+	5.3	4.6	4.2	---	7	10	12	---	180
10	300	160	450	22	18.0x32.5x42.0	37.5	---	B32676□3106+	---	7.7	6.9	---	---	10	12	---	90
12	300	160	450	40	22.0x36.5x31.5	27.5	---	B32674□3126+	5.2	4.5	4.0	---	7	10	12	---	160
12	300	160	450	22	18.0x32.5x42.0	37.5	---	B32676□3126+	---	6.8	6.1	---	---	10	12	---	90
15	300	160	450	22	20.0x39.5x42.0	37.5	10.2	B32676□3156+	---	5.8	5.2	4.0	---	10	12	20	75
20	300	160	450	22	28.0x37.0x42.0	37.5	10.2	B32676□3206+	---	5	4.3	3.1	---	10	12	22	55
22	300	160	450	22	28.0x42.5x42.0	37.5	20.3	B32676□3226+	---	4.8	4.1	3.0	---	10	12	22	55
25	300	160	450	22	28.0x42.5x42.0	37.5	20.3	B32676□3256+	---	4.6	3.8	2.8	---	10	12	22	55
30	300	160	450	22	30.0x45.0x42.0	37.5	20.3	B32676□3306+	---	4.4	3.7	2.6	---	10	12	22	54
30	300	160	450	15	30.0x45.0x57.5	52.5	20.3	B32678□3306+	---	---	---	4	---	---	---	22	36
35	300	160	450	15	30.0x45.0x57.5	52.5	20.3	B32678□3356+	---	---	---	3.4	---	---	---	22	36
40	300	160	450	15	30.0x45.0x57.5	52.5	20.3	B32678□3406+	---	---	---	3	---	---	---	22	36
47	300	160	450	15	35.0x50.0x57.5	52.5	20.3	B32678□3476+	---	---	---	2.7	---	---	---	22	28
60	300	160	450	15	35.0x50.0x57.5	52.5	20.3	B32678□3606K	---	---	---	2.6	---	---	---	22	28

' ' = 'D' for Ø0.8mm, 'E' for Ø1.0mm, 'F' for Ø1.2mm, 'G' for 4-pin. See page 1 for preferred lead execution.

'+' = Tolerance J (5%), K (10%).

PU = Packing unit.

Other executions, intermediate values upon request.



C _R μF	U _N (V _{dc})	U _{RMS} (V _{ac})	U _{PK} (V _{dc})	dV/dt (V/μs)	Dimensions (Max.) b x h x l (mm)	P (mm)	P1 4-pin (mm)	Ordering Code	ESR (mΩ) @ 100 KHz				I _{RMS} (A) @ 100 KHz, 70°C				PU (pcs)
									2-pin		4-pin		2-pin		4-pin		
									Ø 0.8	Ø 1.0	Ø 1.2	Ø 1.2	Ø 0.8	Ø 1.0	Ø 1.2	Ø 1.2	
1.5	450	275	675	75	11.0x19.0x31.5	27.5	---	B32674□4155+	7.9	7.5	7.1	---	8	9	10	---	320
2.2	450	275	675	75	12.5x21.5x31.5	27.5	---	B32674□4225+	6.3	6.0	5.7	---	9	10	11	---	280
2.2	450	275	675	54	12.0x22.0x42.0	37.5	---	B32676□4225+	---	14.0	13.1	---	---	9	10	---	135
3	450	275	675	54	12.0x22.0x42.0	37.5	---	B32676□4305+	---	13.7	12.7	---	---	10	11	---	135
3.3	450	275	675	75	15.0x24.5x31.5	27.5	---	B32674□4335+	4.7	4.3	4.0	---	9	10	12	---	240
3.3	450	275	675	54	14.0x25.0x42.0	37.5	---	B32676□4335+	---	13.2	12.2	---	---	10	11	---	115
4	450	275	675	54	14.0x25.0x42.0	37.5	---	B32676□4405+	---	12.2	11.1	---	---	11	12	---	115
4.7	450	275	675	75	18.0x27.5x31.5	27.5	---	B32674□4475+	4.8	4.1	3.5	---	9	11	14	---	200
4.7	450	275	675	54	16.0x28.5x42.0	37.5	---	B32676□4475+	---	11.5	10.3	---	---	12	13	---	100
5.0	450	275	675	75	16.0x32.0x31.5	27.5	---	B32674□4505+	4.8	4.1	3.5	---	9	11	14	---	220
5.6	450	275	675	75	18.0x33.0x31.5	27.5	---	B32674□4565+	4.2	3.6	3.1	---	9	12	14	---	200
5.6	450	275	675	54	16.0x28.5x42.0	37.5	---	B32676□4565+	---	10.2	9.5	---	---	12	14	---	100
6	450	275	675	75	21.0x31.0x31.5	27.5	---	B32674□4605+	4.1	3.5	3.0	---	9	12	14	---	180
6.8	450	275	675	75	22.0x36.5x31.5	27.5	---	B32674□4685+	3.8	3.3	2.8	---	9	12	14	---	160
6.8	450	275	675	54	18.0x32.5x42.0	37.5	---	B32676□4685+	---	8.6	7.7	---	---	12	14	---	90
7.5	450	275	675	75	22.0x36.5x31.5	27.5	---	B32674□4755+	3.7	3.2	2.8	---	9	12	14	---	160
8.2	450	275	675	54	20.0x39.5x42.0	37.5	10.2	B32676□4825+	---	7.2	6.4	3.3	---	12	14	24	75
10	450	275	675	54	20.0x39.5x42.0	37.5	10.2	B32676□4106+	---	6.0	5.3	2.2	---	12	14	27	75
15	450	275	675	54	28.0x42.5x42.0	37.5	10.2	B32676□4156+	---	4.1	3.3	1.8	---	12	14	29	55
20	450	275	675	54	30.0x45.0x42.0	37.5	20.3	B32676□4206K	---	3.3	2.6	1.4	---	12	14	29	54
20	450	275	675	35	30.0x45.0x57.5	52.5	20.3	B32678□4206+	---	---	---	2.2	---	---	---	29	36
25	450	275	675	35	30.0x45.0x57.5	52.5	20.3	B32678□4256+	---	---	---	2	---	---	---	29	36
30	450	275	675	35	35.0x50.0x57.5	52.5	20.3	B32678□4306+	---	---	---	1.7	---	---	---	29	28
35	450	275	675	35	35.0x50.0x57.5	52.5	20.3	B32678□4356+	---	---	---	1.4	---	---	---	29	28

C _R μF	U _N (V _{dc})	U _{RMS} (V _{ac})	U _{PK} (V _{dc})	dV/dt (V/μs)	Dimensions (Max.) b x h x l (mm)	P (mm)	P1 4-pin (mm)	Ordering Code	ESR (mΩ) @ 100 KHz				I _{RMS} (A) @ 100 KHz, 70°C				PU (pcs)
									2-pin		4-pin		2-pin		4-pin		
									Ø 0.8	Ø 1.0	Ø 1.2	Ø 1.2	Ø 0.8	Ø 1.0	Ø 1.2	Ø 1.2	
1	630	350	950	100	11.0x19.0x31.5	27.5	---	B32674□6105+	10.5	9.9	9.4	---	7	8	9	---	320
1.5	630	350	950	100	12.5x21.5x31.5	27.5	---	B32674□6155+	7.7	7.4	7.1	---	9	12	12	---	280
2	630	350	950	73	12.0x22.0x42.0	37.5	---	B32676□6205+	---	12.2	11.5	---	---	10	11	---	135
2.2	630	350	950	100	15.0x24.5x31.5	27.5	---	B32674□6225+	6.0	5.5	5.0	---	9	12	13	---	240
2.7	630	350	950	73	14.0x25.0x42.0	37.5	---	B32676□6275+	---	10.5	9.8	---	---	10	12	---	115
3.3	630	350	950	100	16.0x32.0x31.5	27.5	---	B32674□6335+	5.0	4.5	4.0	---	9	12	14	---	220
3.3	630	350	950	73	16.0x28.5x42.0	37.5	---	B32676□6335+	---	9.3	8.5	---	---	10	13	---	100
4	630	350	950	73	16.0x28.5x42.0	37.5	---	B32676□6405+	---	7.2	6.4	---	---	11	13	---	100
4.7	630	350	950	100	22.0x36.5x31.5	27.5	---	B32674□6475+	4.7	4.0	3.4	---	9	12	14	---	160
4.7	630	350	950	73	18.0x32.5x42.0	37.5	---	B32676□6475+	---	5.8	5.1	---	---	12	14	---	90
5	630	350	950	100	22.0x36.5x31.5	27.5	---	B32674□6505+	4.7	4.0	3.4	---	9	12	14	---	160
6.8	630	350	950	73	20.0x39.5x42.0	37.5	10.2	B32676□6685+	---	4.9	4.2	2.5	---	12	14	22	75
7.5	630	350	950	73	20.0x39.5x42.0	37.5	10.2	B32676□6755+	---	4.6	3.9	2.3	---	12	14	27	75
8.2	630	350	950	73	28.0x37.0x42.0	37.5	10.2	B32676□6825+	---	4.3	3.6	2.1	---	12	14	29	55
10	630	350	950	73	28.0x42.5x42.0	37.5	20.3	B32676□6106+	---	3.9	3.1	1.9	---	12	14	29	55
12	630	350	950	73	28.0x42.5x42.0	37.5	20.3	B32676□6126+	---	3.8	3	1.8	---	12	14	29	55
14	630	350	950	73	30.0x45.0x42.0	37.5	20.3	B32676□6146+	---	3.7	2.9	1.7	---	12	14	29	54
15	630	350	950	50	30.0x45.0x57.5	52.5	20.3	B32678□6156+	---	---	---	2.7	---	---	---	29	36
20	630	350	950	50	35.0x50.0x57.5	52.5	20.3	B32678□6206+	---	---	---	2	---	---	---	29	28
25	630	350	950	50	35.0x50.0x57.5	52.5	20.3	B32678□6256+	---	---	---	1.8	---	---	---	29	28

C _R μF	U _N (V _{dc})	U _{RMS} (V _{ac})	U _{PK} (V _{dc})	dV/dt (V/μs)	Dimensions (Max.) b x h x l (mm)	P (mm)	P1 4-pin (mm)	Ordering Code	ESR (mΩ) @ 100 KHz				I _{RMS} (A) @ 100 KHz, 70°C				PU (pcs)
									2-pin		4-pin	2-pin		4-pin			
									Ø 0.8	Ø 1.0	Ø 1.2	Ø 1.2	Ø 0.8	Ø 1.0	Ø 1.2	Ø 1.2	
0.68	750	375	1125	125	11.0x19.0x31.5	27.5	---	B32674□1684+	12.0	11.4	10.8	---	7	8	8	---	320
1	750	375	1125	125	12.5x21.5x31.5	27.5	---	B32674□1105+	9.0	8.4	7.8	---	9	9	10	---	280
1.5	750	375	1125	125	14.0x24.5x31.5	27.5	---	B32674□1155+	6.9	6.3	5.8	---	9	12	13	---	260
1.5	750	375	1125	85	12.0x22.0x42.0	37.5	---	B32676□1155+	---	15.2	12.2	---	---	9	11	---	135
2	750	375	1125	85	14.0x25.0x42.0	37.5	---	B32676□1205+	---	12.2	10.9	---	---	10	12	---	115
2.2	750	375	1125	125	18.0x27.5x31.5	27.5	---	B32674□1225+	5.3	4.8	4.4	---	9	12	14	---	200
3.3	750	375	1125	125	21.0x31.0x31.5	27.5	---	B32674□1335+	5.0	4.4	3.9	---	9	12	14	---	180
3.3	750	375	1125	85	18.0x32.5x42.0	37.5	---	B32676□1335+	---	9.6	8.4	---	---	11	14	---	90
4.0	750	375	1125	125	22.0x36.5x31.5	27.5	---	B32674□1405+	4.9	4.1	3.5	---	9	12	14	---	160
4.7	750	375	1125	85	20.0x39.5x42.0	37.5	10.2	B32676□1475+	---	5.7	4.7	3.8	---	12	14	22	75
5.6	750	375	1125	85	20.0x39.5x42.0	37.5	10.2	B32676□1565+	---	5.2	4.2	3.6	---	12	14	24	75
6.8	750	375	1125	85	28.0x37.0x42.0	37.5	20.3	B32676□1685+	---	4.9	4	3.2	---	12	14	28	55
9	750	375	1125	85	28.0x42.5x42.0	37.5	20.3	B32676□1905+	---	4.4	3.3	2.5	---	12	14	29	55
10	750	375	1125	85	30.0x45.0x42.0	37.5	20.3	B32676□1106+	---	4.2	3	2.3	---	12	14	29	54
15	750	375	1125	60	30.0x45.0x57.5	52.5	20.3	B32678□1156K	---	---	---	2.7	---	---	---	29	36
20	750	375	1125	60	35.0x50.0x57.5	52.5	20.3	B32678□1206K	---	---	---	1.9	---	---	---	29	28

C _R μF	U _N (V _{dc})	U _{RMS} (V _{ac})	U _{PK} (V _{dc})	dV/dt (V/μs)	Dimensions (Max.) b x h x l (mm)	P (mm)	P1 4-pin (mm)	Ordering Code	ESR (mΩ) @ 100 KHz				I _{RMS} (A) @ 100 KHz, 70°C				PU (pcs)
									2-pin		4-pin	2-pin		4-pin			
									Ø 0.8	Ø 1.0	Ø 1.2	Ø 1.2	Ø 0.8	Ø 1.0	Ø 1.2	Ø 1.2	
0.47	875	400	1300	150	11.0x19.0x31.5	27.5	---	B32674□8474+	14.0	13.5	13.0	---	7	7	7	---	320
0.68	875	400	1300	150	11.0x21.0x31.5	27.5	---	B32674□8684+	11.5	11.0	10.5	---	8	8	8	---	320
1	875	400	1300	150	13.5x23.0x31.5	27.5	---	B32674□8105+	8.4	8.0	7.6	---	9	9	10	---	260
1	875	400	1300	100	12.0x22.0x42.0	37.5	---	B32676□8105+	---	14.1	13.3	---	---	10	11	---	135
1.5	875	400	1300	150	18.0x27.5x31.5	27.5	---	B32674□8155+	5.5	5.0	4.6	---	9	12	14	---	200
1.5	875	400	1300	100	14.0x25.0x42.0	37.5	---	B32676□8155+	---	12.2	11.1	---	---	10	11	---	115
2.2	875	400	1300	150	18.0x33.0x31.5	27.5	---	B32674□8225+	5.3	4.8	4.4	---	9	12	14	---	200
2.2	875	400	1300	100	16.0x28.5x42.0	37.5	---	B32676□8225+	---	10.5	9.5	---	---	11	12	---	100
3	875	400	1300	150	22.0x36.5x31.5	27.5	---	B32674□8305+	4.5	4.0	3.6	---	9	12	14	---	160
3.3	875	400	1300	100	20.0x39.5x42.0	37.5	10.2	B32676□8335+	---	6.5	5.5	4.8	---	12	14	25	75
4	875	400	1300	100	20.0x39.5x42.0	37.5	10.2	B32676□8405+	---	5.8	4.7	4	---	12	14	26	75
4.7	875	400	1300	100	28.0x37.0x42.0	37.5	20.3	B32676□8475+	---	5.1	4.1	3.3	---	12	14	27	55
6.8	875	400	1300	100	28.0x42.5x42.0	37.5	20.3	B32676□8685+	---	4.9	3.7	3.1	---	12	14	28	55
7.5	875	400	1300	100	30.0x45.0x42.0	37.5	20.3	B32676□8755+	---	4.7	3.5	2.9	---	12	14	29	54
10	875	400	1300	70	30.0x45.0x57.5	52.5	20.3	B32678□8106+	---	---	---	2.5	---	---	---	29	36
15	875	400	1300	70	35.0x50.0x57.5	52.5	20.3	B32678□8156K	---	---	---	2	---	---	---	29	28

‘□’ = ‘D’ for Ø0.8mm, ‘E’ for Ø1.0mm, ‘F’ for Ø1.2mm, ‘G’ for 4-pin. See page 1 for preferred lead execution.

‘+’ = Tolerance J (5%), K (10%).

PU = Packing unit.

Other executions, intermediate values upon request.

Issue by: I.Vázquez

Date: 16/05/2005

Ed.: 02

© EPCOS AG 2001. All Rights Reserved. Reproduction, publication and dissemination of this data sheet, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited. The information contained in this data sheet describes the type of component and shall not be considered as guaranteed characteristics. Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.