# 827914-1 - ACTIVE


#### AMPMODU

TE Internal #: 827914-1 Board-to-Board Jumpers & Shunts, AMPMODU MOD IV, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -40 – 185 °F [-40 – 85 °C]

#### View on TE.com >



Connectors > PCB Connectors > Board-to-Board Connectors > Board-to-Board Jumpers & Shunts



#### Shunt Type: AMPMODU MOD IV

Shunt Style: Open Top

Connector System: Board-to-Board

Number of Positions: 2

Centerline (Pitch): 2.54 mm [.1 in]

### Features

#### **Product Type Features**

Connector System

Connector & Contact Terminates To

Board-to-Board

Printed Circuit Board

#### **Configuration Features**

Number of Positions	2		
Body Features			
Handle	Without		
Primary Product Color	Green		
Contact Features			
Contact Mating Area Plating Material Thickness	.4 µm		
Contact Mating Area Plating Material	Gold Beryllium Copper		
Contact Base Material			
Shunt Type	AMPMODU MOD IV		
Shunt Style	Open Top		
Contact Current Rating (Max)	3 A		
lousing Features			
Housing Material	PBT GF		

**&** For support call+1 800 522 6752

Dimensions

### 827914-1

Board-to-Board Jumpers & Shunts, AMPMODU MOD IV, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -40 – 185 °F [-40 – 85 °C]



Product Height	6 mm[.236 in]
Usage Conditions	
Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
Approved Standards	CSA Certified, UL Recognized
UL Flammability Rating	UL 94V-0
Packaging Features	
Jumper & Shunt Packaging	Loose Piece
Packaging Quantity	1400
Packaging Method	Box

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## 827914-1

Board-to-Board Jumpers & Shunts, AMPMODU MOD IV, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -40 – 185 °F [-40 – 85 °C]



# **Compatible Parts**



# Customers Also Bought



		6-1		
			=TE	
TE Part #1586627-1	Т	FE Part #796690-8	TE Part #ANT-433-SP	
04P CMNL HDR VRT W/DH LF	Т	FERMI-BLOK PCB MOUNT 8P	Antenna SP PCB RPC 433MHz SMT	

ETE

## Documents

#### **CAD** Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_827914-1\_A.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_827914-1\_A.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_827914-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the  $\ensuremath{\text{Terms}}$  and  $\ensuremath{\text{Conditions}}$  of use.

### 827914-1

Board-to-Board Jumpers & Shunts, AMPMODU MOD IV, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -40 – 185 °F [-40 – 85 °C]



Product Specifications Product Specification

English

Product Environmental Compliance Product Compliance Document

English

Product Compliance Document

English