

20A, 100V - 150V Trench Schottky Rectifier

FEATURES

- Patented Trench Schottky technology
- Excellent high temperature stability
- Low forward voltage
- Low power loss/ high efficiency
- High forward surge capability
- Compliant RoHS
- Halogen-free according to IEC 61249-2-21


APPLICATIONS

- Switching mode power supply (SMPS)
- Adapters
- Lighting application
- On-board DC/DC converter

MECHANICAL DATA

- Case: ITO-220AB
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 2 whisker test
- Mounting torque: 0.56 N·m maximum
- Polarity: As marked
- Weight: 1.70g (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
I_F	20	A
V_{RRM}	100 - 150	V
I_{FSM}	120	A
T_{JMAX}	150	°C
Package	ITO-220AB	
Configuration	Dual dies	



ITO-220AB



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)					
PARAMETER	SYMBOL	TSF20H 100C-S	TSF20H 120C-S	TSF20H 150C-S	UNIT
Marking code on the device		TSF20H 100C	TSF20H 120C	TSF20H 150C	
Repetitive peak reverse voltage	V_{RRM}	100	120	150	V
Reverse voltage, total rms value	$V_{R(RMS)}$	70	84	105	V
Forward current	I_F	20			A
Surge peak forward current, 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	120			A
Critical rate of rise of off-state voltage	dv/dt	10,000			V/ μs
Junction temperature	T_J	-55 to +150			°C
Storage temperature	T_{STG}	-55 to +150			°C

THERMAL PERFORMANCE			
PARAMETER	SYMBOL	TYP	UNIT
Junction-to-case thermal resistance	$R_{\theta JC}$	4.5	°C/W

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)							
PARAMETER		CONDITIONS	SYMBOL	TYP	MAX	UNIT	
Forward voltage per diode ⁽¹⁾	TSF20H100C-S	$I_F = 5\text{A}, T_J = 25^\circ\text{C}$	V_F	0.59	-	V	
	TSF20H120C-S			0.66	-	V	
	TSF20H150C-S			0.74	-	V	
	TSF20H100C-S	$I_F = 10\text{A}, T_J = 25^\circ\text{C}$		0.71	0.79	V	
	TSF20H120C-S			0.78	0.86	V	
	TSF20H150C-S			0.82	0.92	V	
		TSF20H100C-S		$I_F = 5\text{A}, T_J = 125^\circ\text{C}$	0.53	-	V
		TSF20H120C-S			0.56	-	V
		TSF20H150C-S			0.60	-	V
		TSF20H100C-S		$I_F = 10\text{A}, T_J = 125^\circ\text{C}$	0.62	0.70	V
		TSF20H120C-S			0.64	0.72	V
		TSF20H150C-S			0.68	0.78	V
Reverse current @ rated V_R per diode ⁽²⁾	TSF20H100C-S TSF20H120C-S	$T_J = 25^\circ\text{C}$	I_R	-	150	μA	
	TSF20H150C-S	-		100	μA		
	TSF20H100C-S TSF20H120C-S	$T_J = 125^\circ\text{C}$		-	18	mA	
	TSF20H150C-S			-	12	mA	

Notes:

1. Pulse test with $PW = 0.3\text{ms}$
2. Pulse test with $PW = 30\text{ms}$

ORDERING INFORMATION		
ORDERING CODE⁽¹⁾	PACKAGE	PACKING
TSF20HxC-S	ITO-220AB	50 / Tube

Notes:

1. "x" defines voltage from 100V(TSF20H100C-S) to 150V(TSF20H150C-S)

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics




Fig.5 Typical Reverse Characteristics





Fig.6 Typical Forward Characteristics



CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.7 Typical Reverse Characteristics






Fig.8 Typical Forward Characteristics



PACKAGE OUTLINE DIMENSIONS



DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	4.30	4.70	0.169	0.185
A2	2.30	2.96	0.091	0.117
b	0.50	0.90	0.020	0.035
b1	-	1.80	-	0.071
b2	0.95	1.45	0.037	0.057
c	0.46	0.76	0.018	0.030
c2	2.50	3.16	0.098	0.124
D	14.80	15.50	0.583	0.610
D1	2.40	3.20	0.094	0.126
D2	6.30	6.90	0.248	0.272
E	9.60	10.30	0.378	0.406
e	2.41	2.67	0.095	0.105
L	12.60	13.80	0.496	0.543
L4	-	4.10	-	0.161
P	3.00	3.40	0.118	0.134

MARKING DIAGRAM



- P/N = Marking Code
- G = Green Compound
- YWW = Date Code
- F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.