


SMCJE

Automotive grade 1500 W Transient voltage suppressor



Product features

- Automotive grade (AEC-Q101 qualified)
- Low profile SMC package
- Excellent clamping capability
- High reliability application
- 1500 W peak pulse power capability at 10/1000 μ s waveform
- Typical I_R less than 1 μ A
- Fast response time: typically less than 1.0 ps from 0 V to V_{BR} minimum
- Plastic package meets UL 94 V-0 flammability rating
- Meets moisture sensitivity level (MSL) level 1
- Terminal: tin plated, solderable per J-STD-002
- UL 497B recognized.
File No. : E198449 Guide QVGQ2

Applications


- Automotive chassis and safety systems
- Advanced driver assistance systems (ADAS)
- Communication and infotainment systems
- Network systems and body electronics
- Power Train controls
- xEV and battery systems

Environmental compliance and general specifications



- AEC-Q101 qualified



Ordering part number



PIN configuration




Absolute maximum ratings

(+25 °C, RH=45%-75%, unless otherwise noted)

Parameter	Symbol	Value	Unit
Storage operating junction temperature range	T_{STG}/T_J	-55 to +150	°C
Steady state power dissipation at $T_L = +75$ °C	$P_{M(AV)}$	6.5	W
Peak pulse power dissipation on 10/1000 μ s waveform	P_{PP}	1500	W
Maximum instantaneous forward voltage at 100 A for unidirectional	V_F	5	V
Peak forward surge current, 8.3 ms single half sine wave ¹	I_{FSM}	200	A
Typical thermal resistance junction to lead	$R_{\theta_{JL}}$	15	°C/W
Typical thermal resistance junction to ambient	$R_{\theta_{JA}}$	75	°C/W

1. Measured on 8.3 ms single half sine wave or equivalent square wave for unidirectional device only, duty cycle = 4 per minute maximum

Mechanical parameters, pad layout- mm/inches



Dimension	Millimeters		Inches	
	Minimum	Maximum	Minimum	Maximum
A	5.75	6.25	0.226	0.246
B	6.90	7.40	0.272	0.291
C	2.75	3.25	0.108	0.128
D	0.95	1.52	0.037	0.060
E	7.70	8.20	0.303	0.323
F	0.051	0.203	0.002	0.008
G	0.15	0.31	0.006	0.012
H	2.15	2.62	0.085	0.103
J	2.40	-	0.094	-
K	-	4.20	-	0.165
L	3.30	-	0.130	-

Part marking



Cathode band (uni-polar only)

Part marking:


xxxx = Date code

yyy- Refer to marking designator listed in Electrical characteristics table

Packaging information - mm/inches

Drawing not to scale.

Supplied in tape and reel packaging, 3,000 parts per 13" diameter reel (EIA-481 compliant)




Dimensions	Millimeters	Inches
A0	6.05 ± 0.3	0.238 ± 0.012
B0	8.31 ± 0.3	0.327 ± 0.012
C	330.0	13.0
D0	1.55 ± 0.1	0.061 ± 0.004
E	1.75 ± 0.2	0.069 ± 0.008
E1	13.3 ± 0.3	0.524 ± 0.012
F	7.50 ± 0.2	0.295 ± 0.008
P0	4.00 ± 0.2	0.157 ± 0.008
P1	8.00 ± 0.2	0.3145 ± 0.008
P2	2.00 ± 0.2	0.079 ± 0.008
W	16.0 ± 0.2	0.630 ± 0.008
W1	19.7 ± 2.0	0.776 ± 0.079

Electrical specifications (+25 °C)


Part number		Marking		V_R	$I_R @ V_R$	$V_{BR} @ I_T$		I_T	$V_C @ I_{PP}$	I_{PP}
Uni-polar	Bi-polar	Uni	Bi	(V)	(μ A)	min (V)	max (V)	(mA)	max (V)	(A)
SMCJE15AH	SMCJE15CAH	GEM	BEM	15	1	16.7	18.5	1	24.4	61.5
SMCJE16AH	SMCJE16CAH	GEP	BEP	16	1	17.8	19.7	1	26	57.7
SMCJE17AH	SMCJE17CAH	GER	BER	17	1	18.9	20.9	1	27.6	54.4
SMCJE18AH	SMCJE18CAH	GET	BET	18	1	20	22.1	1	29.2	51.4
SMCJE20AH	SMCJE20CAH	GEV	BEV	20	1	22.2	24.5	1	32.4	46.3
SMCJE22AH	SMCJE22CAH	GEX	BEX	22	1	24.4	26.9	1	35.5	42.3
SMCJE24AH	SMCJE24CAH	GEZ	BEZ	24	1	26.7	29.5	1	38.9	38.6
SMCJE26AH	SMCJE26CAH	GFE	BFE	26	1	28.9	31.9	1	42.1	35.6
SMCJE28AH	SMCJE28CAH	GFG	BFG	28	1	31.1	34.4	1	45.4	33.1
SMCJE30AH	SMCJE30CAH	GFK	BFK	30	1	33.3	36.8	1	48.4	31
SMCJE33AH	SMCJE33CAH	GFM	BFM	33	1	36.7	40.6	1	53.3	28.2
SMCJE36AH	SMCJE36CAH	GFP	BFP	36	1	40	44.2	1	58.1	25.8
SMCJE40AH	SMCJE40CAH	GFR	BFR	40	1	44.4	49.1	1	64.5	23.3
SMCJE43AH	SMCJE43CAH	GFT	BFT	43	1	47.8	52.8	1	69.4	21.6
SMCJE45AH	SMCJE45CAH	GFV	BFV	45	1	50	55.3	1	72.7	20.6
SMCJE48AH	SMCJE48CAH	GFX	BFX	48	1	53.3	58.9	1	77.4	19.4
SMCJE51AH	SMCJE51CAH	GFZ	BFZ	51	1	56.7	62.7	1	82.4	18.2
SMCJE54AH	SMCJE54CAH	GGE	BGE	54	1	60	66.3	1	87.1	17.2
SMCJE58AH	SMCJE58CAH	GGG	BGG	58	1	64.4	71.2	1	93.6	16.1
SMCJE60AH	SMCJE60CAH	GGK	BGK	60	1	66.7	73.7	1	96.8	15.5
SMCJE64AH	SMCJE64CAH	GGM	BGM	64	1	71.1	78.6	1	103	14.6
SMCJE70AH	SMCJE70CAH	GGP	BGP	70	1	77.8	86	1	113	13.3
SMCJE75AH	SMCJE75CAH	GGR	BGR	75	1	83.3	92.1	1	121	12.4
SMCJE78AH	SMCJE78CAH	GGT	BGT	78	1	86.7	95.8	1	126	11.9
SMCJE85AH	SMCJE85CAH	GGV	BGV	85	1	94.4	104	1	137	11
SMCJE90AH	SMCJE90CAH	GGX	BGX	90	1	100	111	1	146	10.3
SMCJE100AH	SMCJE100CAH	GGZ	BGZ	100	1	111	123	1	162	9.3
SMCJE110AH	SMCJE110CAH	GHE	BHE	110	1	122	135	1	177	8.5
SMCJE120AH	SMCJE120CAH	GHG	BHG	120	1	133	147	1	193	7.8
SMCJE130AH	SMCJE130CAH	GHK	BHK	130	1	144	159	1	209	7.2
SMCJE150AH	SMCJE150CAH	GHM	BHM	150	1	167	185	1	243	6.2
SMCJE160AH	SMCJE160CAH	GHP	BHP	160	1	178	197	1	259	5.8
SMCJE170AH	SMCJE170CAH	GHR	BHR	170	1	189	209	1	275	5.5
SMCJE180AH	SMCJE180CAH	GHT	BHT	180	1	201	222	1	292	5.2
SMCJE190AH	SMCJE190CAH	GHU	BHU	190	1	211	234	1	307	4.9
SMCJE200AH	SMCJE200CAH	GHV	BHV	200	1	224	247	1	324	4.7
SMCJE210AH	SMCJE210CAH	GHW	BHW	210	1	233	258	1	337	4.5
SMCJE220AH	SMCJE220CAH	GHX	BHX	220	1	246	272	1	356	4.2
SMCJE250AH	SMCJE250CAH	GJG	BJG	250	1	279	309	1	405	3.7
SMCJE300AH	SMCJE300CAH	GJK	BJK	300	1	335	371	1	486	3.1
SMCJE350AH	SMCJE350CAH	GJM	BJM	350	1	391	432	1	567	2.7
SMCJE400AH	SMCJE400CAH	GJP	BJP	400	1	447	494	1	648	2.3
SMCJE440AH	SMCJE440CAH	GJR	BJR	440	1	492	543	1	713	2.1

Ratings and V-I characteristic curves (+25 °C unless otherwise noted)

V- I curve characteristics (Uni-directional)



V- I curve characteristics (Bi-directional)



Surge waveform: 10/1000 μ s

V_R : Stand-off voltage – Maximum voltage that can be applied

V_{BR} : Breakdown voltage


V_C : Clamping voltage – Peak voltage measured across the suppressor at a specified I_{PP}

I_R : Reverse leakage current


I_T : Test current

V_F : Forward voltage drop for Uni-directional


Pulse waveform



Pulse derating curve



Peak pulse power dissipation curve



Solder reflow profile



Table 1 - Standard SnPb solder (T_C)

Package thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2 - Lead (Pb) free solder (T_C)

Package thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 – 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Reference J-STD-020

Profile feature	Standard SnPb solder	Lead (Pb) free solder
Preheat and soak	<ul style="list-style-type: none"> Temperature min. (T_{smin}) Temperature max. (T_{smax}) Time (T_{smin} to T_{smax}) (t_s) 	<ul style="list-style-type: none"> 100 °C 150 °C 60-120 seconds
Ramp up rate T_L to T_p	3 °C/ second max.	3 °C/ second max.
Liquidous temperature (T_L)	183 °C	217 °C
Time (t_L) maintained above T_L	60-150 seconds	60-150 seconds
Peak package body temperature (T_p)*	Table 1	Table 2 (+0, -5 °C)
Time (t_p)* within 5 °C of the specified classification temperature (T_C)	20 seconds*	40 seconds*
Ramp-down rate (T_p to T_L)	6 °C/ second max.	6 °C/ second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com/electronics

© 2021 Eaton
All Rights Reserved
Printed in USA
Publication No. ELX1064 BU-ELX21064
June 2021

Eaton is a registered trademark.
All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

