
TE Internal #: 2016742-6 SMPM Cable Assembly, 1.97 ft [.6 m], Blue Cable, 0 – 67 GHz Operating Frequency, 50 Ω , FEP, 28 – 30 AWG, .102 in [2.6 mm]

Diameter, SMPM Plug

View on TE.com >



Cable Assemblies > RF Cable Assemblies



Connector Type (End A): SMPM Plug

Jacket Material: FEP

Cable Assembly Length: .6 m [1.97 ft]

Cable Color: Blue

Operating Temperature Range: -45 - 85 °C [-49 - 185 °F]

Features

Product Type Features

| Product Type Features | |
|----------------------------|--------------------------|
| Connector Type (End A) | SMPM Plug |
| Connector Type (End B) | 1.85mm Series RF CA Plug |
| Cable Assembly Type | SMPM |
| Configuration Features | |
| Number of Positions | 8 |
| Electrical Characteristics | |
| Insulation Resistance | 500 MΩ |
| Operating Voltage | 150 V |
| Impedance | 50 Ω |
| Signal Characteristics | |
| Velocity of Propagation | 74 % |
| Body Features | |
| Conductor Plating Material | Silver |

HST

Strain Relief Type



| Shield Plating Material | Silver |
|--------------------------------------|---------------------------|
| Shield Material | Copper Wire |
| Body Plating Material | Stainless Steel |
| Conductor Material | Copper |
| Jacket Material | FEP |
| Cable Color | Blue |
| Contact Features | |
| Center Contact Plating | Gold |
| Ferrule Plating Material | Gold |
| Contact Mating Area Plating Material | Gold |
| Ferrule Material | Copper |
| Contact Base Material | Beryllium Copper Alloy |
| Dimensions | |
| Wire Size | 28 – 30 AWG |
| Outside Cable Diameter | 2.6 mm[.102 in] |
| Usage Conditions | |
| Operating Temperature Range | -45 – 85 °C[-49 – 185 °F] |
| Operation/Application | |
| Shielded | Yes |
| Operating Frequency | 0 – 67 GHz |
| Other | |
| Cable Assembly Length | .6 m[1.97 ft] |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|---|---|
| EU ELV Directive 2000/53/EC | Not Yet Reviewed |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (8.35% in Component Part) Article Safe Usage Statements: |



Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

| Halogen Content | Low Bromine/Chlorine - Br and Cl < 900 |
|-----------------|--|
| | ppm per homogenous material. Also BFR /CFR/PVC Free |

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Documents

Product Drawings
40GHZ,8IN1,SMPM TO 2.92,M-M,L610

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2016742-6_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2016742-6_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2016742-6_1.3d_stp.zip

SMPM Cable Assembly, 1.97 ft [.6 m], Blue Cable, 0 – 67 GHz Operating Frequency, 50 Ω , FEP, 28 – 30 AWG, .102 in [2.6 mm] Diameter, SMPM Plug



English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English