APPLICAE	BLE STANI	DARD										
OPERATING		E DANIGE	-55 °C TO 85 °	)C (1)	- 1	ORAGE MPERATURE RANGE			-10 °C TO 60 °C			
RATING	TEMPERATURE RANGE		100 V AC		OPERATING RANGE				40 % TO 80 %			
10,4111	CURRENT		0.5 A	STORAGE HI								
	CONNENT			IFICA					40 70 10 10 70			
IT	 EM		TEST METHOD		TION		PE		EMENTS	ΙQΤ	ТАТ	
CONSTRU			TEST WETHOD				IVE.	ZOIIVE	INICINIO	Q	141	
		VISUALI	Y AND BY MEASURING IN	STRUME	NT I	ACCO	RDING TO	DRAW	/ING	X	×	
MARKING			MED VISUALLY.	011101112			.5	, D		×	×	
ELECTRIC	CHARAC	TERISTI	CS							'	_	
CONTACT R	ESISTANCE	,				40 mΩ MAX.				×		
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20 mV MAX, 1 mA(DC OR 1000Hz)				50 mΩ MAX.				×		
INSULATION RESISTANCE		250 V DC				100 MΩ MIN.				×		
VOLTAGE P		300 V/ A	300 V AC FOR 1 min.				ASHOVEE	OR BE	REAKDOWN.	×	+	
	CAL CHAR					.,	STIOVE			1 ^		
MECHANICA			ES INSERTIONS AND EXTR	RACTION	is I	⊕ COI	NTACT R	FSISTA	NCE: 50 mΩ MAX.	×	T	
OPERATION						② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				1		
AN AT SHOCK 49		FREQUENCY 10 TO 55 Hz,						CAL DI	SCONTINUITY OF	×		
		AMPLITUDE: 1.5 mm, AT 2 h FOR 3 DIRECTION.				1 µs. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.						
		490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms								×	-	
			AT 3 TIMES FOR 3 DIRECTIONS.									
ENVIRON	MENTAL C	HARAC	TERISTICS		•					•	•	
DAMP HEAT EXPOS			SED AT 40±2 °C, 90 ~ 95 %, 96 h.			$\bigcirc$ CONTACT RESISTANCE: 50 m $\Omega$ MAX.				×		
(STEADY STATE)						_			TANCE:100 MΩ MIN.	_		
RAPID CHANGE OF TEMPERATURE		TEMPERATURE-55 $\rightarrow$ +15 $\sim$ +35 $\rightarrow$ +85 $\rightarrow$ +15 $\sim$ +35 $\circ$ C TIME 30 $\rightarrow$ MAX 5 $\rightarrow$ 30 $\rightarrow$ MAX 5 min UNDER 5 CYCLES.				③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.						
		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				① CONTACT RESISTANCE: 50 mΩ MAX. ② NO HEAVY CORROSION.				×		
		EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA-38)				W NO REAVI CORROSION.						
RESISTANCE TO		1) REFLOW SOLDERING : 250 °C MAX,				NO DEFORMATION OF CASE OF						
SOLDERING HEAT		: 220 °C MIN,				EXCESSIVE LOOSENESS OF THE						
		FOR 60 s 2) SOLDERING IRONS : 360 °C,				TERMINALS. 					+	
		2) SOLDE		5 s						×		
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE, 240°C,				A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.				×		
		FOR IMM	ERSION DURATION, 3 s	sec		THE S	URFACE	BEING	MMERSED.			
COUN	COUNT DESCRIPTION OF REVIS		ON OF REVISIONS	IONS DESI		SNED			CHECKED		DATE	
<u> </u>												
REMARK	 (1)TEMPERATU	RE RISE IN	ICLUDED WHEN ENERGIZED.			APPRO		'ED HS.OKAWA		05.	07.15	
. ,			TES A LONG-TERM STORAGE STATE  JCT BEFORE THE BOARD MOUNTED.			CHECKED					07.14	
									KT.DOI			
Unless of	herwise sne	ecified re	refer to MIL-STD-1344.			DRAWN			AK.SUZUKAWA			
	·		urance Test X:Applicable Tes				RAWING NO.			34-152945-25		
		PECIFICATION SHEET			PART NO.		FX6-*P-0. 8SV2 (71)					
			ECTRIC CO., LTD.	CODE NO					$\wedge$	1/		
I IIROSE EI				CODE NO.					<u>, ∪ \</u>	''		