


Specifications:

规格:

- 1.Voltage rating:250VAC/DC
额定电压: 250V AC/DC
 - 2.Current rating:5A AC/DC
额定电流: 5A AC/DC
 - 3.Withstanding voltage:1000V AC/minute
耐受电压: 1000V AC/分钟
 - 4.Temperature range: -55°C~+105°C
温度范围: -55°C~+105°C
 - 5.Insulation resistance:500MΩ MIN
绝缘电阻: 500MΩ MIN
 - 6.Contact resistance:30mΩ Max
接触电阻: 30mΩ Max
- Material:
材料:
- 7.Rubber core:PBT+G/F UL94V-0
胶芯: PBT+C/F UL94V-0
 - 8.The iron shell:Steel ; Tin Plating
铁壳: 钢 ; 镀锡
 - 9.Terminal:Brass
端子: 黄铜

X01 XX W X X X X L
① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series NO.
- ② Row No.Pin No.XX-09;15;25;37
- ③ Welding Board Angle :W-Male
- ④ T: Tradutional C: Car-pin
- ⑤ Planting Category: 1:Gold 1u ;2:Gold 2u ;3:Gold 3u ;4:Gold 5u ;5:Gold 15u ;6:Gold 30u ;7:Terminal half- Gold Bright Tin;8: Terminal half- Gold 2u Bright Tin ;9: Terminal half- Gold 3u Bright Tin;10: Terminal half- Gold 5u Bright Tin ;11: Terminal half- Gold 15u Bright Tin;12: Terminal half- Gold 30u Bright Tin ;13: Terminal half- Gold Matte Tin;14:Terminal half- Gold 2u Matte Tin ;15:Terminal half- Gold 3u Matte Tin ;16:Terminal half- Gold 5u Matte Tin ;17:Terminal half- Gold 15u Matte Tin;18:Terminal half- Gold 30u Matte Tin
- ⑥ TinColor:B-BLACK W-White BL-Blue
- ⑦ 1:TYPE-1; 5:TYPE-5
- ⑧ L: Stitching lengthening



NUMBER OF POSITIONS	DIMENSION			
	A±0.25	B±0.13	C±0.38	D±0.25
9	18.00	24.99	30.80	19.28
15	26.50	33.32	39.20	27.51
25	40.00	47.04	53.05	41.28
37	56.60	63.50	69.40	57.71

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°
ΔX					L ≤ 4	±0.2
ΔX					4 < L ≤ 16	±0.3
ΔX					16 < L ≤ 63	±0.4
MARK					L > 63	±0.5
REVISIONS						UNSPECIFIED TOLERANCES



DSND	SCALE: N/A	MODEL TYPE: D-SUB
DWN	VIEW:	PART NO.: X01XXWXXXXL
CHKD	UNIT: mm/in	DWG NO.: X-X01XXWXXXXL
APPD	SIZE: A4	WEIGHT SHEET REVISION
XKB INDUSTRIAL PRECISION CO.,LIMITED		1/1 A0