

Buchanan

TE Internal #: 2-2342077-5 PCB Terminal Blocks, Header, Wire-to-Board, 25 Position, .15 in [3.81 mm] Centerline, 1 Row, Operating Voltage 300 VAC, Printed Circuit Board

View on TE.com >





Terminal Block Connector Type: Header

Connector System: Wire-to-Board

Number of Positions: 25

Centerline (Pitch): 3.81 mm [.15 in]

Number of Rows: 1

Features



Product Type Features

Header Type	Fully Shrouded
Terminal Block Connector Type	Header
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Stacking Configuration	Side Stackable
Number of Positions	25
Number of Rows	1
Electrical Characteristics	
Operating Voltage	300 VAC
Body Features	
Primary Product Color	Black
Product Orientation	Right Angle

2-2342077-5

PCB Terminal Blocks, Header, Wire-to-Board, 25 Position, .15 in [3.81 mm] Centerline, 1 Row, Operating Voltage 300 VAC, Printed Circuit Board



Contact Features

Contact Mating Area Plating Material	Tin
Contact Base Material	Copper Magnesium
Contact Current Rating (Max)	11 A
Termination Features	
Termination Post & Tail Length	1.9 mm[.075 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	High Temperature Polyamide
Centerline (Pitch)	3.81 mm[.15 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Packaging Features	



Packaging Method

Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer

C For support call+1 800 522 6752

02/17/2024 05:13PM | Page 2

2-2342077-5

PCB Terminal Blocks, Header, Wire-to-Board, 25 Position, .15 in [3.81 mm] Centerline, 1 Row, Operating Voltage 300 VAC, Printed Circuit Board



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



Documents

Product Drawings 25POS HDR 90 DEG,HT,3.81MM PITCH,TL1.9MM

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_2-2342077-5_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-2342077-5_A.3d_igs.zip

English

2-2342077-5

PCB Terminal Blocks, Header, Wire-to-Board, 25 Position, .15 in [3.81 mm] Centerline, 1 Row, Operating Voltage 300 VAC, Printed Circuit Board



Customer View Model

ENG_CVM_CVM_2-2342077-5_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages BUCHANAN TERMINAL BLOCKS CATALOG - EUROSTYLE TERMINAL BLOCKS

English

Agency Approvals

UL

English