SC380A400FP

Hyde Park, Ultrasonic sensor, discrete, flat profile, 12 24 V DC



Main

Range of Product Sensor Type Ultrasonic sensor Series name Superprox + Device short name SC380 Sensor design Flat form Type of sensing window Material Plastic Enclosure Material ULTEM Front material Glass epoxy Type of output signal Discrete Wiring Technique 4-wire [Us] rated supply voltage limits Supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Application		
Series name Superprox + Device short name SC380 Sensor design Flat form Type of sensing window Configurable Material Plastic Enclosure Material ULTEM Front material Glass epoxy Type of output signal Discrete Wiring Technique 4-wire [Us] rated supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete proximity	Range of Product	Hyde Park
Device short name SC380 Sensor design Flat form Type of sensing window Configurable Material Plastic Enclosure Material ULTEM Front material Glass epoxy Type of output signal Discrete Wiring Technique 4-wire [Us] rated supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete proximity	Sensor Type	Ultrasonic sensor
Sensor design Flat form Type of sensing window Configurable Material Plastic Enclosure Material ULTEM Front material Glass epoxy Type of output signal Discrete Wiring Technique 4-wire [Us] rated supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete proximity	Series name	Superprox +
Type of sensing window Material Plastic Enclosure Material ULTEM Front material Glass epoxy Type of output signal Discrete Wiring Technique 4-wire [Us] rated supply voltage limits Supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete	Device short name	SC380
Material Plastic Enclosure Material ULTEM Front material Glass epoxy Type of output signal Discrete Wiring Technique 4-wire [Us] rated supply voltage Supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete proximity	Sensor design	Flat form
Enclosure Material Front material Glass epoxy Type of output signal Wiring Technique 4-wire [Us] rated supply voltage Supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete	Type of sensing window	Configurable
Front material Glass epoxy Type of output signal Discrete Wiring Technique 4-wire [Us] rated supply voltage Supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete proximity	Material	Plastic
Type of output signal Discrete Wiring Technique 4-wire [Us] rated supply voltage Supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete	Enclosure Material	ULTEM
Wiring Technique 4-wire [Us] rated supply voltage Supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete proximity	Front material	Glass epoxy
[Us] rated supply voltage Supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete proximity	Type of output signal	Discrete
voltage Supply voltage limits 1028 V DC Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete proximity	Wiring Technique	4-wire
Electrical connection Remote male connector M12 4 pins, 5.98 in (152 mm) Product Specific Discrete proximity		1224 V DC overload and short-circuit protection
(152 mm) Product Specific Discrete proximity	Supply voltage limits	1028 V DC
• • • • • • • • • • • • • • • • • • • •	Electrical connection	• •
	•	Discrete proximity

Complementary

[Sn] nominal sensing distance	4.00 in (101.6 mm)	
Maximum differential travel	0.03 in (0.7 mm)	
Blind zone	0.25 in (6.4 mm)	
Transmission frequency	500 kHz	
Repeat accuracy	0.7 %	
Beam angle	8 °	
Minimum size of detected object	Cylinder diameter 2.5 mm - up to 1 mm sensing distance	
Current Consumption	25 mA	
Maximum switching current	100 mA reverse polarity protection	
Height	0.30 in (7.62 mm)	
Width	0.75 in (19.05 mm)	
Depth	0.30 in (7.62 mm)	
Length	1.30 in (33.02 mm)	
Net Weight	0.09 lb(US) (0.04 kg)	

Environment

Product Certifications	UL	
Marking	CE	
NEMA degree of protection	NEMA 4X indoor use only)	
IP degree of protection	IP67	
Ambient Air Temperature for Operation	-22158 °F (-3070 °C)	
Ambient Air Temperature for Storage	-40212 °F (-40100 °C)	
Relative humidity	100 % without condensation	
Vibration resistance	+/-1 mm 1055 Hz)IEC 60068-2-6	
Shock resistance	30 gn in all 3 axes 11 ms IEC 60068-2-27	
Resistance to electromagnetic fields	9.14 V/m (10 V/m) level 3 IEC 61000-4-3	
Resistance to fast transients	1 kV level 3 IEC 61000-4-4	

Ordering and shipping details

Category	US10DS222490
Discount Schedule	0DS2
GTIN	3389119086240
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE	
Office Type of Fackage 1	FOL	
Number of Units in Package 1	1	
Package 1 Height	3.31 in (8.415 cm)	
Package 1 Width	1.50 in (3.81 cm)	
Package 1 Length	3.31 in (8.415 cm)	
Package 1 Weight	12.80 oz (362.874 g)	

Offer Sustainability

REACh Regulation EU RoHS Directive Not applicable, out of EU RoHS legal scope	hemicals including: Diisononyl of California to cause cancer, own to the State of California arm. For more information go to
ELL DoUS Directive	
EU RoHS Directive Not applicable, out of EU RoHS legal scope	

Contractual warranty

Warranty	18 months	