# 154N-050A-R - ACTIVE

MEAS | MEAS 154 Series TE Internal #: 154N-050A-R TE Internal Description: 50 PSIA RIBBON CABLE MV PRESSURE SENSOR 19MM MV OUTPUT PRESSURE SENSOR

View on TE.com >



Sensors > Pressure Sensors > Media Isolated Pressure Sensors > 19MM MV OUTPUT PRESSURE SENSOR



Pressure: [50 psi]

Media Isolated Pressure Sensor Type: Media Isolated mV Output Pressure Sensors

Media Isolated Pressure Sensor Style: Absolute

Output/Span: 100mV

Operating Temperature Range: -40 – 125 °C [-40 – 257 °F]

### All 19MM MV OUTPUT PRESSURE SENSOR (38)

## Features

## **Product Type Features**

Media Isolated Pressure Sensor Type

Media Isolated Pressure Sensor Style	Absolute						
Configuration Features							
Electrical Connection	Ribbon Cable						
Electrical Characteristics							
Supply Current	1.5 mA						
Dimensions							
Dimensions	Dia 18.97 x 13.8 mm[Dia .746 x .54 in]						
Usage Conditions							
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]						
Operation/Application							
Proof Pressure Range	3X						
	50 psi						
Output/Span	100mV						
Packaging Features							

**C** For support call+1 800 522 6752

02/17/2024 03:53PM | Page 1



Media Isolated Pressure Sensor Package	O-Ring Mount
Other	
Non-Linearity	± .1 %
Sensor Options	No Tube
Product Compliance	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Methanone, (diphenylphosphinyl)(2,4,6- trimethylphenyl)- (1% in Component a) Article Safe Usage Statements: Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


## **Compatible Parts**

#### 50 PSIA RIBBON CABLE MV PRESSURE SENSOR





## Also in the Series | MEAS 154 Series



# Customers Also Bought



. ≡TE		TE	
TE Part #154N-100A-R 19MM MV OUTPUT PRESSURE SENSOR	E Part #4515-DS3B030GP RESS XDCR,ANALOG,INH20 RANGE	TE Part #M5256-00000E-006BG PRESS XDCR M5256-00000E-006BG	TE Part #20005705-00 PRESS XDCR U5256-000002-001BG



## Documents

CAD Files

3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_154N-050A-R\_F1.2d\_dxf.zip

English

154N-050A-R

50 PSIA RIBBON CABLE MV PRESSURE SENSOR



Customer View Model ENG\_CVM\_CVM\_154N-050A-R\_F1.3d\_igs.zip

English

Customer View Model ENG\_CVM\_CVM\_154N-050A-R\_F1.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 154NC

English