TE Internal #: 2103177-1

Housing for Female Terminals, Wire-to-Device / Wire-to-Board / Wire-to-Wire, 2 Position, .409 in [10.4 mm] Centerline, Sealable,

Orange, Wire & Cable

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings











Connector System: Wire-to-Board, Wire-to-Device, Wire-to-Wire

Number of Positions: 2

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 10.4 mm [.409 in]

Sealable: Yes

Features

Product Type Features

Mixed & Hybrid Connector Connector Shape Rectangular Wire-to-Board, Wire-to-Device, W Wire Connector & Housing Type Housing for Female Terminals Sealable Yes Connector & Contact Terminates To Wire & Cable Primary Locking Feature Integrated in Housing Configuration Features	ire-to-
Connector System Wire-to-Board, Wire-to-Device, Wwire Connector & Housing Type Housing for Female Terminals Sealable Yes Connector & Contact Terminates To Wire & Cable Primary Locking Feature Integrated in Housing	ire-to-
Connector & Housing Type Housing for Female Terminals Yes Connector & Contact Terminates To Wire & Cable Primary Locking Feature Integrated in Housing	ire-to-
Sealable Connector & Contact Terminates To Wire & Cable Primary Locking Feature Integrated in Housing	
Connector & Contact Terminates To Wire & Cable Primary Locking Feature Integrated in Housing	
Primary Locking Feature Integrated in Housing	
Configuration Features	
Number of Positions 2	
Number of Rows 1	
Electrical Characteristics	
Nominal Voltage Architecture 600 V	

Orange

Body Features

Primary Product Color



Connector & Keying Code	A
Contact Features	
Contact Size	2.8mm
Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA GF
Centerline (Pitch)	10.4 mm[.409 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
Packaging Quantity	1
Packaging Method	Package
Other	
Connector Position Assurance Capable	Yes
Connector Position Assurance Capable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC



Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CAT-LMPH9507
Low & Medium Power Header



Customers Also Bought



















Documents

Product Drawings

PLUG ASSY, KEY A, TA,CPA, HVA280-2PHI XE

English

PLUG ASSY, KEY A, TA,CPA, HVA280-2PHI XE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2103177-1_B_c-2103177-1-b.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2103177-1_B_c-2103177-1-b.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2103177-1_B_c-2103177-1-b.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English