DEUTSCH | DEUTSCH DT-XT

TE Internal #: 2600042-7

TE Internal Description: 12CCT RECEP BLACK K A W/LARGE SEAL

DT-XT 12-way Receptacle Connectors


View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DT-XT 12-way Receptacle Connectors











Connector System: Wire-to-Wire

Number of Positions: 12

Connector & Housing Type: Receptacle
Centerline (Pitch): 4.45 mm [.175 in]

Sealable: Yes

All DT-XT 12-way Receptacle Connectors (5)

Features

Product Type Features

Primary Product Color

Connector & Keying Code

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Receptacle
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	12
Number of Rows	2
Body Features	

Black

А



Contact Features

Contact Size	Size 16
Mating Pin Diameter	1.56 mm[.061 in]
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	4.45 mm[.175 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

No

Product Compliance

Other

For compliance documentation, visit the product page on TE.com>

Connector Position Assurance Capable

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | DEUTSCH DT-XT



Automotive Housings(57)



Customers Also Bought



TE Part #2213627-1
ASSEMBLY, ROT DIM REC 49.22MM 5
POS 150C



TE Part #DT06-08SB-CE01 PLG, 8P, BLK, E, CAP, B



TE Part #2213626-1 GASKET, SEALING ROT DIM RECEPT





TE Part #4-1393249-3 W58-XC4C12A-20=W58



TE Part #4-1393249-6 W58-XC4C12A-30=W58



TE Part #2600043-8 12CCT PLUG BLACK K A W/LARGE SEAL





Documents

Product Drawings

12CCT RECEP BLACK K A W/LARGE SEAL



English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2600042-7_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2600042-7_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2600042-7_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English