

Series: Ceramic Patch Antenna

TECHNICAL DATA SHEET

Description: 2.4-2.5GHz RHCP 25x25x4mm

6.5dBic patch antenna

PART NUMBER: W3229



Features:

2400-2500 MHz

Size: 25x25x4mm

Polarization: RHCP

Gain: +6.5dBic

Pin feed, adhesive tape

RoHS compliant

Moisture sensitivity level:MSL1

Applications:

- 2.4-2.5GHz ISM Band radios
- · WiFi, Bluetooth
- Applications requiring high gain directional antenna pattern

All dimensions are in mm / inches

Issue: 1910

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

For more information:

Pulse Worldwide Headquarters 15255 Innovation Drive #100 San Diego, CA 92128 USA Tel:1-858-674-8100 Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



Description: 2.4-2.5GHz RHCP 25x25x4mm

6.5dBic patch antenna

Series: Ceramic Patch Antenna

PART NUMBER: W3229

ELECTRICAL	SPECIFICATIONS
------------	-----------------------

Frequency	2400-2500MHz
Nominal Impedance	50 Ω
Return Loss	-7dB
Axial Ratio(typical)	3dB
Peak Gain	6.5dBic
Efficiency	80%
Polarization	RHCP

MECHANICAL SPECIFICATIONS

Overall Length 25x25x4mm

Weight 8.08g

MSL Level Not applicable for non-reflow part

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature -40~+105° C

RoHS Compliant Yes

(*) All RF parameters measured on 70*70mm metal ground plane in free space.






Description: 2.4-2.5GHz RHCP 25x25x4mm

6.5dBic patch antenna

PART NUMBER: W3229

Series: Ceramic Patch Antenna

MECHANICAL DRAWING



NO.	Description	Structure and material
1	Antenna Substrate	Dielectric Ceramics
2	Pin	Copper and tinplated
3	Electrode	Ag Plated
4	Ground Base	Ag Plated
5	Adhesive type	NITTO 5000NS




Description: 2.4-2.5GHz RHCP 25x25x4mm

6.5dBic patch antenna

PART NUMBER: W3229

Series: Ceramic Patch Antenna

TEST SETUP



Test on 70*70mm metal ground plane in free space.



Description: 2.4-2.5GHz RHCP 25x25x4mm


6.5dBic patch antenna

PART NUMBER: W3229


Series: Ceramic Patch Antenna

CHARTS

Return Loss



Efficiency(%)



Issue: 1910





Description: 2.4-2.5GHz RHCP 25x25x4mm


6.5dBic patch antenna

PART NUMBER: W3229


Series: Ceramic Patch Antenna

CHARTS

Peak Gain(dBic)



Axial Ratio(dB)



Issue: 1910

ROHS



Description: 2.4-2.5GHz RHCP 25x25x4mm


6.5dBic patch antenna

PART NUMBER: W3229

Series: Ceramic Patch Antenna

CHARTS

Radiation Pattern (2450MHz)







Series: Ceramic Patch Antenna

TECHNICAL DATA SHEET

Description: 2.4-2.5GHz RHCP 25x25x4mm

6.5dBic patch antenna

PART NUMBER: W3229

PACKAGING

40pcs antennas per tray

15pcs trays per box

Outside box size: 285mm*375mm*200mm

600pcs antennas per outside box

