



Data sheet | Item number: 2091-1126

1-conductor female connector; push-button; Push-in CAGE CLAMP®; 1.5 mm<sup>2</sup>; Pin spacing 3.5 mm; 6-pole; 1,50 mm<sup>2</sup>; light gray



[www.wago.com/2091-1126](http://www.wago.com/2091-1126)



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Item description

- Universal connection of all conductor types
- Simple, push-in termination of solid and ferruled conductors
- Easy-to-use design does not require special tools
- Ability to wire while mated or unmated
- Testing parallel to conductor entry – tip contact
- Also available with gripping plates
- Integrated locking latches prevent accidental disconnection

## Data

### Notes

#### Safety information

The **picoMAX® Pluggable Connection System** includes connectors without breaking capacity in accordance with DIN EN 61984. When used as intended, these connectors must not be connected /disconnected when live or under load. The circuit design should ensure header pins, which can be touched, are not live when unmated.

#### Variants:

Direct marking

Other versions (or variants) can be requested from WAGO Sales or configured at <https://configurator.wago.com/>.

## Electrical data

### Ratings per IEC/EN

| Ratings per                   | IEC/EN 60664-1  |
|-------------------------------|---|
| Nominal voltage (III/3)       | 160 V   |
| Rated impulse voltage (III/3) | 2.5 kV  |
| Rated voltage (III/2)         | 160 V   |
| Rated impulse voltage (III/2) | 2.5 kV  |
| Nominal voltage (II/2)        | 320 V   |
| Rated surge voltage (II/2)    | 2.5 kV  |
| Rated current                 | 10 A  |
| Legend (ratings)              | (III / 2) ≙ Overvoltage category III / Pollution degree 2 |

### Ratings per UL

|                                |         |
|--------------------------------|---------|
| Approvals per                  | UL 1059 |
| Rated voltage UL (Use Group B) | 300 V   |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



|                                |       |
|--------------------------------|-------|
| Rated current UL (Use Group B) | 10 A  |
| Rated voltage UL (Use Group D) | 300 V |
| Rated current UL (Use Group D) | 10 A  |

### Connection data

|                            |   |
|----------------------------|---|
| Connection points          | 6 |
| Total number of potentials | 6 |
| Number of connection types | 1 |
| Number of levels           | 1 |

### Connection 1

|   |   |
|---|---|
| Connection technology                             | Push-in CAGE CLAMP®                         |
| Actuation type                                    | Push-button                                 |
| Actuation direction 1                             | Operation parallel to conductor entry       |
| Solid conductor                                   | 0.2 ... 1.5 mm <sup>2</sup> / 24 ... 14 AWG |
| Fine-stranded conductor                           | 0.2 ... 1.5 mm <sup>2</sup> / 24 ... 14 AWG |
| Fine-stranded conductor; with insulated ferrule   | 0.25 ... 0.75 mm <sup>2</sup>               |
| Fine-stranded conductor; with uninsulated ferrule | 0.25 ... 1.5 mm <sup>2</sup>                |
| Strip length                                      | 8 ... 9 mm / 0.31 ... 0.35 inches           |
| Pole number                                       | 6   |

### Physical data

|             |                        |
|-------------|------------------------|
| Pin spacing | 3.5 mm / 0.138 inches  |
| Width       | 21 mm / 0.827 inches   |
| Height      | 14 mm / 0.551 inches   |
| Depth       | 11.4 mm / 0.449 inches |

### Mechanical Data

|                          |     |
|--------------------------|-----|
| Variable coding          | Yes |
| Anti-rotation protection | Yes |

### Plug-in connection

|                                      |                         |
|--------------------------------------|-------------------------|
| Contact type (pluggable connector)   | Female connector/socket |
| Connector (connection type)          | for conductor           |
| Mismatching protection               | No                      |
| Plugging without loss of pin spacing | Yes                     |

Subject to changes. Please also observe the further product documentation!



|                               |      |
|-------------------------------|------|
| Locking of plug-in connection | none |
|-------------------------------|------|

## Material data

Note (material data)

Information on material specifications can be found here

|                             |  |
|-----------------------------|--|
| Color                       | light gray                             |
| Material group              | I                                      |
| Insulation material         | Polyphthalamide (PPA GF)               |
| Flammability class per UL94 | V0                                     |
| Clamping spring material    | Chrome-nickel spring steel (CrNi)      |
| Contact material            | Electrolytic copper (E <sub>Cu</sub> ) |
| Contact plating             | Tin                                    |
| Fire load                   | 0.064 MJ                               |
| Weight                      | 2.8 g                                  |

## Environmental requirements

|                         |                 |
|-------------------------|-----------------|
| Limit temperature range | -60 ... +100 °C |
| Processing temperature  | -35 ... +60 °C  |

## Commercial data

|                       |                         |
|-----------------------|-------------------------|
| Product Group         | 26 (picoMAX Connectors) |
| eCl@ss 10.0           | 27-14-11-06             |
| eCl@ss 9.0            | 27-14-11-06             |
| ETIM 8.0              | EC001284                |
| ETIM 7.0              | EC001284                |
| ECCN                  | NO DATA                 |
| PU (SPU)              | 100 pcs                 |
| Packaging type        | box                     |
| Country of origin     | DE                      |
| GTIN                  | 4050821160793           |
| Customs tariff number | 85366990990             |

## Environmental Product Compliance

|                        |                         |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|






## Approvals / Certificates

Subject to changes. Please also observe the further product documentation!






WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

## General approvals

| Logo   | Approval                                     | Additional Approval Text | Certificate name |
|--|--|--------------------------|------------------|
|  | <b>CB</b><br>DEKRA Certification B.V.        | IEC 61984                | NL-49736 /A1     |
|    | <b>CSA</b><br>DEKRA Certification B.V.       | C22.2 No. 158            | 2362521          |
|    | <b>CSA</b><br>DEKRA Certification B.V.       | C22.2                    | 2362521          |
|    | <b>KEMA/KEUR</b><br>DEKRA Certification B.V. | EN 61984                 | 71-102260 REV.1  |
|    | <b>UL</b><br>Underwriters Laboratories Inc.  | UL 1977                  | E45171           |
|  | <b>UR</b><br>Underwriters Laboratories Inc.  | UL 1059                  | E45172           |

## Counterpart

|  |   |  |
|--|---|--|
|   | <b>Item no.2091-1406/005-000</b><br>THT male header; 1.0 mm Ø solder pin; straight; clamping collar; Pin spacing 3.5 mm; 6-pole; light gray | <a href="http://www.wago.com/2091-1406/005-000">www.wago.com/2091-1406/005-000</a> |
|   | <b>Item no.2091-1406</b><br>THT male header; 1.0 mm Ø solder pin; straight; Pin spacing 3.5 mm; 6-pole; light gray                          | <a href="http://www.wago.com/2091-1406">www.wago.com/2091-1406</a>                 |
|   | <b>Item no.2091-1406/200-000</b><br>THR male header; 1.0 mm Ø solder pin; straight; Pin spacing 3.5 mm; 6-pole; light gray                  | <a href="http://www.wago.com/2091-1406/200-000">www.wago.com/2091-1406/200-000</a> |
|  | <b>Item no.2091-1426</b><br>THT male header; 1.0 mm Ø solder pin; angled; Pin spacing 3.5 mm; 6-pole; light gray                            | <a href="http://www.wago.com/2091-1426">www.wago.com/2091-1426</a>                 |
|   | <b>Item no.2091-1406/205-000</b><br>THR male header; 1.0 mm Ø solder pin; straight; clamping collar; Pin spacing 3.5 mm; 6-pole; light gray | <a href="http://www.wago.com/2091-1406/205-000">www.wago.com/2091-1406/205-000</a> |

Subject to changes. Please also observe the further product documentation!



**Item no.2091-1426/005-000**  
THT male header; 1.0 mm Ø solder pin; angled; clamping collar; Pin spacing 3.5 mm; 6-pole; light gray

[www.wago.com/2091-1426/005-000](http://www.wago.com/2091-1426/005-000)



**Item no.2091-1426/200-000/997-406**  
THR male header; 1.0 mm Ø solder pin; angled; in tape-and-reel packaging; Pin spacing 3.5 mm; 6-pole; light gray

[www.wago.com/2091-1426/200-000/997-406](http://www.wago.com/2091-1426/200-000/997-406)



**Item no.2091-1426/200-000**  
THR male header; 1.0 mm Ø solder pin; angled; Pin spacing 3.5 mm; 6-pole; light gray

[www.wago.com/2091-1426/200-000](http://www.wago.com/2091-1426/200-000)



**Item no.2091-1426/205-000**  
THR male header; 1.0 mm Ø solder pin; angled; clamping collar; Pin spacing 3.5 mm; 6-pole; light gray

[www.wago.com/2091-1426/205-000](http://www.wago.com/2091-1426/205-000)



**Item no.2091-1526/002-000**  
1-conductor male connector; Push-in CAGE CLAMP®; 1.5 mm²; Pin spacing 3.5 mm; 6-pole; Integrated release lever; 1,50 mm²; light gray

[www.wago.com/2091-1526/002-000](http://www.wago.com/2091-1526/002-000)



**Item no.2091-1526/020-000**  
1-conductor male connector; Push-in CAGE CLAMP®; 1.5 mm²; Pin spacing 3.5 mm; 6-pole; DIN-35 rail /panel mounting; Snap-in mounting feet; Integrated release lever; 1,50 mm²; light gray

[www.wago.com/2091-1526/020-000](http://www.wago.com/2091-1526/020-000)



**Item no.2091-1636/024-000**  
Panel feedthrough male connector; clamping collar; 1.5 mm²; 6-pole; Pin spacing 3.5 mm; light gray

[www.wago.com/2091-1636/024-000](http://www.wago.com/2091-1636/024-000)



**Item no.2091-1506/002-000**  
1-conductor male connector; Push-in CAGE CLAMP®; 1.5 mm²; Pin spacing 3.5 mm; 6-pole; Gripping plate; 1,50 mm²; light gray

[www.wago.com/2091-1506/002-000](http://www.wago.com/2091-1506/002-000)



**Item no.2091-1706**  
THT pin strip; 1.0 mm Ø solder pin; straight; Pin spacing 3.5 mm; 6-pole; black

[www.wago.com/2091-1706](http://www.wago.com/2091-1706)



**Item no.2091-1726**  
THT pin strip; 1.0 mm Ø solder pin; angled; Pin spacing 3.5 mm; 6-pole; black

[www.wago.com/2091-1726](http://www.wago.com/2091-1726)



**Item no.2091-1706/200-000**  
THR pin strip; 1.0 mm Ø solder pin; straight; Pin spacing 3.5 mm; 6-pole; black

[www.wago.com/2091-1706/200-000](http://www.wago.com/2091-1706/200-000)



**Item no.2091-1726/200-000**  
THR pin strip; 1.0 mm Ø solder pin; angled; Pin spacing 3.5 mm; 6-pole; black

[www.wago.com/2091-1726/200-000](http://www.wago.com/2091-1726/200-000)



**Item no.2091-1426/200-604**  
THR male header; 1.0 mm Ø solder pin; angled; Pin spacing 3.5 mm; 6-pole; black



[www.wago.com/2091-1426/200-604](http://www.wago.com/2091-1426/200-604)

Subject to changes. Please also observe the further product documentation!

## Optional accessories


### Tool

#### Operating tool

|  |   |  |
|--|---|--|
|   | <b>Item no.: 2092-1630</b><br>Unlocking tool; orange  | <a href="http://www.wago.com/2092-1630">www.wago.com/2092-1630</a> |
|  | <b>Item no.: 210-719</b><br>Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft | <a href="http://www.wago.com/210-719">www.wago.com/210-719</a>     |

### Testing and measuring

#### Testing accessories

|  |   |  |
|--|---|--|
|  | <b>Item no.: 735-500</b><br>WAGO Test pin; 1 mm Ø; 30 V AC / 60 V DC; CAT0; 1 A; 6 mm uninsulated; Test lead for soldering up to 0,5mm <sup>2</sup> | <a href="http://www.wago.com/735-500">www.wago.com/735-500</a> |
|--|---|--|



### Coding

#### Coding

|   |   |  |
|---|---|--|
|  | <b>Item no.: 2091-1610</b><br>Coding key carrier; suitable for 3.5 mm pin spacing; orange | <a href="http://www.wago.com/2091-1610">www.wago.com/2091-1610</a> |
|---|---|--|

### Strain relief

#### Strain relief plate

|   |  |  |
|---|--|--|
|    | <b>Item no.: 2091-1602</b><br>Gripping plate; for female and male connectors; 1 part; Pin spacing 3.5 mm; light gray   | <a href="http://www.wago.com/2091-1602">www.wago.com/2091-1602</a>                 |
|  | <b>Item no.: 2091-1602/002-000</b><br>Gripping plate with sliding connector release; for female and male connectors; 2 parts; Pin spacing 3.5 mm; light gray | <a href="http://www.wago.com/2091-1602/002-000">www.wago.com/2091-1602/002-000</a> |

## Downloads

### Documentation

#### Additional Information

|                        |            |        |          |
|------------------------|------------|--------|----------|
| Technical Section      | 2019 Apr 3 | pdf    | Download |
| Technical explanations |            | 2.1 MB |          |

### CAD/CAE-Data

#### CAD data

|                        |     |          |
|------------------------|-----|----------|
| 2D/3D Models 2091-1126 | URL | Download |
|------------------------|-----|----------|

#### CAE data

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.

ZUKEN Portal 2091-1126

[URL](#)

[Download](#)

### Asset Administration Shell

Asset Administration Shell 2091-1126

[URL](#)

[Download](#)

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 2091-1126


[URL](#)

[Download](#)


1-conductor female connector; push-button; Push-in CAGE CLAMP®; 1.5 mm<sup>2</sup>; Pin spacing 3.5 mm; 6-pole; 1,50 mm<sup>2</sup>; light gray

## Installation Notes

### Locking system




Disconnecting a female connector via unlocking tool. Plug unlocking tool into the male header's locking latch.



Insert unlocking tool until it hits the backstop. Wedge opens locking latches.


Subject to changes. Please also observe the further product documentation!






Pull on both unlocking tool and conductors to remove female connector from male header.


### Conductor termination



Inserting fine-stranded conductor into mated female connector via push-button.



Inserting a fine-stranded conductor into an unmated female connector via push-button.



Inserting solid and ferruled conductors via push-in termination.


### Marking

Subject to changes. Please also observe the further product documentation!




Pole marking via factory direct marking.

### Coding



Coding a female connector (via coding key carrier and two keys for female connector, see symbol).

### Testing



Testing via 1 mm Ø test pin – touch contact.

Subject to changes. Please also observe the further product documentation!