RQ73C2B806RBTD <- ACTIVE

Holsworthy | Holsworthy RQ73

TE Internal #: 8-2176389-5 806 Ω, Thin Film, Precision Resistor, .1 %, 2 Termination, 1206, Taped & Reeled, .4 W, ±10 ppm/°C, Solder, Height .022 in [.55 mm], Holsworthy RQ73

View on TE.com >





Resistor Type: Precision Resistor

Number of Terminations: 2

Package Size Code: 1206

- Packaging Method: Taped & Reeled
- Passive Component Tolerance: .1 %

Features



Product Type Features

Resistor Type	Precision Resistor
Package Size Code	1206
Element Type	Thin Film
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Operating Voltage	200 V
Passive Component Tolerance	.1 %
Resistance Class	Up to 1kΩ
Resistance Value	806 Ω
Power Rating	.4 W
Termination Features	
Number of Terminations	2
Surface Mount Resistor Termination Type	Solder

RQ73C2B806RBTD

806 Ω, Thin Film, Precision Resistor, .1 %, 2 Termination, 1206, Taped & Reeled, .4 W, ±10 ppm/°C, Solder, Height .022 in [.55 mm], Holsworthy RQ73



Dimensions

Product Height	.55 mm[.022 in]
Product Length	3.05 mm[.12 in]
Product Width	1.55 mm[.061 in]
Usage Conditions	
Temperature Coefficient	±10 ppm/°C
Packaging Features	
Packaging Method	Taped & Reeled
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE

Does not contain REACH SVHC

2023 (235)

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

RQ73C2B806RBTD

806 Ω , Thin Film, Precision Resistor, .1 %, 2 Termination, 1206, Taped & Reeled, .4 W, ±10 ppm/°C, Solder, Height .022 in [.55 mm], Holsworthy RQ73







Also in the Series | Holsworthy RQ73



Surface Mount Resistors(3078)



Customers Also Bought



Documents

Product Drawings RQ 1206 806R 0.1% 10PPM 5K RL

English

CAD Files

3D PDF

3D

RQ73C2B806RBTD

806 Ω, Thin Film, Precision Resistor, .1 %, 2 Termination, 1206, Taped & Reeled, .4 W, ±10 ppm/°C, Solder, Height .022 in [.55 mm], Holsworthy RQ73



Customer View Model

ENG_CVM_CVM_8-2176389-5_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_8-2176389-5_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_8-2176389-5_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.