

MAG-MATE | MAG-MATE 300

TE Internal #: 62420-1 Magnet Wire Terminals, Poke-In, Size 2, 21 – 19 AWG Aluminum Wire, .41 – .65 mm Aluminum Wire, Lead Wire Size 20 – 18 AWG, MAG-MATE 300

View on TE.com >

Terminals & Splices > Magnet Wire Terminals



Magnet Wire Terminal Type: Poke-In Compatible With Cavity Size: Size 2 Aluminum Wire Size: .41 – .65 mm Lead Wire Size: 20 – 18 AWG

Features



Product Type Features	
Compatible With Discrete Wire Type	Magnet Wire, Solid
Body Features	
Compatible With Cavity Size	Size 2
Contact Features	
Magnet Wire Terminal Type	Poke-In
Terminal Plating Material	Tin
Terminal Orientation	Straight
Termination Features	
Termination Method to Wire & Cable	Insulation Displacement (IDC)
Mechanical Attachment	
Mating Retention Type	Barbs
Dimensions	
Terminal Height	7.87 mm[.31 in]
Aluminum Wire Size	.41 – .65 mm

62420-1

Magnet Wire Terminals, Poke-In, Size 2, 21 – 19 AWG Aluminum Wire, .41 – .65 mm Aluminum Wire, Lead Wire Size 20 – 18 AWG, MAG-MATE 300



Lead Wire Size	.81 – 1.02 mm²
Magnet Wire Size	.64 – .81 mm
Stock Thickness (Magnet Wire Side)	.41 mm[.016 in]
Product Length	7.62 mm[.3 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-20 – 105 °C[-4 – 221 °F]
Operation/Application	
Compatible With Wire Base Material	Aluminum, Copper
Identification Marking	
Identification Number	15
Packaging Features	
Packaging Quantity	12000
Packaging Method	Reel, Reel/Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Salder Dragon Canability	Not applicable for colder process capability

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent to these limits as defined in the Annexes of Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits

Magnet Wire Terminals, Poke-In, Size 2, 21 – 19 AWG Aluminum Wire, .41 – .65 mm Aluminum Wire, Lead Wire Size 20 – 18 AWG, MAG-MATE 300



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Also in the Series MAG-MATE 300



TE Part # 5-62420-1

Customers Also Bought



Magnet Wire Terminals, Poke-In, Size 2, 21 – 19 AWG Aluminum Wire, .41 – .65 mm Aluminum Wire, Lead Wire Size 20 – 18 AWG, MAG-MATE 300



TE		
TE Part #1740533-7 AMP DUOPLUG POW CONNECTOR	TE Part #2-284866-3 DUOPLUG SIDE LOCK., 3 POS, Sel load, 1/2	TE Part #293132-3 DUOPLUG 2.5 pitch, with External Walls

Documents

Product Drawings MAG-MATE TERM 20-22 016 TPBR

Japanese

MAG-MATE TERM 20-22 016 TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_62420-1_CE.2d_dxf.zip

English

Customer View Model ENG_CVM_CVM_62420-1_CE.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_62420-1_CE.3d_stp.zip

English

By downloading the CAD file I accept and agree to the $\ensuremath{\mathsf{Terms}}\xspace$ and $\ensuremath{\mathsf{Conditions}}\xspace$ of use.

Datasheets & Catalog Pages Magnet Wire Terminals & Splices

English

Product Specifications Application Specification

English

Instruction Sheets STD MAG-MATE INSERTION MODULE

Japanese