

### AMP | AMP MCP 1.5K, AMP MCP Connector System

TE Internal #: 1718490-1

Housing for Female Terminals, Wire-to-Wire, 9 Position, .157 in [4 mm] Centerline, Black, Signal, Cable Mount (Free-Hanging), Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > AMP MCP Unsealed Connector Housings











Connector System: Wire-to-Wire

Number of Positions: 9

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 4 mm [.157 in]

Sealable: No

All AMP MCP Unsealed Connector Housings (191)

## **Features**

## **Product Type Features**

Product Type Features	
Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	9
Number of Rows	1
Electrical Characteristics	
Operating Voltage	36 VDC

12 V, 24 V

Nominal Voltage Architecture



Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	A
Contact Features	
Contact Size	1.5K
Contact Type	Receptacle
Mating Tab Width	1.6 mm[.063 in]
Mechanical Attachment	
Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	4 mm[.157 in]
Dimensions	
Connector Height	4.2 mm[.165 in]
Product Width	23.5 mm[.925 in]
Product Length	37.2 mm[1.465 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F]
	•
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operating Temperature Range  Operation/Application	
Operation/Application	-40 – 120 °C[-40 – 248 °F]
Operation/Application  Circuit Application	-40 – 120 °C[-40 – 248 °F]
Operation/Application  Circuit Application  Industry Standards	-40 – 120 °C[-40 – 248 °F]  Signal
Operation/Application Circuit Application Industry Standards UL Flammability Rating	-40 – 120 °C[-40 – 248 °F]  Signal



#### Other

Serviceable	Yes
Connector Position Assurance Capable	No

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**














TE Part # 1-1670615-1
36POS,MIXED,HEADER ASSY,CONV.
KIT 25POS



TE Part # 1-1718492-3 1.5MM TAB HSG 36 POS ASSY



TE Part # 1-1718492-5
1.5MM TAB HSG 36 POS ASSY



TE Part # 1-2112891-5 36POS,TAB 1.5X0.6,TAB HSG,ASSY



TE Part # 1-2112891-6 36POS,TAB 1.5X0.6,TAB HSG,ASSY



TE Part # 1-2141847-4
CARRIER,RECEPTCALE HSG, 36POS,
ASSY



TE Part # 1-2364901-2 36POS. AMP MCP 1,5K, REC HSG ASSY, UNSLD



TE Part # 2-1670615-1 36POS,MIXED,HEADER ASSY,CONV. KIT 25POS

## Also in the Series | AMP MCP 1.5K



Automotive Connector Caps & Covers
(1)



Automotive Housings(94)



Automotive Terminals(3)




Insertion & Extraction Tools(1)

# Also in the Series | AMP MCP Connector System



Automotive Connector Caps & Covers (22)



Automotive Connector Locks & Position Assurance(6)



Automotive Housings(332)



Automotive Terminals(130)






Connector Seals & Cavity Plugs(7)



Insertion & Extraction Tools(13)



Other Automotive Connector Accessories(2)



PCB Headers & Receptacles(28)

## Customers Also Bought



TE Part #1-1718492-1

AMP MCP Unsealed Connector

Housings



TE Part #1-1718485-4

CARRIER FOR RECEPT INSERTS 36
POS



TE Part #1241374-1
AMP MCP 1.5K, CONTACT



TE Part #2819196-4 3 W ABS CABLE ASSY MBB 2.000

TE Part #3-2819195-2 2W ABS CABLE ASSY, 14.000 MM

TE Part #336363-3
TOP COVER, ISCS

## **Documents**

## **Product Drawings**

AMP MCP 1.5 RECEPT HSG 9 POS

English

#### **CAD Files**

Customer View Model

ENG\_CVM\_1718490-1\_A1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_1718490-1\_A1.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_1718490-1\_A1.2d\_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Housing for Female Terminals, Wire-to-Wire, 9 Position, .157 in [4 mm] Centerline, Black, Signal, Cable Mount (Free-Hanging), Hybrid



Product Specifications
Application Specification

German