

AMP | Superseal Pro

TE Internal #: 2345394-1

Receptacle, Cable-to-Cable, 4 Position, Sealable, Black, Wire & Cable, Power & Signal, Cable Mount (Free-Hanging), Superseal Pro

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings











Connector System: Cable-to-Cable

Number of Positions: 4

Connector & Housing Type: Receptacle

Sealable: Yes

Mating Tab Width: 2.8 mm [.109 in]

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Cable-to-Cable
Connector & Housing Type	Receptacle
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Locking Lance
Configuration Features	
Number of Positions	4
Number of Rows	1
Electrical Characteristics	
Nominal Voltage Architecture	50 V
Body Features	
Primary Product Color	Black



Connector	&	Kevina	Code
	\sim	1 C y II I G	COGC

Contact Features

Contact Size	2.8mm
Mating Tab Width	2.8 mm[.109 in]
Mating Pin Diameter	5 mm[.196 in]

Mechanical Attachment

Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Usage Conditions

Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Other

Connector Position Assurance Capable Yes	Connector Position Assurance Capable	Yes	
--	--------------------------------------	-----	--

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts






Also in the Series | Superseal Pro









Customers Also Bought













HYBRID 42P CAP ASSY BLK









TE Part #2345390-2 3POS,AMP MCP 2.8,REC HSG ASSY, SLD,COD 2 TE Part #3-1813099-1 2.5mm SOCKET HSG ASSEMBLY (GREEN 4POS)

Documents

Product Drawings

4POS,AMP MCP 2.8,REC HSG ASSY,SLD,COD 1

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2345394-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2345394-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2345394-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English