Potter & Brumfield | Potter & Brumfield KUP

TE Internal #: 8-1393117-9

Power Relays, Industrial Panel Plug-In, Monostable, AC, 2.9 VA Coil Power Rating AC, 7200 Ω Coil Resistance, Potter & Brumfield KUP

View on TE.com >



Relays & Contactors > Relays > Power Relays



Power Relay Type: Industrial Panel Plug-In
Coil Magnetic System: Monostable, AC
Coil Power Rating Class: [2-3 VA]
Coil Power Rating AC: 2.9 VA

Coil Resistance: 7200Ω

Features

Product Type Features

Troduct Type reduces	
Power Relay Type	Industrial Panel Plug-In
Electrical Characteristics	
Insulation Initial Dielectric Between Coil & Contact Class	1500 – 2500 V
Insulation Initial Dielectric Between Contacts & Coil	2200 Vrms
Actuating System	AC
Insulation Initial Dielectric Between Open Contacts	1200 Vrms
Contact Limiting Making Current	10 A
Contact Limiting Short-Time Current	10 A
Contact Limiting Continuous Current	10 A
Insulation Initial Dielectric Between Adjacent Contacts	2200 Vrms
Insulation Initial Resistance	100 ΜΩ
Contact Limiting Breaking Current	10 A
Coil Magnetic System	Monostable, AC
	2 – 3 VA
Coil Power Rating AC	2.9 VA
Coil Resistance	7200 Ω
Coil Special Features	Electrical Indicator, UL Coil Insulation Class B
Coil Voltage Rating	240 VAC



Contact Switching Load (Min)	300mA @ 12V
Contact Voltage Rating	240 VAC
Body Features	
Product Weight	85 g[2.988 oz]
Contact Features	
Contact Arrangement	3 Form C (CO)
Contact Current Class	16 A
Contact Current Rating (Max)	10 A
Contact Material	AgCdO
Contact Number of Poles	3
Relay Terminal Type	Quick Connect, Solder
Mechanical Attachment	
Relay Mounting Type	Socket
Relay Mounting Type Dimensions	Socket
	35 – 40 mm
Dimensions	
Dimensions Length Class (Mechanical)	35 – 40 mm
Dimensions Length Class (Mechanical) Height Class (Mechanical)	35 – 40 mm 40 – 50 mm
Dimensions Length Class (Mechanical) Height Class (Mechanical) Width Class (Mechanical)	35 – 40 mm 40 – 50 mm 30 – 40 mm
Dimensions Length Class (Mechanical) Height Class (Mechanical) Width Class (Mechanical) Product Width	35 – 40 mm 40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in]
Dimensions Length Class (Mechanical) Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length	35 – 40 mm 40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in]
Dimensions Length Class (Mechanical) Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length Product Height	35 – 40 mm 40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in]
Dimensions Length Class (Mechanical) Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length Product Height Usage Conditions	35 – 40 mm 40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in] 50 mm[1.97 in]
Dimensions Length Class (Mechanical) Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length Product Height Usage Conditions Environmental Ambient Temperature Class	35 – 40 mm 40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in] 50 mm[1.97 in]
Dimensions Length Class (Mechanical) Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length Product Height Usage Conditions Environmental Ambient Temperature Class Environmental Ambient Temperature (Max)	35 – 40 mm 40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in] 50 mm[1.97 in] 0 – 50 °C 45 °C[113 °F]
Dimensions Length Class (Mechanical) Height Class (Mechanical) Width Class (Mechanical) Product Width Product Length Product Height Usage Conditions Environmental Ambient Temperature Class Environmental Ambient Temperature (Max) Operating Temperature Range	35 – 40 mm 40 – 50 mm 30 – 40 mm 35.7 mm[1.405 in] 38.9 mm[1.55 in] 50 mm[1.97 in] 0 – 50 °C 45 °C[113 °F]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2023

(235)

Candidate List Declared Against: JUNE

2022 (224)

SVHC > Threshold:

Cadmium oxide (7.95% in Component Part)

Article Safe Usage Statements:

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts











Also in the Series | Potter & Brumfield KUP









Relay Accessories, Sockets & Clips(12)


Customers Also Bought



TE Part #9-1415018-1 SR6A4110 - V23050-A1110-A533



TE Part #87631-5 10 MODIV HSG COMP DR .100 POL



TE Part #1-640515-0 24P MR II CAP HSG V0





TE Part #2-1393118-7 KUP-14D35-24=KU



TE Part #7-1393246-4 W23-X1A1G-40=W23/W31



TE Part #53406-1 PIDG PVF2 R 22-16COM22-18MIL 6



TE Part #1379118-4 6POS MQS TAB





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_8-1393117-9_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_8-1393117-9_D.3d_igs.zip



English

Customer View Model

ENG_CVM_CVM_8-1393117-9_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

KUP Series Panel Plug-in Relay

English

Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

UL

English