ANT-2.4-WRT-MON-SMA V ACTIVE



TE Internal #: L9000106-01

Dome/Puck Antenna, Single Band, ISM / Zigbee / Bluetooth, External Mount, Panel, SMA, Omnidirectional, Single Port, Gain 0 <

3 dBi

View on TE.com >



Antennas



Wireless Application: Bluetooth, ISM, Zigbee

Mounting Location: External

Mounting Type: Panel

Antenna Termination: SMA Antenna Type: Dome/Puck

Features

Product Type Features

Antenna Product Type	Antenna
Antenna Termination	SMA

Configuration Features

Antenna Style	Dome
Mounting Location	External
Antenna Type	Dome/Puck
Band Type	Single Band
Port Configuration	Single Port

Electrical Characteristics

VSWR (Max)	<1.9:1
Impedance	50 Ω

Signal Characteristics

Gain (Max)	.8 dB
Frequency Band	2400 – 2485 MHz
Nominal Frequency Range	2400 – 2500
Peak Gain	0 < 3 dBi

Body Features

Product Weight	19.59 g[.691 oz]
\sim	

Dome/Puck Antenna, Single Band, ISM / Zigbee / Bluetooth, External Mount, Panel, SMA, Omnidirectional, Single Port, Gain 0 < 3 dBi



Mechanical Attachment	
Polarization	Linear
Mounting Type	Panel
Dimensions	
Cable Length	.21 m[.71 ft]
Product Width	19 mm[.75 in]
Product Length	26.8 mm[1.06 in]
Product Height	0 mm[0 in]
Operation/Application	
Antenna Environment	Outdoor
Directionality	Omnidirectional

Bluetooth, ISM, Zigbee

Bluetooth, ISM, Zigbee

Product Compliance

Wireless Application

Primary Application

Industry Standards

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous

Dome/Puck Antenna, Single Band, ISM / Zigbee / Bluetooth, External Mount, Panel, SMA, Omnidirectional, Single Port, Gain 0 < 3 dBi



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts





SMA Jack 50 Ohm PCB Through Hole





Customers Also Bought








TE Part #3-640440-4 04P MTA100 CONN ASSY 22AWG RED

















Documents

Dome/Puck Antenna, Single Band, ISM / Zigbee / Bluetooth, External Mount, Panel, SMA, Omnidirectional, Single Port, Gain 0 < 3 dBi



Product Drawings

Antenna 2.45GHz WRT Monopole SMA

English

Datasheets & Catalog Pages

Sub-6 Cellular LTE-5G NR Frequency Band Guide

English

2.4 GHz WiFi External Panel-Mount Antenna

English

Virtual Antenna

English

Microsplatch Ground Plane Optimization

English