



VEHICULAR 3-PORT MULTIBANDANTENNA VLT69273X11G

698-960 / 1710-2700 / 2300-2700 / 4900-6000 MHz + GPS ANTENNA

The Laird vehicular 3-port multiband antenna covers the 698-960/1710-2700 MHz, 2300-2700/ 4900-6000 MHz as well as GPS (1575.42 MHz) frequency ranges. Configured with 2-port, dual-band elements in addition to 1-port with integrated GPS. Connector options include SMA male connectors for 3G/4G LTE and GPS ports with an RSMA male connector for the WiFi port. The housing incorporates a low-profile, rugged design that meets IP67 standards. The antenna also features high impact, UV-resistant polycarbonate plastic available in black or white.

SPECIFICATIONS

PARAMETER	PERFORMANCE			
Model Number	VLT69273B11G-518A (Black)		VLT69273W11G-518A (White)	
No. of Ports	3 (1 port 3G/4G LTE, 1-port WiFi, 1-port GPS)			
	3G/4G Port		WiFi Port	
Frequency Bands (MHz)	698-960 MHz	1710-2700 MHz	2300-2700 MHz	4900-6000 MHz
Peak Gain * dBi	2.6	4.7	4.9	6.0
Max Gain +/- 30 above horizon	N/A	N/A	N/A	5.7
VSWR* Typical	< 1.9:1	< 1.6:1	< 1.6:1	< 1.6:1
VSWR * Max	< 2.0:1			
Port-to-Port Isolation	> 22 dB			
Nominal Impedance	50 Ohm			
Polarization	Vertical Linear			
Azimuth Beam Width	Omnidirectional			

*Measured on 1 ft. (30.48 cm) diameter ground plane

SPECIFICATIONS

PARAMETER	PERFORMANCE
Input Power, Max	50 Watt (ambient temp. of 25°C / 77°F)
Operating Temperature	-30° C to +70° C (-22°F to +158°F)
Dimensions (dia. x hgt)	132 mm x 75 mm (5.2" x 2.9")
Weight	0.74 kg (1.63 lb)
RF Connector	SMA-Male (3G/4G port) RSMA-Male (WiFi port)
Cable (exposed length)	LMR [®] -195 or equivalent- 518.2 cm (17 ft)
Radome / Baseplate Material	PC, UL94 - V0 Rating, UV Stable (Black & White)
Material Compliance	ROHS compliant
IP Dust & Water Ingress Rating	IP67

*Measured on 1 ft. (30.48 cm) diameter ground plane

GPS ANTENNA SPECIFICATIONS

PARAMETER	PERFORMANCE		
Frequency Band	1575.42 MHz (GPS L1)		
Band Width	6 MHz (Typical)		
Amplifier Gain	27 dB ± 3 dBc		
Nominal Impedance	50 Ohm		
Output VSWR	< 1.5:1		
DC Voltage	2.7 - 12 Vdc		
DC Current	20 mA (Nominal); 30 mA (-40°C - +85°C)		
Out-of-Band Signal Rejection	> 40 dB rejection @ ± 50 MHz from center frequency		
Intermodulation@ CW Mode (-40°C - +85°C)	Int1	Int2	IM3
Power, dBm	-10(1842.8 MHz)	-10(2110 MHz)	-100(1575.6 MHz)
Power, dBm	-10(829.58 MHz)	-10(2405 MHz)	-100(1575.42 MHz)
Power, dBm	-10(755.42 MHz)	-10(820 MHz)	-100(1575.42 MHz)
Input 1 dB Compression @ 750 MHz, 2000 MHz & 3500 MHz	> 10 dBm (-40°C - +85°C)		
RF Connector	SMA-Male		
Cable (exposed length)	RG174-518.2 cm (17ft)		

PART NUMBER	
VLT69273B11G-518A	1-Port 4G/LTE, 1-Port GPS: SMA Male; 1 Port WiFi:RSMA Male(Black)
VLT69273W11G-518A	1-Port 4G/LTE, 1-Port GPS: SMA Male; 1 Port WiFi:RSMA Male(White)

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use.

TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

©2021 TE Connectivity. All Rights Reserved.

11/21 Original

