

Part Number: 1200680190

**Product Description :** Micro-Change (M12) In-Line Splitter, 4 Pole, 1 x 4-Pole Male (Straight) to 2 x 3-Pole Female (Straight), 22 AWG PVC

Cable, 1.0m Length

Status: Active

Engineering Number: 884A30K03M010

Series Number: 120068

**Product Category:** Industrial Tees and

Splitters

#### **Documents & Resources**

### **Drawings**

Drawing 1200680190\_sd.pdf

## **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>6</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Contains Lead per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

## **Part Details**

## General

Status	Active
Category	Industrial Tees and Splitters
Series	120068
Description	Micro-Change (M12) In-Line Splitter, 4 Pole, 1 x 4-Pole Male (Straight) to 2 x 3-Pole Female (Straight), 22 AWG PVC Cable, 1.0m Length
IP Rating	IP67
Product Family	Brad Micro-Change (M12) Connectors
Product Name	Micro-Change (M12)
Туре	Splitter - In-line
UPC	78678845021

# Agency

CSA	LR6837
UL	E152210

## Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC

# Physical

Color - Cable Jacket	Yellow
Drop Connector	N/A
Drop Gender	N/A
Keyway	Single
LED Indicator	No
Left Trunk Connector	Micro-Change (M12)
Left Trunk Gender	Male
Leg 1 Length	1.0m
Leg 2 Length	1.0m
Material - Cable Jacket	TPE

Material - Connector Body	TPE
Material - Coupling Nut	Nickel-plated Brass
Net Weight	232.828/g
Poles	3 Female/4 Male
Right Trunk Connector	Micro-Change (M12)
Right Trunk Gender	Female
Temperature Range - Operating	-30°C TO +80°C

This document was generated on Apr 11, 2024